

HARDWARE FEATURES	
Processor	Qualcomm Atheros Enterprise 560MHz CPU, MIPS 74Kc
Memory	64MB DDR2 RAM, 8MB Flash
Interface	1 10/100Mbps Shielded Ethernet Port (Passive PoE in) 1 Grounding Terminal 1 Reset Button
Power Supply	Passive Power over Ethernet via LAN0 (+4,5pins; -7,8pins) Voltage range: 16-27VDC
Power Consumption	10.5 Watts Max Note: When deployed using Passive PoE, the power drawn from the power source will be higher by some amount depending on the length of the connecting cable.
Dimensions (W x D x H)	8.8 x 3.1 x 2.4 in
Antenna Type	Built-in 13dBi 2 x 2 Dual-polarized Directional Antenna Beam Width: 45° (H-Plane) / 30° (E-Plane) Note: For more details, please refer to datasheet
Protection	15KV ESD Protection 6KV Lightning Protection
Enclosure	Outdoor ASA stabilized plastic material IPX5 waterproof Certification
WIRELESS FEATURES	
Wireless Standards	IEEE 802.11a/n (with Pharos MAXtream disabled)
Proprietary Protocol	TDMA Mode (with Pharos MAXtream enabled)
Wireless Speeds	Up to 300Mbps (40MHz,Dynamic) Up to 144.4Mbps (20MHz,Dynamic) Up to 72.2Mbps (10MHz,Dynamic) Up to 36.1Mbps (5MHz,Dynamic)
Frequency	5.15~5.85GHz Note: Available operating frequency may vary depending on the limitations of the countries or regions in which the device is used.
Transmission Power	23dBm/200mw (Adjustable power by 1dBm) Note: Maximum transmission power may vary across different channels depending on the limitations of the countries or regions in which the device is used.
SOFTWARE FEATURES	

SOFTWARE FEATURES

Wireless Configurations	Pharos MAXtream TDMA Technology 802.11a/n Modes Selectable Channel Width: 5/10/20/40MHz Automatic Channel Selection Transmission Power Control Dynamic Frequency Selection (DFS) WDS Enable/Disable Security: WPA/WPA2, WPA-PSK/WPA2-PSK (AES/TKIP) Encryption, 64/128/152-bit WEP Encryption SSID Broadcast Enable/Disable Multi-SSID with VLAN Tagging (AP mode only) Distance/ACK Timeout Setting Wireless MAC Address Filter Wireless Advanced: > Beacon Interval/RTS Threshold/Fragmentation >Threshold/DTIM Interval/AP Isolation/Short GI/Wi-Fi Multimedia
Management	Discovery and Remote Management via Pharos Control application HTTP/HTTPS Web-based management System Log SNMP Agent(v2c) Ping Watch Dog Dynamic DDNS SSH Server
System Tools	Wireless Signal Quality Indicators: Signal Strength/Noise/Transmit CCQ/CPU/Memory Monitors: Throughput/Stations/Interfaces/ARP/Routes/WAN/DHCP Spectrum Analyzer Speed Test Ping Traceroute
System-level Optimizations	Optimized IGMP Snooping/Proxy for multicast applications Hardware watch dog

POE ADAPTER FEATURES

Dimensions(W x D x H)	4.3 x 2.2 x 1.3 in
Interfaces	1 AC Jack with Earth Ground 1 10/100Mbps Shielded Ethernet Port (Power + Data) 1 10/100Mbps Shielded Ethernet Port (Data)
Button	Remote Reset Button
Power Status LEDs	Green
Input	100-240VAC, 50/60Hz
Output	24VDC, 1.0A Max +4, 5pins; -7, 8pins. (Support up to 60m Power over Ethernet)
Efficiency	>80%
Certifications	CE/FCC

OTHERS

Certification	FCC, RoHS, IPX5
---------------	-----------------

OTHERS

Package Contents	Outdoor Wireless CPE 24V 1A Passive PoE Adapter Pole Mounting Straps AC Power Cord Installation Guide
System Requirements	Google Chrome, Safari, and Firefox browsers for web GUI management
Environment	Operating Temperature: -30°C~70°C (-22°F~158°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing

About Us

Corporate Profile
Contact Us
Careers at TP-Link
Privacy Policy

Press

News
Awards
Security Advisory

Partners

Partner Program
Training & Certifications
Deal Registration

Subscription ⓘ

 Email Address

Follow Us



United States / English

Copyright © 2019 TP-Link Technologies Co., Ltd. All rights reserved.