

3G/4G Routers TL-MR6400		Overview	Specifications	Support
HARDWARE FEATURES				
Interface	3 10/100Mbps LAN Ports, 1 10/100Mbps LAN/WAN Port, 1 Micro SIM Card Slot			
Button	WPS/Reset Button, Wireless On/Off Button, Power On/Off Button			
External Power Supply(EU)	9V/0.85A			
External Power Supply(APAC)	12V/1A			
Dimensions (W x D x H)	7.95 x 5.71 x 1.34 in. (202 x 145 x 34 mm)			
Antenna Type	V3/APAC: 2 Internal 4G LTE Antennas V4/V2/V1: 2 Detachable 4G LTE Antennas			
Compatibility	NBN - Fibre to the Premises (FTTP) - Wireless Router Mode. NBN - Fibre to the Home (FTTH) - Wireless Router Mode. For further information on NBN connections please visit: http://www.nbnco.com.au/learn-about-the-nbn/network-technology.html			
WIRELESS FEATURES				
Wireless Standards	IEEE 802.11b/g/n 2.4GHz			
Frequency	2.4GHz			
Signal Rate	300Mbps at 2.4GHz			
Reception Sensitivity	11g 54M: -74dBm 11n HT20: -71dBm 11n HT40: -67dBm			
Transmit Power	CE: <20dBm(2.4GHz)			
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics			
Wireless Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions			
Network Type (V3)	4G: FDD-LTE B1/B3/B7/B8/B20 (2100/1800/2600/900/800MHz) TDD-LTE B38/B39/B40/B41 (2600/1900/2300/2500MHz) 3G: DC-HSPA+/HSPA+/HSPA/UMTS B1/B8 (2100/900MHz)00MHz)			
Network Type(APAC V3)	4G: FDD-LTE B1/B3/B5/B7/B8/B20/B28 (2100/1800/850/2600/900/800/700MHz) TDD-LTE B38/B39/B40/B41 (2600/1900/2300/2500MHz) 3G: DC-HSPA+/HSPA+/HSPA/UMTS B1/B5/B8 (2100/850/900MHz)z)			
Network Type				
SOFTWARE FEATURES				
Operating Modes	3G/4G Router, Wireless Router			

SOFTWARE FEATURES

Management	Access Control, Local Management, Remote Management reboot schedule
WAN Connection Type	Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, NO-IP
VPN	PPTP VPN, IPSec VPN , OpenVPN
Access Control	Parental Control, Local Management Control
Firewall Security	DoS, SPI Firewall, IP Address Filter/Domain Filter, IP and MAC Address Binding
Protocols	Supports IPv4 and IPv6
Guest Network	2.4GHz guest network x 1

OTHERS

Certification	CE, RoHS
Package Contents	300Mbps Wireless N 4G LTE Router, TL-MR6400 RJ45 Ethernet Cable Power Adapter Quick Installation Guider
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browsers or higher, or other Java-enabled browsers SIM Card
Environment	Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Warranty	Limited 3-Year Warranty For further information on our warranty policy please visit: http://www.tp-link.com.au/support/rma

About Us

Corporate Profile
Contact Us
Privacy Policy

Press

News
Awards
Security Advisory
Upcoming Exhibitions

Where to Buy

Distributor
Retail
Reseller
ISP
Online Stores

Partners

Partner Program
Technology Library
Deal Registration

Promotions

Join TP-Link Community

Email Address

Follow Us

Australia / English

Copyright © 2019 TP-Link Technologies Co., Ltd. All rights reserved.