

# Datasheet FUJITSU Image Scanner fi-7240

The essential fi Series scanner with exceptional business performance



The fi-7240 scans A4 portraits at 40 ppm/80 ipm (200/300 dpi), loads up to 80 sheets at a time, and ensures utmost efficiency with amazing scanning performance.

### Assistance for safe and reliable scanning

The fi-7240 possesses diverse stable paper feeding mechanisms, ensuring speedy and high quality scanning without relying on PC performance. Minimize risk of document damage with Paper Protection function monitoring paper feed distance. And bid farewell to missing edges with the scanner's Skew Reducer mechanism. Potential information loss, resulting from multiple sheets being fed through the scanner at once, is also no longer an issue with Ultrasonic Multi-feed detection.

## Boosted usability with a user-friendly and versatile design

Equipped with a built-in flatbed, this scanner can scan fragile documents and thick books, impossible to scan with ADF. Scan a wide variety of paper (27 to 413 g/m²), as well as plastic cards, utilizing its straight paper feeding path, with a single push of a button. Daily maintenance tasks, including interior cleaning and roller replacement, can also be done with ease for long-lasting utilization.

## High quality images in any condition

Enjoy sharp, high quality images with the fi-7240's CCD image sensors. Subtle changes in scanning environment, such as in air temperature and LED illumination, are also no longer a need for concern with the scanner automatically changing background colors to maintain consistently crisp images.

## Advanced software for maximized efficiency

Bypass the inconvenience of making fine adjustments to OCR settings with the PaperStream IP scanner driver, supporting both TWAIN and ISIS. The software automatically converts scanned images into exceptionally clean images, supporting OCR accuracy even when scanning documents with background patterns or wrinkled and soiled documents. Seamlessly linked to Paper-Stream IP, PaperStream Capture effectively and efficiently feeds information into your organization workflow with its various batch scanning capture features. Automatically utilizing data extracted from barcodes and patch codes, the software also determines your preferred saving destinations and eliminates time allocated to routine tasks.

### **Technical Information**

icciiiica			
Scanner Type		ADF (Automatic Document Feeder) / Flatbed, Duplex	
Scanning Speed*1 (A4 Portrait) (Color*2/Grayscale*2/Monochrome*3)		ADF Simplex: 40 ppm (200/300 dpi)	
		Duplex: 80 ipm (200/300 dpi) Flatbed 1.7 seconds (200 dpi)	
Image Sensor Type		Color CCD x 3 (front x 1, back x 1, Flatbed x 1)	
Light Source		White LED Array x 3 (front x 1, back x 1, Flatbed x 1)	
Optical Resolution		600 dpi	
Output Resolution*4 (Color / Grayscale / Monochrome)		50 to 600 dpi (adjustable by 1 dpi increments), 1,200 dpi (driver)*5	
Output Format		Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit	
Background Colors		ADF: White / Black (selectable) Flatbed: White (or optional black)	
Document	Size		
ADF	Maximum*6	216 x 355.6 mm (8.5 x 14 in.)	
	Minimum* <sup>7</sup>	50.8 x 54 mm (2 x 2.1 in.)	
	Long Page Scanning*8	5,588 mm (220 in.)	
Flatbed	Maximum	216 x 297 mm (8.5 x 11.7 in.)	
Paper Wei	ght (Thickness)*9		
Paper		27 to 413 g/m² (7.2 to 110 lb)*10	
Plastic Card		1.4 mm (0.055 in.) or less (ADF)*11	
ADF Capacity*12*13		80 sheets (A4 80 g/m² or Letter 20 lb)	
Expected Daily Volume*14		6,000 sheets	
Multifeed Detection		Overlap detection (Ultrasonic sensor), Length detection	
Paper Protection		Lag detection	
Interface		USB 2.0 / USB 1.1	
Power Requirements		AC 100 to 240 V ±10 %	
Power Consumption			
Operating Mode		39 W or less	
Sleep Mode		1.8 W or less	
Auto Standby (Off) Mode		0.35 W or less	

5 to 35 ℃	5 to 35 °C (41 to 95 °F)	
20 to 80%	(non-condensing)	
ENERGY S	TAR®, RoHS	
300 x 577	x 234 mm (11.8 x 22.7 x 9.2 in.)	
8.8 kg (19	0.4 lb)	
Windows® 3 Windows Se (64-bit), Wi 2008 R2 (64	10 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit), 7 (32-bit/64-bit), Windows Server® 2019 (64-bit), rrver® 2016 (64-bit), Windows Server® 2012 R2 indows Server® 2012 (64-bit), Windows Server® 4-bit), Windows Server® 2008 (32-bit/64-bit), ntu)*1547	
PaperStrear Software Op	m IP Driver (TWAIN/TWAIN x64/ISIS), WIA Driver <sup>*17</sup> , m Capture, ScanSnap Manager for fi Series <sup>*18</sup> , peration Panel, Error Recovery Guide, ABBYY for ScanSnap <sup>™*18</sup> , Scanner Central Admin	
detection, E Error diffusi (None/Red/ output, Hol De-Skew, Ed	e output, Automatic color detection, Blank page Dynamic threshold (iDTC), Advanced DTC, SDTC, on, Dither, De-Screen, Emphasis, Dropout color Green/Blue/White/Saturation/Custom), sRGB e punch removal, Index tab cropping, Split image, dge filler, Vertical streaks reduction, Cropping, hold, Moire removal	
ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM		
PA03670-D801	Black flatbed background pad	
PA03360-0013	Each package contains 5 carrier sheets	
PA43404-A433	Reads PDF417, QR code, Data Matrix, Aztec Code	
PA43404-A665	PaperStream Capture Pro optional license	
3670-0001	Every 200,000 sheets or one year	
3670-0002	Every 200,000 sheets or one year	
	20 to 80% ENERGY S  300 x 577  8.8 kg (19  Windows® Windows® Windows® Windows® (64-bit), W 2008 R2 (6- Linux (Ubu)  PaperStrear PaperStrear PaperStrear Software Op FineReader  Multi image detection, Error diffusi (None/Red/ output, Holl De-Skew, Er Static thres  ADF pape Setup DVI  PA03670-D801  PA03360-0013  PA43404-A433	

\*1 Actual scanning speeds are affected by data transmission and software processing times. \*2 Indicated speeds are from using JPEG compression. \*3 Indicated speeds are from using TIFF CCITT Group 4 compression. \*4 Selectable maximum density may vary depending on the length of the scanned document. \*5 Limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). \*6 Scans folded documents of up to 297 x 432 mm (11.7 x 17 in.) with carrier sheet scanning. \*7 Scanning area limitations only apply when using the ADF. There are no limitations when using the flatbed. \*8 Capable of scanning documents longer than A4 (210 x 297 mm / 8.3 x 11.7 in.) sizes. When using PaperStream IP (TWAIN/ISIS) to scan at 200 dpi, the maximum scanning length is 5,588 mm (220 in.). \*9 Paper weight limitations only apply when using the ADF. There are no limitations when using the flatbed. \*10 Thicknesses of up to 127 to 209 g/m² (34 to 56 lb) can be scanned for A8 (52 x 14 mm / 2.1 x 2.9 in.) sizes. \*11 Capable of scanning up to 3 cards at a time (Note: does not set more than one embossed card at a time). \*12 Maximum capacity depends on paper weight and may vary. \*13 Capable of setting additional documents while scanning. \*14 Numbers are calculated using scanning speeds and typical hours of scanner use, and are not meant to guarantee daily volume or unit durability. \*15 Excludes the ADF paper chute and stacker. \*16 Availability of support may vary depending on region. \*17 Functions equivalent to those offered by PaperStream IP may not be available with the Image Scanner Driver for Linux and WIA Driver. \*18 Software can be downloaded from the website designated in the Setup DVD-ROM.

ABBYYM Spreader Engine © ABBYY. OCR by ABBYY. ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

Safety Precautions
Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings. ENERGY STAR®

PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

Specifications are subject to change without notice. Visit the fi Series website for more information. http://imagescanner.fujitsu.com/

## Contact