

NEO PLUS DRAFTING

ASSEMBLY INSTRUCTIONS

pago



STEP 1

Insert castors into base



STEP 2

Insert gas cylinder into base



STEP 3

Base with gas inserted



STEP 4

insert drafting ring over gas as shown
base assembly complete



STEP 5

Seat assembly leave elastic in place This keeps the two sections of the back bellow in place



STEP 6

Back assembly



STEP 7

Insert back assembly firmly into mechanism Push all the way until the back bottoms out The ratchet height adjuster works like a car head rest Press all the way down then lift up to required position

When back is in place remove elastic band



push stem through hole to desired back height. Tighten with knob



STEP 9

Chair assembly complete



STEP 10

insert 4 into 9
insert **base assembly** into **chair assembly**

NEO PLUS DRAFTING

ASSEMBLY INSTRUCTIONS

pago



STEP 1

Insert castors into base



STEP 2

Insert gas cylinder into base



STEP 3

Base with gas inserted



STEP 4

insert drafting ring over gas as shown
base assembly complete



STEP 5

Seat assembly leave elastic in place This keeps the two sections of the back bellow in place



STEP 6

back assembly



STEP 7

Insert back assembly firmly into mechanism Push all the way until the back bottoms out The ratchet height adjuster works like a car head rest Press all the way down then lift up to required position

When back is in place remove elastic band



Step 8 push stem through hole to desired back height. Tighten with knob



STEP 9

Chair assembly complete



STEP 10

insert 4 into 9
insert **base assembly** into **chair assembly**