Panasonic ideas for life

Panasonic

electronic board

UB-5325 UB-5825 UB-7325

Panaboard[™]

Metallic Type

MARKET TREND

Plain Paper Printing



USB Interface

Microsoft®

Windows Vista™,

Windows® XP,

Windows® 2000,

Windows® Me,

Windows® 98

operating systems

Used for

Seminars

Meetings

Brain Storming


Scheduling

Training

Improves your Presentations and meetings Panaboard UB-5325, UB-5825, UB-7325

- Our range of Panaboards come with an integral printer for easy-operation.
- Plain paper printing with multiple copies.
- Panaboard can work as a PC printer.
- Panaboard can be controlled from PC.
- Panaboard keeps 100% audience attention and increases participation.
- Panaboard increases efficiency and reduces meeting time.
- Panaboard can be wall-mounted or used with floor-stand option.

PC Interface



Panaboard UB-5325, UB-5825 and UB-7325 come with utility software that consists of Document Manager and Document

Panasonic Document Management System


Viewer. The meeting contents on the Panaboard screen will become meeting minutes with some annotation by Document Viewer function. The Document Manager makes it easy to file and distribute the meeting minutes quite easily. Supported saving file format is BMP, TIFF, JPG, PNG and PDF.

> The scanned image is monochrome. The annotation function is used to make the coloured text.

Printer Driver

The Panaboard can also work as a PC printer. In a meeting, if you need to print out some documents, the Plug & Play of USB makes it easy to print out documents from the Panaboard.







1 Screen can also be used for the Projector. (UB-7325)

TWAIN Driver				
Panaboard-UBS USB TWAIN Drive	9(x)			
<u> </u>				

By just one click, you can scan the image on the Panaboard screen as image data to your computer and from your computer, you can control the

Panaboard function just like operating the Panaboard control panel.

Specifications						
<u> </u>	Model number	LID 5005	LID FOOF	UB-7325		
General	Model number	UB-5325	UB-5825	0		
Power Supply	- (Oneretional)	AC 100 - 120 V, 50/60 Hz or AC 220 - 240 V, 50/60 Hz				
Power Consumption (Operational) External Dimensions (Height X Width X Depth, without stand)		1.40 A (AC 100 - 120 V) or 0.75 A (AC 220 - 240 V)				
		1,396 mm X 1,550 mm X 230 mm 36.0 kg	1,396 mm X 1,912 mm X 230 mm 38.5 kg	1,396 mm x 1,648 mm x 264 mm 42.5 kg		
Weight (without stand) Input Block)	30.0 kg	36.3 kg	42.5 Kg		
Panel Dimensions (I	Haiselet V Miliate	900 mm X 1.400 mm	000 V 4 700	000 mm V 4 400 mm		
Panel Surface	Height X Width)	,	900 mm X 1,762 mm	900 mm X 1,400 mm 4 (endless type)*1		
Copying Area (Heic	alat V Milatta	2 (endless type)		` ', ',		
1, 0 , 0	gnt X Wiatn)			850 mm X 1,330 mm		
Scanning System			Image sensors			
Output Block						
Printing System		Fusion thermal transfer type				
Copy Paper		Standard or recycled paper (60-90 g/m ²)				
Copy Paper size		A4 or Letter				
Copy Density		203 dpi (8 dots/mm)				
Copy Color		Black				
Time Required for C		15 sec./sheet				
Continuous Copies		1 to 9				
Contrast Adjustmen		Two levels : Normal/Dark				
2-screen Compress	17 0		Yes	No		
System Require	ements					
Computer		IBM® PC/AT or compatible machine with a CD-ROM drive				
CPU		Pentium® II or higher processor				
Interface		USB 1.1 or USB 2.0 (This electronic board functions with USB 1.1.)				
Operating System		Windows Vista™ (32 bits)*2, Windows® XP, Windows® 2000, Windows® 98, Windows® Me				
Memory		Windows® 98/Me: 64 MB or more, Windows® 2000: 128 MB or more,				
		Windows® XP: 256 MB or more, Windows Vista™: 512 MB or more				
Hard Disk		At least 240	MB free space (except saving space for	image file)		
Accessories						
		Operating instructions, Installation manA4 or Letter Size Paper for test (20 sheet)	ual • Power Cord • Markers (black, interpretable) • Thermal Transfer Film (10 m)	red and blue, one each) • Software CD-ROM • Eraser (one po		
Optional Equipr	ment					
Wall-Mounting Kit		KX-B063				
		KX-B061				
Stand						
Stand Separately Avai	ilable					
Separately Avai	ilable		UG-6001 (Set of 2 rolls [50 ml)			
	ilable	KX-R031 (set of 10 black mark	UG-6001 (Set of 2 rolls [50 m]) ers). KX-B032 (set of 10 red markers). KX	(-B033 (set of 10 blue markers)		
Separately Avai Replacement film	ilable	KX-B031 (set of 10 black mark	UG-6001 (Set of 2 rolls [50 m]) ers), KX-B032 (set of 10 red markers), KX KX-B042 (set of 6 erasers)	(-B033 (set of 10 blue markers)		

- Screen can also be used for the Projector.
- Please download the latest printer driver and application for

Windows Vista™ from the following web site: http://panasonic.co.jp/pcc/products/en/eboard/download/index.html



Note:

- Microsoft, Windows and Windows Vista are either registered trademarks or
- trademarks of Microsoft Corporation in the United States and other countries.

 Windows is Microsoft® Windows® operating system.

 IBM is a registered trademark of International Business Machines Corporation.
- Pentium is a registered trademark of Intel Corporation in the U.S. and other countries. All trademarks referred to in this catalog are property of their respective companies.

http://panasonic.co.jp/pcc/en/ http://www.panasonic.co.jp/global



UB-5325 2-Screen Standard size





UB-7325 reen Standard size

(Stand option)