



KEY FEATURES

700c alloy flat bar road frame with comfort road geometry

Lightweight alloy fork with alloy steer tube

Lightweight wheels with alloy hubs, with Weinmann double wall rims

Kenda 700c x 28c fast rolling road tyres

21 speed Shimano EZ-fire shifting with cassette

Selle Royal saddle for maximum riding comfort

Powerful Promax mini V-Brakes

Apollo custom comfort grip

GEOMETRY	S	M	L	XL
STACK	553	574	593	614
REACH	397	415	424	437
STAND OVER HEIGHT	406	439	462	486
EFFECTIVE TOP TUBE	555	585	605	625
SEAT TUBE (CENTRE TO TOP)	450	500	530	560
SEAT ANGLE	74.0°	73.5°	73.0°	73.0°
HEAD TUBE LENGTH	130	150	170	190
HEAD ANGLE	72.0°	72.5°	72.5°	73.0°
WHEEL BASE	1030	1050	1065	1075
CHAIN STAY LENGTH	430	430	430	430
BB DROP	70	70	70	70
FORK RAKE	50	50	50	50
AXLE TO CROWN	397	397	397	397
REAR DROPOUT SPACING	130	130	130	130

SPECIFICATIONS

FRAME	Butted 6061 aluminium frame with integrated head tube, pannier mounts and replaceable forged derailleur hanger	HEADSTEM	Alloy 4 bolt stem, bore: 31.8mm L: S=75mm, M/L=90mm, XL=105mm	CHAIN	KMC Z-51
FORK	Full alloy ovalised straight blades with rack mounts	CRANKSET	Alloy crank with 48 x 38 x 28T L: S/M/L/XL=170mm	BRAKES	Mini alloy linear pull calipers
HEADSET	A-head semi integrated 1-1/8" with 10mm cone spacer	BOTTOM BRACKET	Cartridge bottom bracket	WHEELS	700c custom Weinmann X-M1 32 hole double wall A/V rims, alloy hubs and stainless spokes.
HANDLEBAR	Alloy flat bar, bore: 31.8mm, W: 580mm, sweep: 5°	PEDALS	High impact resin	TYRES	Kenda 700 x 28c wire bead
GRIP	Kraton ERGO comfort grip	F. DERAILLEUR	Shimano TX-800 top pull for 31.8mm	SADDLE	Factor Ergotech saddle
		R. DERAILLEUR	Shimano TY-300 7 speed	SEATPOST / CLAMP	Alloy 27.2mm micro adjust
		SHIFT LEVERS	Shimano EF-41 Ez Fire 21 speed	EXTRAS	N/A
		CASSETTE	Shimano 7 speed cassette 12-28T		