FORTEC AUSTRALIA

HEAD OFFICE
108 Motivation Drive
Wangara WA 6065
T 08 6267 2370
info@fortecaustralia.com.au

BRISBANE
6/15 Motorway Circuit
Ormeau QLD 4208
T 07 3106 4220

SYDNEY
Level 5, 35 Saunders Street
Pyrmont NSW 2009
T 02 8318 4311

TPH. waterproofing systems

Production
TPH Bausysteme GmbH
Nordportbogen 8 · 22848 Norderstedt · Germany
Phone + 49 (0) 40 / 52 90 66 78 - 0
www.tph-bausysteme.com

FORTEC AUSTRALIA

TPH. waterproofing systems

Sealing systems and upgrate solutions for fresh and waste water structures

Sealing of expansion joints

PROOFMATE® EK
Box profile based on EPDM

FIX-O-FLEX
Mastic adhesive and sealing compound based on SPPO

Stopping of water inrush

PUR-O-STOP FS-L + FS-C
Slowly curing, from ridged to tough elastic, 2C polyurethane resin, which foams up in contact with water.

Emscher sewer (D)

Manhole cover sealing

HYDROPOX FLEX F
Flexible PC fine mortar based on epoxy resin.
Max. grain size: 0.7mm

- for bonding and sealing of manhole covers
- for bonding and sealing of pipe breakthroughs
- for bridges or other dynamically burdened places

Coatings

HYDROPOX EPG-T
Coating based on EP for all kind of concrete surfaces.

- High resistance against abrasion
- High resistance against chemicals
- Very high UV resistance
- High resistance against farmyard waste processing facilities

Sealing crack injection

PUR-O-CRACK
2C-injection resin based on polyurethane

- Officially approved system
- Proven against water pressure of 7 bars
- Approved for use in CHF plants
- listed in BASt

Annulus gap grouting

RUBBERTITE®
Very low viscous 3C acrylate gel, multi purpose applicable

- Very good penetration, even in water filled cracks
- Long term stable. Proven stability of at least 16 years



Sealing even under water

PROOFMATE® FD
Sealing membrane based on EPDM
Thickness: 1 mm.



PROOFMATE® F
Mastic adhesive and sealing compound based on SPPO

Hydrophobizing treatments

AQUAPROTECT®
Silane based solvent free protection for hydrophobic purposes.

- Impregnation purposes against water, chlorides, deicing salt and bases

Crack bridging:

- water proof up to 0.15mm
- rain water proof up to 0.20mm