

Machinery

Product Catalogue

2019



GLOBAL
INDUSTRIAL

Machinery



Plate compactors

MODEL	MT0090	MT0105
WEIGHT	65kg	87kg
PLATE SIZE	510 x 370mm	590 x 435mm
COMPACTING DEPTH	200mm	300mm
FREQUENCY	5600rpm	7000rpm
HANDLE	Foldable	Flip over & foldable
ENGINE BRAND	Loncin	
ENGINE POWER	6.5hp / 4.8kW	
FUEL TYPE	Petrol	
FUEL TANK SIZE	3.6L	



Slip-on fire unit

MODEL	MP1200
PUMP	Model MP0120 – 300L/min, 6.5hp petrol pump
TANK SIZE	600L
HOSE REEL	30m
FIRE NOZZLE	Fan to stream variable flow nozzle
SKID SIZE	2100mmL x 860mmD



50mm petrol fire fighting pumps

MODEL	MP0120	MP0130
IMPELLER	Single impeller	Twin impeller
WEIGHT	26kg	26kg
OUTLET SIZES	40mm / 25mm / 25mm	
INLET SIZE	50mm	
WATER FLOW	300L/min	
SUCTION	6m	
MAX HEAD	55m	75m
ENGINE POWER	6.5hp / 4.8kW	
FUEL TYPE	Petrol	
FUEL TANK SIZE	3.6L	

Surface cleaner



MODEL	MPWAF2201
MAX PRESSURE	4000psi (27Mpa)
WATER VOLUME	minimum volume 11 L/min
WATER TEMPERATURE	Cold to 82°C
CONSTRUCTION	Stainless steel
SPRAY DIAMETER	52cm
CONNECTION	Quick coupler





3000PSI & 4000PSI pressure washer

MODEL	MPW0050	MPW0055	MPW0058	MPW0060
OPERATING PRESSURE	2700psi		3600psi	
MAX PRESSURE	3000psi		4000psi	
WATER FLOW	10L/min		15L/min	
PUMP BRAND	AR (Italy)			
PUMP TYPE	Axial		Triplex	
ENGINE BRAND	Lifan			Briggs & Stratton
FUEL TYPE	Unleaded petrol			
ENGINE POWER	7hp		13hp	
STARTING SYSTEM	Recoil start		Electric start & recoil start	
STANDARD NOZZLES	4 different spray nozzles			
TURBO NOZZLE	Included			
HOSE LENGTH	15m			30m reel
BASE	2 wheel trolley			4 wheel trolley
DETERGENT INJECTION LINE	Included on all models			



Used Denyo & Airman air compressors

MODEL	Airman 50CFM	Airman 70CFM	Denyo 70CFM	Airman 90CFM	Denyo 90CFM	Airman 125CFM	Denyo 130CFM
AIR DELIVERY	50CFM	70CFM		90CFM		125CFM	130CFM
RATED PRESSURE	100psi or 7kg/m ³						
FREE AIR DELIVERY	1.4m ³ /min	2m ³ /min		2.5m ³ /min		3.5m ³ /min	
ENGINE INFO.	The engine brand will be different for models and years, but generally we use a Isuzu, Kubota and Yanmar. The engines are a water cooled, 3 cylinders diesel direct injection engine with that have natural aspiration.						
CANOPY	Heavy duty weatherproof silenced canopy						
STARTING SYSTEM	12V key start						
NOISE LEVEL	66dB 75dB at 7m depending on compressor size						
DIMENSIONS	1.5L x 0.77 x 0.85W	1.5 x 0.77L x 0.85W		1.6 x 0.77L x 0.9W		1.7L x 0.91W x 1.08H	
WEIGHT	340kg	475kg		525kg		680kg	



Engine powered piston air compressors

	39CFM-13HP PETROL LIFAN AIR COMPRESSOR	39CFM-13.5HP PETROL BRIGGS & STRATTON AIR COMPRESSOR	39CFM-7.7HP DIESEL HAILIN AIR COMPRESSOR
MODEL	MCFS050	MCFS060	MCFS040
FUEL TYPE	Petrol		Diesel
WEIGHT	245kg		
DIMENSIONS	1400L x 500W x 1040H		
DISPLACEMENT	39cfm (1104L/min)		
FREE AIR DELIVERY	30cfm (850L/min)		
RATED OPERATING PRESSURE	115psi (8 bar)		
TANK CAPACITY	160L		
COMPRESSOR CYL.	Twin head		
APPROVALS	Work Safe approval with registered tank		
OUTLETS	2 x ¼" outlets 1 x ½" outlet		1 x ½" outlet
MOTOR BRAND	Petrol Lifan		Diesel Hailin
HORSEPOWER	13Hp	13.5Hp	7.7Hp
DECOMPRESSION LEVER	No		Yes
FUEL TANK	5.4lt		
MOTOR RPM	3600rpm		3000rpm
STARTING SYSTEM	12V electric with recoil backup		
FORK ENTRY POINT	Yes		
RUBBER FOOTPLATES	Yes		



Electric piston air compressors

	27CFM 3 - PHASE ELECTRIC AIR COMPRESSOR	39CFM-13.5HP PETROL BRIGGS & STRATTON AIR COMPRESSOR	52CFM 3 - PHASE ELECTRIC AIR COMPRESSOR
MODEL	MCFS010	MCFS020	MCFS030
WEIGHT	230kg	250kg	340kg
DIMENSIONS	1400L x 500W x 1000H		1400 x 610W x 1210H
DISPLACEMENT	27cfm (760L/min)	37cfm (1047L/min)	52cfm (1472L/min)
FREE AIR DELIVERY	20cfm (556L/min)	27cfm (764L/min)	42.5cfm (1203L/min)
RATED OPERATING PRESSURE	115psi (8 bar)		
TANK CAPACITY	160L		300L
COMPRESSOR CYL.	Triple head	Twin head	Triple head
APPROVALS	Work Safe approval with registered tank. MEPS approved high efficiency motor		
OUTLETS	2 x ¼" outlets 1 x ½" outlet		
MOTOR TYPE	Teco 5.5hp – 7.3 amp running current	Teco 7.5hp – 10.3 amp running current	Teco 10hp – 13.8 amp running current
HORSEPOWER	5.5hp	7.5hp	10hp
MOTOR RPM	1455rpm		
3 - PHASE PLUG HEAD	20 amp – 5 pin		32 amp – 5 pin
FORK ENTRY POINT	Yes		
RUBBER FOOTPLATES	Yes		