



**Style Guide** Office Signage

Current as at 15, October

# Contents

---

Housekeeping .....	03
Brand Finishes .....	05
Signage Suite Overview .....	07
Sign Types .....	10
Internal Applications .....	47
Optional Applications .....	53
Engineering Certificates .....	61



1.0

# House-keeping

It is natural for a business to grow and evolve over time, and therefore crucial that our internal and external audiences keep up with these changes. This house-keeping is included to ensure all branding reflects the business as a whole, by sharing the upkeep and maintenance requirements to do so.

# Maintenance

---

## 1. Regular Cleaning

Vinyl Signage: Clean vinyl signage regularly with a mild detergent and water solution. Avoid using abrasive cleaners or rough materials that could scratch the surface.

Illuminated Signs: Dust and dirt can accumulate on illuminated signs, impacting visibility. Use a soft cloth or sponge with a gentle cleaning solution to wipe down the surface. Ensure the power supply is turned off before cleaning.

## 2. Inspection & Repair

Vinyl Signage: Periodically inspect vinyl signs for any signs of wear, tear, or fading. Replace damaged sections promptly to maintain a professional appearance and ensure readability. Illuminated Signs: Check the wiring, bulbs, and connections of illuminated signs regularly. Replace any faulty components immediately to avoid disruptions in visibility.

## 3. Pest Control

Prevent Pest Infestations: Inspect signage regularly for signs of pest infestation, such as insect nests or rodent damage. Take appropriate measures to deter pests and protect signage from damage.

## 4. Professional Maintenance

Annual Inspections: Schedule annual inspections by a professional signage maintenance service provider. They can identify potential issues early and perform any necessary repairs or maintenance tasks. Signage Upgrades: Consider periodic upgrades or refurbishments to keep signage looking fresh and appealing to customers. This may involve updating graphics, replacing outdated technology in illuminated signs, or refreshing materials.

## 5. Safety Considerations

Electrical Safety: Regularly check wiring and connections for any signs of wear or damage. Heightened Awareness: In areas prone to extreme weather events, such as cyclones or bushfires, take extra precautions to secure signage and minimise potential hazards during adverse conditions.

## 6. Documentation

Maintenance Records: Keep detailed records of all maintenance activities, inspections, repairs, and upgrades performed on signage. This documentation can be valuable for tracking performance over time and planning future maintenance efforts. By following these maintenance guidelines, you can ensure that your signage remains attractive, functional, and compliant with regulations, enhancing your brand visibility and making a positive impression on customers in Australia.

2.0

# Brand Finishes

The brand finishes are composed of a distinct colour palette chosen to represent the brand.

# Colour Palette

---

## Primary Palette



RGB 43 43 43

CMYK 10 3 3 90

PANTONE Black 7 C

PAINT **2 PACK PAINT**

To match Patone Black 7 C

**ACRYLIC PAINT**

NZ - Dulux, the Kuiti, NZ10H1

AU - Dulux, Black Caviar EB, SN4H9

**VINYL**

Auvery 921 Black Matte

**CLADDING**

Alupanel, FR (Group 2) – Matte

Anthracite Grey



255 179 0

0 30 100 0

1235 C

PAINT **2 PACK PAINT**

To match Patone 1235 C

**ACRYLIC PAINT**


Dulux 'Gold Rush A 169'

**VINYL**

3M, Golden Yellow 3630-125

**ACRYLIC**

Custom Yellow Translucent Acrylic (stocked by The Blueprint)



255 255 255

0 0 0 0

PAINT **2 PACK PAINT**

To match Alupanel FR Matte White

**ACRYLIC PAINT**

Dulux 'Vivid White SW1G1'

**VINYL**

Auvery 730 Matte White

**CLADDING**

Alupanel, FR (Group 2) – 3mm Matte White


## Secondary Palette



RGB 197 199 201

CMYK 0 0 0 25

PAINT **ACRYLIC PAINT**  
Dulux 'Endless Dusk'



241 241 242

0 0 0 5

**ACRYLIC PAINT**  
Dulux 'Terrace White'  
**VINYL**  
Metamark M7

# Signage Suite Overview

This section provides a comprehensive look into the various external signage features available to display for our offices.

3.0

# Signage Suite Overview

## Code Legend

Signage Type = Beginning of Code. EG. Ampersand – Low Level = A/LL

Size = After Signage Code. EG. Ampersand – Low Level = A/LL-800

Non-illuminated = End of code, N = Non-illuminated, EG. Ampersand – Low Level = A/LL-800-N



Raine&Horne®

3000

Raine&Horne.

FFL

FA-150/-N - Fascia Lettering + FASCIA-350-(AorB) - Fascia Cladding  
 FA-175/-N - Fascia Lettering + FASCIA-500-(AorB) - Fascia Cladding  
 FA-225/-N - Fascia Lettering + FASCIA-600-(AorB) - Fascia Cladding

Fascia Sign  
 Fabricated background to suit site condition.  
 Illuminated or non-illuminated wordmark logo.

A/HL-800 - 800mmH Ampersand  
 A/HL-1100 - 1100mmH Ampersand  
 A/HL-1350 - 1350mmH Ampersand

Ampersand - High Level  
 Fabricated brand mark.  
 Illuminated or Non-illuminated.

WM/HL-300 - 300mmH Wordmark  
 WM/HL-500 - 500mmH Wordmark

Wordmark Logo - High Level  
 Fabricated wordmark.  
 Illuminated or Non-illuminated.

3000

Raine&Horne.

FFL

TR-150/-N - Transom Lettering + TRANSOM-350-(AorB) - Transom Cladding  
 TR-175/-N - Transom Lettering + TRANSOM-500-(AorB) - Transom Cladding  
 TR-225/-N - Transom Lettering + TRANSOM-600-(AorB) - Transom Cladding

Transom Sign  
 Fabricated background to suit site condition.  
 Illuminated or non-illuminated wordmark logo.

UA-1500 - 1500mmW Lightbox  
 UA-1800 - 1800mmW Lightbox

Under Awning Sign  
 Under Awning Lightbox, double sided.  
 Illuminated or Non-illuminated.

CA-500 - 500mmW Lightbox  
 CA-750 - 750mmW Lightbox

Cantilevered Sign  
 Cantilevered Lightbox, double sided.  
 Illuminated or Non-illuminated.



# Signage Suite Overview

## Code Legend

Signage Type = Beginning of Code, EG. Ampersand – Low Level = A/LL

Size = After Signage Code, EG. Ampersand – Low Level = A/LL-800

Non-Illuminated = End of code, N = Non-illuminated, EG. Ampersand – Low Level = A/LL-800-N



# 4.0

## Sign Types



This section provides a comprehensive look into the various external signage features available to display for our offices.

## FA-xxx-N Fascia Logo

## FASCIA-xxx-(A,BorC)

## Fascia Cladding

- FA-150-N - Fascia Lettering + **FASCIA-350-(A,BorC)** - Fascia Cladding
- FA-175-N - Fascia Lettering + **FASCIA-500-(A,BorC)** - Fascia Cladding
- FA-225-N - Fascia Lettering + **FASCIA-600-(A,BorC)** - Fascia Cladding
- FA-325-N - Fascia Lettering + **FASCIA-1000-(A,BorC)** - Fascia Cladding
- FA-350-N - Fascia Lettering + **FASCIA-1200-(A,BorC)** - Fascia Cladding
- FA-375-N - Fascia Lettering + **FASCIA-1400-(A,BorC)** - Fascia Cladding
- FA-400-N - Fascia Lettering + **FASCIA-1600-(A,BorC)** - Fascia Cladding



Typical Fascia Elevation  
Scale 1:25

**FASCIA SIGN**

Non-illuminated wordmark logo.  
Refer to following page for details.

**APPLICATION NOTES****A. Logo Size**

Standard logo sizes:  
150mmH - Fascias 350 to 499mmH  
175mmH - Fascias 500 to 599mmH  
225mmH - Fascias 600 to 800mmH  
325mmH - Fascias 801 to 1000mmH  
350mmH - Fascias 1001 to 1200mmH  
375mmH - Fascias 1201 to 1400mmH  
400mmH - Fascias 1401 to 1600mmH

**B. Clear Space**

X = clear space top, bottom, & left of logo.  
Logo is centred vertically on the fascia panel & clear space to the left is equal to the space top & bottom.


**C. Logo Placement**

Logo to be preferably left aligned, but may be right aligned if the location has better visibility.


## FA-xxx-N Fascia Logo

## FASCIA-xxx-(A,BorC)

## Fascia Cladding



FA-150-N - Fascia Lettering + FASCIA-400-(A,BorC) - Fascia Cladding  
\*150mmH logo to applied to fascias between 350-499mmH




FA-175-N - Fascia Lettering + FASCIA-500-(A,BorC) - Fascia Cladding  
\*175mmH logo to applied to fascias between 500-599mmH




FA-225-N - Fascia Lettering + FASCIA-650-(A,BorC) - Fascia Cladding  
\*225mmH logo to applied to fascias between 600-800mmH

Typical Fascia Logo Sizes  
Scale 1:20




FA-325-N - Fascia Lettering + FASCIA-1000-(A,BorC) - Fascia Cladding  
\*325mmH logo to applied to fascias between 801-1000mmH



FA-350-N - Fascia Lettering + FASCIA-1200-(A,BorC) - Fascia Cladding  
\*350mmH logo to applied to fascias between 1001-1200mmH



FA-375-N - Fascia Lettering + FASCIA-1400-(A,BorC) - Fascia Cladding  
\*375mmH logo to applied to fascias between 1201-1400mmH



FA-400-N - Fascia Lettering + FASCIA-1600-(A,BorC) - Fascia Cladding  
\*400mmH logo to applied to fascias between 1401-1600mmH

Typical Large Fascia Logo Sizes  
Scale 1:50

**FASCIA SIGN**  
Non-illuminated wordmark logo.  
Refer to following page for details.

## APPLICATION NOTES

## A. Logo Size

Standard logo sizes:  
150mmH - Fascias 350 to 499mmH  
175mmH - Fascias 500 to 599mmH  
225mmH - Fascias 600 to 800mmH  
325mmH - Fascias 801 to 1000mmH  
350mmH - Fascias 1001 to 1200mmH  
375mmH - Fascias 1201 to 1400mmH  
400mmH - Fascias 1401 to 1600mmH

## B. Clear Space

X = clear space top, bottom, & left of logo.  
Logo is centred vertically on the fascia panel & clear space to the left is equal to the space top & bottom.


## C. Logo Placement

Logo to be preferably left aligned, but may be right aligned if the location has better visibility.

## FA-xxx-N Fascia Logo


## FASCIA-xxx-(A,BorC)

## Fascia Cladding




Construction A  
Fascia Sign - Non-illuminated with frame  
Typical Section  
Scale 1:2

**FASCIA-350-A** - Fascia Cladding with Frame  
**FASCIA-500-A** - Fascia Cladding with Frame  
**FASCIA-600-A** - Fascia Cladding with Frame



Construction B  
Fascia Sign - Non-illuminated no frame  
Typical Section  
Scale 1:2

**FASCIA-350-B** - Fascia Cladding No Frame  
**FASCIA-500-B** - Fascia Cladding No Frame  
**FASCIA-600-B** - Fascia Cladding No Frame



Construction C  
Fascia Sign - Non-illuminated flat panels  
Typical Section  
Scale 1:2

**FASCIA-350-C** - Fascia Flat Panels  
**FASCIA-500-C** - Fascia Flat Panels  
**FASCIA-600-C** - Fascia Flat Panels

## GENERAL CONSTRUCTION NOTES

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION A INTENT

## 1. Frame

40x3mm aluminium SHS perimeter frame. Fishplate frame joins to ensure level connections between panels.

## 2. Cladding

Fabricated 3mm Alupanel FR (Group2) matte white cladding at 2400mm or 3000mm lengths. SS wafer head screw fixings along top and bottom edge @ approx. 500mm centres to frame. Fishplates behind panel joins.

## 3. Non-illuminated logo

Profile cut 6mm acrylic adhesive fixed to face of cladding. 2 pack painted to brand colours.

## 4. Fixings

4a. Metal Wall - Minimum of 10xM10 bolts to either Girt or stud + ST 5.8 (#12) screws @500 c/c to metal façade 0.48 BMT (uniformly distributed).

4b. Timber - Minimum of 10xM8 coach screws to either Girt or stud + ST 5.8 (#12) screws @500 c/c to metal façade.

4c. Concrete - 10xM10 (4.6/S) Chemset Bolts. Embedment depth = 90mm.

4d. Structural Tube Sections - Steel SHS or RHS with minimum wall thickness of 3mm. Minimum 8 x M12x75mm Hollow bolts + ST 5.8 (#12) screws @500c/c to metal façade (uniformly distributed).

\*Refer to engineering certification on pages 71-76 for full details.

## CONSTRUCTION B INTENT

## 5. Cladding

Fabricated 3mm Alupanel FR (Group2) matte white cladding at 2400mm or 3000mm lengths. SS wafer head screw fixings along top and bottom edge @ approx. 500mm centres to site structure. Fishplates behind panel joins.

## 6. Non-illuminated logo

Profile cut 6mm acrylic adhesive fixed to face of cladding. 2 pack painted to brand colours.

## CONSTRUCTION C INTENT

## 7. Cladding

Flat 3mm Alupanel FR (Group2) matte white panels at 2400mm or 3000mm lengths. Adhesive fixed to fascia surface to suit site conditions.

## 8. Non-illuminated logo

Profile cut 6mm acrylic adhesive fixed to face of cladding. 2 pack painted to brand colours.

## A/HL-xxx Ampersand - High Level

**A/HL-800** - 800mmH Ampersand Illuminated  
**A/HL-1100** - 1100mmH Ampersand Illuminated  
**A/HL-1350** - 1350mmH Ampersand Illuminated



Typical Elevation - Ampersand - High Level - Small Wall  
Scale 1:25

**AMPERSAND - HIGH LEVEL**  
 Fabricated brand mark.  
 Illuminated or non-illuminated depending on Council regulations and approval.

### APPLICATION NOTES

#### A. Logo Size

Consistent sizes across all sites:  
 - Small 709mmW x 800mmH  
 - Medium 975mmW x 1100mmH  
 - Large 1197mmW x 1350mmH.

#### B. Clear Space

25% logo height.


#### C. Logo Placement

Logo to be aligned to the most prominent top corner of the building.

For smaller walls the logo may be centred on the wall.

# A/HL-xxx Ampersand - High Level


**A/HL-800** - 800mmH Ampersand Illuminated  
**A/HL-1100** - 1100mmH Ampersand Illuminated  
**A/HL-1350** - 1350mmH Ampersand Illuminated



Front View


Side View

**Construction A**  
 Ampersand - High Level - Illuminated  
 Scale 1:25



**Construction A**  
 Ampersand - High Level - Illuminated  
 Scale 1:2


**A/HL-800-N** - 800mmH Ampersand Non-illuminated  
**A/HL-1100-N** - 1100mmH Ampersand Non-illuminated  
**A/HL-1350-N** - 1350mmH Ampersand Non-illuminated



Front View

Side View

**Construction B**  
 Ampersand - High Level - Non-illuminated  
 Scale 1:25



**Construction B**  
 Ampersand - High Level - Non-illuminated  
 Scale 1:2

## GENERAL CONSTRUCTION NOTES

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION A INTENT

- Letter Body**  
Fabricated 2mm / 3mm aluminium ampersand with 100mm(D) returns. All welds to be polished smooth. 2 pac painted to match R&H Gold.
- Illuminated Faces**  
Profile cut 4.5mm opal polycarbonate sign face (certified to group 1 or 2 fire rating) held in place with fabricated aluminium face trims. Face applied translucent vinyl. Any Ampersand over the size of 1200mm, will have a vinyl join on the face.
- Face Trims**  
Profile cut 4.5mm opal polycarbonate sign face (certified to group 1 or 2 fire rating) held in place with fabricated aluminium face trims. Face applied translucent vinyl. Any Ampersand over the size of 1200mm, will have a vinyl join on the face.
- Lighting**  
6500K LEDs (IP67) cool white fitted to backs, type & layout to suppliers specifications, ensure no shadowing & hot spotting.
- Mounting Plates**  
50x4mm aluminium flat bar welded to letter backs at fixing locations.
- Wall Fixings**
  - 6a. Metal Wall** - Minimum 3xM10 bolts to either Girt or stud + Minimum of 7-ST 5.8 (#12) screws to metal façade 0.48 BMT (uniformly distributed).
  - 6b. Timber** - Minimum 3xM8 coach screws to either Girt or stud + Minimum of 7-ST 5.8 (#12) screws to metal façade (uniformly distributed).
  - 6c. Concrete** - 7xM10(4.6/S) Chemset bolts. Embedment depth= 90mm.
- Structural Tube Sections** - Steel SHS or RHS minimum thickness of 3mm. Minimum 3 x M16x75mm Hollow bolts + Minimum of 7-ST 5.8 (#12) screws to metal façade (uniformly distributed).

\*Refer to engineering certification on pages 61-65 for full details.

## CONSTRUCTION B INTENT

- Letter Body**  
Fabricated 2mm / 3mm aluminium ampersand with 100mm(D) returns. All welds to be polished smooth. 2 pac painted to match R&H Gold.
- Non-illuminated Letter Backs**  
Profile cut 3mm aluminium with 40x3mm aluminium angle tabs welded to face. Fabricated letters fixed to backs using SS 316 grade CSK fixings. Paint heads to match returns.

## WM/HL-xxx Wordmark Logo - High Level

**WM/HL-300** - 300mmH Wordmark Illuminated  
**WM/HL-500** - 500mmH Wordmark Illuminated



### WORDMARK LOGO - HIGH LEVEL

Fabricated wordmark.  
 Illuminated or non-illuminated depending on Council regulations and approval.  
 Refer to following pages for details.

#### APPLICATION NOTES

##### A. Logo Size

Consistent sizes across all sites:  
 - Small 2341mmW x 300mmH  
 - Large 3900mmW x 500mmH.

##### B. Clear Space

Minimum clear space is the logo Ampersand height.

##### C. Logo Placement

Logo to be centred aligned on the most prominent high level building wall.

2000

1000

FFL

**ID3** Wordmark Logo - High Level  
 Scale 1:25


# WM/HL-xxx Wordmark Logo - High Level

WM/HL-300 - 300mmH Wordmark Illuminated  
WM/HL-500 - 500mmH Wordmark Illuminated




Front View


Wordmark Logo - High Level - Illuminated  
Scale 1:25



Side View



Wordmark Logo Letters - High Level - Illuminated  
Scale 1:2



Wordmark Logo Ampersand - High Level - Illuminated  
Scale 1:2

## GENERAL CONSTRUCTION NOTES

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION INTENT

### 1. Letter Body

Halo illuminated letters fabricated 3mm aluminium with returns 60mm deep. 2 pac painted to match R&H Charcoal. S/S countersunk screw fix faces to angle brackets & paint heads to match returns.

### 2. Illuminated Backs

Profile cut 9.5mm Zenolex clear polycarbonate (group 1 or 2 fire rated) letter backs or similar.

### 3. Back Brackets

Nominal 25x25x3mm aluminium angle brackets. M6 S/S CSK bolts angle bracket to polycarbonate backs.

### 4. Lighting

6500K LEDs (IP67) cool white fitted to backs, type & layout to suppliers specifications, ensure no shadowing & hot spotting.

### 5. Wall Fixings

5a. Metal Wall - Minimum of 2xM10 bolts to either Grit or stud + ST 5.8 (#12) screws to 0.48 BMT metal façade as per page 86.

5b. Timber - Minimum of 2xM8 coach screws to either Gurt or stud + ST 5.8 (#12) screws as per page 86.

5c. Concrete - M10 (4.6/S) Chemset bolts. Embedment depth = 90 mm. See page 86 for fixing positions.

5d. Structural Tube Sections - Steel SHS or RHS with minimum wall thickness of 3 mm. Minimum 2 x 16x75mm Hollow bolts + ST 5.8 (#12) screws to metal façade as per page 86.

\*Refer to engineering certification on pages 83-88 for full details.

### 6. Trademark Symbol

Profile cut 6mm opal polycarbonate (group 1 or 2 fire rated) adhesive fixed direct to wall. 2 pack painted Charcoal.

### 7. Ampersand Body

Face illuminated ampersand fabricated 3mm aluminium with returns 60mm deep. 2 pac painted to match R&H Gold.

### 8. Illuminated Faces

Fabricated 4.5mm Zenolex opal polycarbonate (group 1 or 2 fire rated) face or similar, with returns for fixing to Ampersand body. Face applied translucent yellow vinyl. 2 pack paint returns of faces to match R&H Gold, opaque. S/S countersunk screw fix faces to body & paint heads to match returns.

## ID3 Wordmark Logo - High Level - Non-illuminated

WM/HL-300-N - 300mmH Wordmark Non-illuminated  
WM/HL-500-N - 500mmH Wordmark Non-illuminated



Front View

Wordmark Logo - High Level - Non-illuminated  
Scale 1:25




Side View

### GENERAL CONSTRUCTION NOTES

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

### CONSTRUCTION INTENT

1. **Letter Body**  
Fabricated 2mm / 3mm aluminium letters & ampersand with 100mm(D) returns. All welds to be polished smooth. 2 pac painted to match R&H Charcoal & Gold.
2. **Non-illuminated Letter Backs**  
Profile cut 20mm thick external grade PVC. Fabricated letters fixed to backs using SS 316 grade CSK fixings. Paint heads to match returns.
3. **Wall Fixings**  
Logo fixed directly to facade to engineers specification to suit structure at each location.



Typical Section Detail

Wordmark Logo Letters - High Level - Non-illuminated  
Scale 1:2

## TR-xxx-N Transom Logo

## TRANSOM-xxx-(AorB) Transom Cladding

- TR-150-N - Transom Lettering + **TRANSOM-350-(AorB)** - Transom Cladding
- TR-175-N - Transom Lettering + **TRANSOM-500-(AorB)** - Transom Cladding
- TR-225-N - Transom Lettering + **TRANSOM-600-(AorB)** - Transom Cladding
- TR-325-N - Transom Lettering + **TRANSOM-1000-(AorB)** - Transom Cladding
- TR-350-N - Transom Lettering + **TRANSOM-1200-(AorB)** - Transom Cladding
- TR-375-N - Transom Lettering + **TRANSOM-1400-(AorB)** - Transom Cladding
- TR-400-N - Transom Lettering + **TRANSOM-1600-(AorB)** - Transom Cladding

**TRANSOM SIGN**

Non-illuminated wordmark logo.  
Refer to following page for details.

**APPLICATION NOTES****A. Logo Size**


Standard logo sizes:  
150mmH - Transoms 350 to 499mmH  
175mmH - Transoms 500 to 599mmH  
225mmH - Transoms 600 to 800mmH  
325mmH - Transoms 801 to 1000mmH  
350mmH - Transoms 1001 to 1200mmH  
375mmH - Transoms 1201 to 1400mmH  
400mmH - Transoms 1401 to 1600mmH

**B. Clear Space**


X = clear space top, bottom, & left of logo.  
Logo is centred vertically on the fascia panel & clear space to the left is equal to the space top & bottom.

**C. Logo Placement**


Logo to be preferably left aligned, but may be right or centre aligned if the location has better visibility.



## TR-xxx-N Transom Logo



TR-150-N - Transom Lettering + TRANSOM-400-(AorB) - Transom Cladding  
\*150mmH logo to applied to transoms between 350-499mmH




TR-175-N - Transom Lettering + TRANSOM-500-(AorB) - Transom Cladding  
\*175mmH logo to applied to transoms between 500-599mmH



TR-225-N - Transom Lettering + TRANSOM-650-(AorB) - Transom Cladding  
\*225mmH logo to applied to transoms between 600-800mmH

Typical Transom Logo Sizes  
Scale 1:20


## TRANSOM-xxx-(AorB) Transom Cladding



TR-325-N - Transom Lettering + TRANSOM-1000-(AorB) - Transom Cladding  
\*325mmH logo to applied to transoms between 801-1000mmH



TR-350-N - Transom Lettering + TRANSOM-1200-(AorB) - Transom Cladding  
\*350mmH logo to applied to transoms between 1001-1200mmH



TR-375-N - Transom Lettering + TRANSOM-1400-(AorB) - Transom Cladding  
\*375mmH logo to applied to transoms between 1201-1400mmH



TR-400-N - Transom Lettering + TRANSOM-1600-(AorB) - Transom Cladding  
\*400mmH logo to applied to transoms between 1401-1600mmH

Typical Large Transom Logo Sizes  
Scale 1:50

## TRANSOM SIGN

Non-illuminated wordmark logo.  
Refer to following page for details.

## APPLICATION NOTES

## A. Logo Size

Standard logo sizes:  
150mmH - Transoms 350 to 499mmH  
175mmH - Transoms 500 to 599mmH  
225mmH - Transoms 600 to 800mmH  
325mmH - Transoms 801 to 1000mmH  
350mmH - Transoms 1001 to 1200mmH  
375mmH - Transoms 1201 to 1400mmH  
400mmH - Transoms 1401 to 1600mmH

## B. Clear Space


X = clear space top, bottom, & left of logo.  
Logo is centred vertically on the fascia panel & clear space to the left is equal to the space top & bottom.

## C. Logo Placement

Logo to be preferably left aligned, but may be right or centre aligned if the location has better visibility.


## TR-xxx-N Transom Logo

## TRANSOM-xxx-(AorB) Transom Cladding



Construction A  
Transom Sign - Non-illuminated with frame - Typical Section  
Scale 1:2

**TRANSOM-350-A** - Transom Cladding with Frame  
**TRANSOM-500-A** - Transom Cladding with Frame  
**TRANSOM-600-A** - Transom Cladding with Frame



Construction B  
Transom Sign - Non-illuminated no frame - Typical Section  
Scale 1:2

**TRANSOM-350-B** - Transom Cladding No Frame  
**TRANSOM-500-B** - Transom Cladding No Frame  
**TRANSOM-600-B** - Transom Cladding No Frame

## GENERAL CONSTRUCTION NOTES

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION A INTENT

## 1. Frame

25x3mm aluminium SHS perimeter frame. Fishplate frame joins to ensure level connections between panels.

## 2. Cladding - Folded

Fabricated 3mm Alupanel FR (Group2) matte white cladding at 2400mm or 3000mm lengths. SS wafer head screw fixings along top and bottom edge @ approx. 500mm centres to frame. Fishplates behind panel joins.

## 3. Non-illuminated logo

Profile cut 6mm acrylic adhesive fixed to face of cladding. 2 pack painted to brand colours.

## 4. Fixings

4a. Metal Wall - Minimum of 10xM10 bolts to either Girt or stud + ST 5.8 (#12) screws @500 c/c to metal façade 0.48 BMT (uniformly distributed).

4b. Timber - Minimum of 10xM8 coach screws to either Girt or stud + ST 5.8 (#12) screws @500 c/c to metal façade.

4c. Concrete - 10xM10 (4.6/S) Chemset Bolts. Embedment depth = 90mm.

4d. Structural Tube Sections - Steel SHS or RHS with minimum wall thickness of 3mm. Minimum 8 x M12x75mm Hollow bolts + ST 5.8 (#12) screws @500c/c to metal facade (uniformly distributed).

\*Refer to engineering certification on pages 71-76 for full details.

## CONSTRUCTION B INTENT


## 5. Cladding - Flat

Flat 3mm Alupanel FR (Group2) matte white panels at 2400mm or 3000mm lengths. Adhesive fixed to transom surface to suit site conditions.

## 6. Non-illuminated logo

Profile cut 6mm acrylic adhesive fixed to face of cladding. 2 pack painted to brand colours.

# TR-xxx- Transom Logo - Illuminated



Typical Section - Illuminated Letters  
Transom Sign - Illuminated with frame - Typical Section  
Scale 1:2

Typical Section - Illuminated Ampersand  
Transom Sign - Illuminated with frame - Typical Section  
Scale 1:2

**TR-150** - Transom Lettering + **TRANSOM-350-A** - Transom Cladding  
**TR-175** - Transom Lettering + **TRANSOM-500-A** - Transom Cladding  
**TR-225** - Transom Lettering + **TRANSOM-600-A** - Transom Cladding  
**TR-325** - Transom Lettering + **TRANSOM-1000-A** - Transom Cladding  
**TR-350** - Transom Lettering + **TRANSOM-1200-A** - Transom Cladding  
**TR-375** - Transom Lettering + **TRANSOM-1400-A** - Transom Cladding  
**TR-400** - Transom Lettering + **TRANSOM-1600-A** - Transom Cladding

## GENERAL CONSTRUCTION NOTES


- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION INTENT


- 1. Letter Body**  
Profile cut 30mm opal acrylic. Faces & 12mm of returns 2 pac painted to match R&H Charcoal. Rear 18mm of letter return to remain opal for halo illumination.
- 2. Letter Cover**  
2 to 3mm opal acrylic diffuser.
- 3. Power Feeds**  
Input DC12V .
- 4. Lighting**  
8mm Diode Leds, resin set Inside letter body.
- 5. Cladding Fixings**  
M4 Pins with nylon nuts to the rear fix to cladding.
- 6. Trademark Symbol**  
Profile cut 4.5mm acrylic adhesive fixed to cladding. 2 pack painted Charcoal.
- 7. Ampersand Body**  
Profile cut 30mm opal acrylic. Translucent gold vinyl to face and returns 2 pac painted to match R&H Gold.

# UA-1500 Under Awning Sign - 1500mmW

**UA-1500** - 1500mmW Lightbox Illuminated  
**UA-1500-N** - 1500mmW Lightbox Non-illuminated



UA-1500 - Under Awning Sign - Right Side  
 Scale 1:25



UA-1500 - Under Awning Sign - Left Side  
 Scale 1:25


**UNDER AWNING SIGN**  
 Under Awning Lightbox, double sided.  
 Illuminated or Non-illuminated.  
 Refer to following page for details.

## APPLICATION NOTES


- A. Logo Size**  
 1/3 lightbox height.
- B. Clear Space**  
 1/3 lightbox height.
- C. Logo Placement**  
 Logo to be aligned to the "road side" of the shop front.
- D. Lightbox Size**  
 Consistent sizes across all sites:
  - Small 1500mmW x 360mmH
  - Large 1800mmW x 420mmH.
- E. Height Above Ground**  
 Install lightbox 2400mm AFFL from ground to bottom of lightbox. Adjust dropers accordingly.

# UA-1800 Under Awning Sign - 1800mmW

**UA-1800** - 1800mmW Lightbox Illuminated  
**UA-1800-N** - 1800mmW Lightbox Non-illuminated



UA-1800 - Under Awning Sign - Right Side  
 Scale 1:25



UA-1800 - Under Awning Sign - Left Side  
 Scale 1:25


**UNDER AWNING SIGN**  
 Under Awning Lightbox, double sided.  
 Illuminated or Non-illuminated.  
 Refer to following page for details.

## APPLICATION NOTES

- A. Logo Size**  
 1/3 lightbox height.
- B. Clear Space**  
 1/3 lightbox height.
- C. Logo Placement**  
 Logo to be aligned to the "road side" of the shop front.
- D. Lightbox Size**  
 Consistent sizes across all sites:
  - Small 1500mmW x 360mmH
  - Large 1800mmW x 420mmH.
- E. Height Above Ground**  
 Install lightbox 2400mm AFFL from ground to bottom of lightbox. Adjust dropplers accordingly.



## UA-1500-N Under Awning Sign (FOR NZ ONLY)




Front View

Under Awning Sign - Non-illuminated  
Scale 1:10




Framework

Under Awning Sign - Non-illuminated  
Scale 1:10



Side View



Typical Section Detail

Under Awning Sign - Non-illuminated  
Scale 1:3

## GENERAL CONSTRUCTION NOTES

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION INTENT

1. Lightbox Subframe  
50x25x3mm aluminium RHS perimeter frame & vertical member.

2. Lightbox Faces  
Fabricated 2mm aluminium faces with 27.5mm returns with equally spaced SS 316 grade CSK fixings. Paint heads to match returns  
Computer cut vinyl graphics applied to faces.

3. Droppers  
32x3mm aluminium SHS dropper sleeves, 2 pack painted R&H charcoal.

4. Ceiling Fixings  
Nominal galvanised M10 threaded rod bolted to top of lightbox and anchored or bolted to ceiling structure to suit site requirements and engineers specifications.  
Indicative ceiling structure shown in typical section detail.

# CA-500 Cantilevered Sign


**CA-500** - 500mmW Lightbox Illuminated  
**CA-500-N** - 500mmW Lightbox Non-illuminated  
**CA-750** - 750mmW Lightbox Illuminated  
**CA-750-N** - 750mmW Lightbox Non-illuminated

**CANTILEVERED SIGN**  
 Cantilevered Lightbox, double sided.  
 Illuminated or Non-illuminated.  
 Refer to following page for details.



**APPLICATION NOTES**  
**A. Logo Size**  
 2/3 lightbox height.  
**B. Clear Space**  
 1/6 lightbox height.  
**C. Lightbox Size**  
 Consistent sizes across all sites:  
 - Small 500mmW x 500mmH  
 - Large 750mmW x 750mmH.  
**D. Usage**  
 Only to be used where under-awning signage (ID5) is not possible.  
**E. Height Above Ground**  
 Install lightbox 2400mm AFFL from ground to bottom of lightbox.

# CA-500 Cantilevered Sign



## GENERAL CONSTRUCTION NOTES

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION INTENT

### 1. Lightbox Case

- 1a. Fabricated 2mm aluminium perimeter layers.
- 2 pac painted white.
- 1b. 40x20x3mm aluminium RHS perimeter frame & vertical member.
- 1c. 40x40x3mm aluminium SHS standoffs welded between plates.
- 1d. 10mm aluminium mounting plate.

### 2. Lightbox Faces - Illuminated

- Fabricated 2mm aluminium faces with 25mm returns with equally spaced SS 316 grade CSK fixings. Paint heads to match returns.

Faces intricut with profile cut acrylic logos - 10mm opal acrylic & 12mm Custom Yellow Translucent Acrylic protruding from signfaces with 3mm opal acrylic backing. Refer to letter detail.

### 3. Lighting

- 6500K side illuminating LEDs cool white and LED driver inside lightbox. Contractor to ensure even and adequate illumination of logo. Include 240V power cable & 3-pin plug.


### 4. Mounting Plate Cover

- Fabricated 2mm aluminium covers, 2 pack painted R&H charcoal. Fixed to top and bottom of standoffs with SS 316 grade CSK fixings. Paint heads to match returns.

### 5. Wall Fixings

- Galvanised ChemSet 5xM12 (5.8/S) Emb= 110mm.


\*Refer to engineering certification on pages 66-70 for full details.




Cantilevered Sign - Ampersand Detail

Scale 1:10


## CA-750 Cantilevered Sign




## Cantilevered Sign - Illuminated



## Cantilevered Sign - Illuminated



## Framework



### Cantilevered Sign - Ampersand Detail

## GENERAL CONSTRUCTION NOTES

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION INTENT

## 1. Lightbox Case

- 1a. Fabricated 2mm aluminium perimeter layers.  
2 pac painted white.
- 1b. 40x20x3mm aluminium RHS perimeter frame & vertical member.
- 1c. 40x40x3mm aluminium SHS standoffs welded between plates.
- 1d. 16mm aluminium mounting plate.

## 2. Lightbox Faces - Illuminated

## 2. Lightbox Faces - Illuminated

Faces intricut with profile cut acrylic logos - 10mm opal acrylic & 12mm Custom Yellow Translucent Acrylic protruding from signfaces with 3mm opal acrylic backing. Refer to letter detail.

### 3. Lighting

6500K side illuminating LEDs cool white and LED driver inside lightbox. Contractor to ensure even and adequate illumination of logo. Include 240V power cable & 3-pin plug.

#### 4. Mounting Plate Cover

Fabricated 2mm aluminium covers, 2 pack painted R&H charcoal. Fixed to top and bottom of standoffs with SS 316 grade CSK fixings. Paint heads to match returns.

## 5 Wall Fixings


5. Wall Fixings  
Galvanised ChemSet 5xM12 (5.8/S) Emb= 110mm

\*Refer to engineering certification on pages 66-70 for full details.

# CA-500-N Cantilevered Sign (FOR NZ ONLY)




Top View



Front View



Side View



Framework

## GENERAL CONSTRUCTION NOTES

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION INTENT

### 1. Lightbox Subframe

- 1a. 50x25x3mm aluminium RHS perimeter frame & vertical member.
- 1b. 40x40x3mm aluminium SHS standoffs welded between plates.
- 1c. 10mm aluminium mounting plate.

### 2. Lightbox Faces - Illuminated

- Fabricated 2mm aluminium faces with 27.5mm returns with equally spaced SS 316 grade CSK fixings. Paint heads to match returns.


Computer cut vinyl graphics applied to faces.

### 3. Mounting Plate Cover

- Fabricated 2mm aluminium covers, 2 pack painted R&H charcoal. Fixed to top and bottom of standoffs with SS 316 grade CSK fixings. Paint heads to match returns.

### 4. Wall Fixings

- Nominal galvanised M10 anchors to wall structure to suit site requirements and engineers specifications. Stagger fixings on mounting plate.



Typical Section Detail

Cantilevered Sign - Non-illuminated  
Scale 1:3

## GG-L Glazing Graphics

**GG-L** - Glazing Graphics - Large 500mmH  
**GG-S** - Glazing Graphics - Small 375mmH

### CONSTRUCTION INTENT

#### 1. Glazing Graphics

Profile cut vinyl Ampersand brand mark reverse applied to front door glazing.

If the door is tinted - face apply vinyl graphics to the door glazing.

### APPLICATION NOTES

#### A. Logo Size

Consistent sizes across all sites:  
 Large 500mmH  
 Small 375mmH.

#### B. Clear Space


None.

#### C. Logo Placement

Logo to be aligned to bottom right corner of glazing.




## A/LL-800 Ampersand - Low Level




**AMPERSAND - LOW LEVEL**  
Fabricated brand mark mounted to floor behind  
shopfront glazing. Illuminated or Non-illuminated.  
Refer to following page for details.

- A. Logo Size**  
Consistent sizes across all sites 800mmH.
- B. Clear Space**  
25% logo height.
- C. Logo Placement**  
Logo to be aligned to bottom left or right corner of  
glazing to suit storefront.
- D. Usage**  
Should not be displayed on offices that have a high  
level ampersand (ID2).

## A/LL-800 Ampersand - Low Level




Front View



Side View

**Ampersand - Low Level - Illuminated**  
Scale 1:10

**GENERAL CONSTRUCTION NOTES**

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

**CONSTRUCTION INTENT****1. Ampersand Body**

Profile cut 4mm aluminium back with fabricated 3mm aluminium returns 120mm deep. 2 pac painted to match R&H Gold.

**2. Illuminated Face**

Profile cut 4.5mm opal acrylic with fabricated returns. Face applied translucent vinyl. 2 pac paint returns of faces to match R&H Gold, opaque. S/S countersunk screw fix faces to body returns & paint heads to match returns.

**3. Mounting Plates**


10mm thick aluminium base plates with 4mm thick aluminium gussets fully welded to inside of letters.

**4. Lighting**

Internally illuminated with 6500K cool white LED modules to suppliers specification & layout, fitted to backs. Ensure no shadowing & hot spotting.

**5. Floor Fixings**

Nominal M10 S/S anchors to engineers specification to suit structure at each location.



Side Section A Detail

**Ampersand - Low Level - Illuminated**  
Scale 1:3

## TD-1 Trading Details



### CONSTRUCTION INTENT

#### 1. Trading Details

Trading hours and licensee details applied to storefront entry glazing.

Profile cut white vinyl graphics reverse applied to front door glazing.

If the door is tinted - face apply vinyl graphics to the door glazing.

### APPLICATION NOTES

#### A. Text Size

Opening hours 25mm Cap H.  
Trading Details 15mm Cap H.

#### B. Placement

Text centred on door glazing.

If licensee trading details cannot be centered on entry door it should be placed on nearest window to the right.

## RW-xxx Reception Wall

- RW-200** - 200mmH Reception Logo Illuminated
- RW-200-N** - 200mmH Reception Logo Non-illuminated
- RW-300** - 300mmH Reception Logo Illuminated
- RW-300-N** - 300mmH Reception Logo Non-illuminated

### RECEPTION WALL

Fabricated wordmark logo to wall behind reception desk. Illuminated or Non-illuminated. Refer to following page for details.

#### APPLICATION NOTES

##### A. Logo Size

Consistent sizes across all sites:

- Small 200mmH
- Large 300mmH.

##### B. Clear Space

Minimum clear space is the logo Ampersand height.

##### C. Logo Placement

Logo to be centred horizontally on reception wall. 2000mm AFFL to top of logo.




Typical Reception Wall Elevation  
Scale 1:25

## RW-xxx Reception Wall - Illuminated - Type 1


**RW-200** - 200mmH Reception Logo Illuminated  
**RW-300** - 300mmH Reception Logo Illuminated



Reception Wall - Illuminated  
Scale 1:10



Reception Wall - Illuminated Letters  
Scale 1:1



Reception Wall - Illuminated Ampersand  
Scale 1:1

## GENERAL CONSTRUCTION NOTES

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION INTENT


- 1. Letter Body**  
Profile cut 30mm opal acrylic. Faces & returns 2 pac painted to match R&H Charcoal.
- 2. Letter Cover**  
2 to 3mm opal acrylic diffuser.
- 3. Power Feeds**  
Aluminium sleeves for power feeds.
- 4. Lighting**  
8mm Diode Leds, resin set Inside letter body.
- 5. Wall Fixings**  
20mm Snap Fixings glued to back of lettering and mechanically fixed to wall.
- 6. Trademark Symbol**  
Profile cut 6mm acrylic adhesive fixed to wall, 2 pack painted Charcoal.
- 7. Ampersand Body**  
Profile cut 30mm opal acrylic. Translucent gold vinyl to face and returns 2 pac painted to match R&H Gold.

## RW-xxx Reception Wall - Illuminated - Type 2


**RW-200** - 200mmH Reception Logo Illuminated  
**RW-300** - 300mmH Reception Logo Illuminated



Reception Wall - Illuminated  
Scale 1:10



Reception Wall - Illuminated Letters  
Scale 1:1



Reception Wall - Illuminated Ampersand  
Scale 1:1

## GENERAL CONSTRUCTION NOTES


- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

## CONSTRUCTION INTENT

1. Letter Body  
Halo illuminated letters fabricated stainless steel with returns 30mm deep. 2 pac painted to match R&H Charcoal. S/S countersunk screw fix faces to acrylic mounting blocks & paint heads to match returns.
2. Illuminated Backs  
Profile cut 6mm clear acrylic letter backs.
3. Mounting Blocks  
10mm clear acrylic mounting blocks adhered to backs.
4. Lighting  
6500K LEDs cool white fitted to backs, type & layout to suppliers specification, ensure no shadowing & hot spotting.
5. Wall Fixings  
Nominal M6 S/S anchors or screws to suit site conditions with Ø12mm CHS sleeves to match wall colour.
6. Trademark Symbol  
Profile cut 6mm acrylic adhesive fixed to wall. 2 pack painted Charcoal.
7. Ampersand Body  
Face illuminated ampersand fabricated stainless steel with returns 30mm deep. 2 pac painted to match R&H Gold.
8. Illuminated Faces  
Fabricated 4.5mm opal acrylic face, with returns for fixing to Ampersand body. Face applied translucent vinyl. 2 pac paint returns of faces to match R&H Gold, opaque. S/S countersunk screw fix faces to body & paint heads to match returns.

## RW-xxx-N Reception Wall - Non-illuminated



**RW-200-N** - 200mmH Reception Logo Non-illuminated  
**RW-300-N** - 300mmH Reception Logo Non-illuminated



**GENERAL CONSTRUCTION NOTES**

- All structural members, connections and fixings to structure to be engineered and certified by a structural engineer to suit site conditions.
- Ensure materials have been certified prior to construction in accordance with NCC Part C1 fire resistance and stability to achieve a group 1 or 2 rating.

**CONSTRUCTION INTENT**  
**9. Non-illuminated Letters**  
 Profile cut 10mm acrylic, 2 pac painted R&H Charcoal & Gold, opaque. Adhesive fixed to wall. Use additional pins if required to suit site conditions.



Reception Wall - Non-illuminated  
 Scale 1:10

## RD-1 Reception Desk



Typical Reception Desk Elevation  
Scale 1:25

**CONSTRUCTION INTENT****1. Reception Desk**

Profile cut 3mm acrylic, 2 pack painted to match R&H Gold, adhesive fixed to face of reception desk.

**APPLICATION NOTES****A. Logo Size**

Consistent sizes across all sites 600mmH.

**B. Clear Space**

25% logo height

**C. Logo Placement**

Logo to be preferably right aligned, but may be left aligned if the location has better visibility.

**D. Usage**

To be used where a reception wall is unavailable.

Exemption can be granted where front of desk is on a different angle to reception desk (e.g. Bondi).

## SS-1 Safety Strip

## CONSTRUCTION INTENT

## SECTION I

11. Safety Strip  
Computer cut Metamark M7 frosted vinyl with cut out Ampersand logos reverse applied to shopfront glazing.


## APPLICATION NOTES

#### A. Logo Size


2/3 safety strip height.

## B. Clear Space

1/6 safety strip height.



## R&H Commercial Fascia & Underawning Sign



### FASCIA SIGN

Non-illuminated wordmark logo.  
Refer to following page for details.

### APPLICATION NOTES

#### A. Logo Size

3 standard logo sizes:  
150mmH - Fascias 350 to 490mmH  
175mmH - Fascias 500 to 590mmH  
225mmH - Fascias 600 to 800mmH


#### B. Clear Space

X = clear space top, bottom, & left of logo.  
Logo is centred vertically on the fascia panel & clear space to the left is equal to the space top & bottom.

#### C. Logo Placement

Logo to be preferably left aligned, but may be right aligned if the location has better visibility.

# R&H Rural      Fascia & Underawning Sign



## FASCIA SIGN

Non-illuminated wordmark logo.  
Refer to following page for details.

## APPLICATION NOTES

### A. Logo Size

3 standard logo sizes:  
150mmH - Fascias 350 to 490mmH  
175mmH - Fascias 500 to 590mmH  
225mmH - Fascias 600 to 800mmH


### B. Clear Space

X = clear space top, bottom, & left of logo.  
Logo is centred vertically on the fascia panel & clear space to the left is equal to the space top & bottom.

### C. Logo Placement

Logo to be preferably left aligned, but may be right aligned if the location has better visibility.

# Shopfront Finishes




## General Construction Notes

### 1. Standard Shopfront Finish

Raine & Horne brand charcoal is the primary storefront finish where possible.

### 2. Alternate Shopfront Finish

Contemporary shopfronts with large glazing sections may have white surrounds where suitable, see example below.



Raine & Horne Style Guide Office Signage

## SF-2 Shopfront Cladding

### GENERAL CONSTRUCTION NOTES

#### 1. Shopfront Cladding

Charcoal cladding - "Matt Anthracite Grey Alupanel, FR (Group 2)". Sizes & fixing details to suit each shopfront.



1. Existing Shopfront



2. Example of charcoal cladding

## Typical Elevation      Shopfront Signage Application 1



## Typical Elevation      Shopfront Signage Application 2




5.0


# Internal Applications

Internal applications extend into the specifics of the logo and ampersand placements within the office space.

## Reception Wall Application



## Reception Desk Ampersand



### RECEPTION DESK


A small fabricated ampersand is not to be installed on top of reception desk, unless the 600mm ampersand cannot be installed to face of reception desk.

A large fabricated ampersand is not to be installed next to the reception desk logo.

No elevation/wall should have more than one logo/ampersand.


## Freestanding Ampersand Application

**FREESTANDING AMPERSAND - LOW LEVEL**  
Only 1 x fabricated freestanding ampersand per office.  
The ampersand should be located away from the reception desk.




## Typical Floor Plan Small Office - Signage Application

---



## Typical Floor Plan Large Corner Office - Signage Application




# Optional Applications

The optional applications sector provides a detailed look into all of the elective design features. The intention behind these additional attributes is to elevate the identity of an individual office and create a strong sense of character and presence in the area.

6.0

## Feature Wall

## Wall Panels

**FEATURE WALL**

1 x wall in the reception/lobby area may be used for a branded wall paper application.

This should be a smaller/secondary wall, and no logo is to be installed on top of the feature wall.

The width of the feature wall should not exceed the height of the wall.

**1. Wall Panels**

Surround by Laminex - 1200mmW x 12mm thick Lining Panel MDF Primed Scallop 45mm.

Panels are ready primed to be painted in the desired brand colour to suit the interior.



## Internal Wall Finishes


---

### Internal Wall Finishes

Offices can be painted in white or light grey, or a combination of the two colours.

However, the wall behind the reception desk/or where the main logo is installed should be white.


### Primary Palette



CMYK 0 0 0 0

PAINT ACRYLIC PAINT

Dulux 'Vivid White SW1G1'



0 0 0 5

ACRYLIC PAINT

Dulux 'Terrace white'



10 3 3 90

ACRYLIC PAINT

Dulux 'Night Sky C25'

## Privacy Film PF1 & PF2

### PRIVACY FILM

Privacy film is only to be used where needed – encourage an open transparent work place.

#### PF1


Digitally printed pattern on optically clear vinyl reverse applied to glazing.

#### PF2


Digitally printed pattern on frosted etch vinyl reverse applied to glazing.

1200mm high privacy film to be installed 600 AFFL.

Not to be used on any external facing windows.



Typical Elevation - Privacy Film - PF1  
Scale 1:25



Typical Elevation - Privacy Film - PF2  
Scale 1:25

## Privacy Film PF1 & PF2



Privacy Film - 4000mmW Sample  
Scale 1:10

### PRIVACY FILM

Privacy film is only to be used where needed – encourage an open transparent work place.


#### PF1

Digitally printed pattern (Colour/White/Colour) and applied internally of glazing.

#### PF2

Digitally printed pattern onto dusted etch. (Colour/White/Colour) and applied internally of glazing.  
1200mm high privacy film to be installed 600 AFFL.  
Not to be used on any external facing windows.

## Wall Paper



### WALL PAPER

Digitally printed wallpaper.

90mmH Ampersands, with pattern centred on wall.

No Ampersands to be "cut off" on edges.

## Wall Paper

**WALL PAPER**  
Digitally printed wallpaper.



Graphic 1 - Raine & Horne Poster Wallpaper



Graphic 2 - Raine & Horne, 1900



Graphic 3 - Raine & Horne Staff 1920



Graphic 4 - Property Management Department 1920



Graphic 5 - Raine Chambers, Pitt Street Sydney

## Wall Graphic



**WALL GRAPHIC**  
Wall painted R&H Charcoal. Stencil paint/mask and spray oversized white ampersand direct to wall, 20mm stroke width.  
Only to be applied to a charcoal wall.

# 7.0

## Engineering Certificates

The optional applications sector provides a detailed look into all of the elective design features. The intention behind these additional attributes is to elevate the identity of an individual office and create a strong sense of character and presence in the area.

## Engineering A/HL-1350

**RE** ROBUST Consulting Engineers Pty Ltd  
Civil & Structural, ABN 14 626 910 750

Suite 7, 750 Blackburn Rd, Clayton, Vic 3168  
0418133012, (+613) 85102535  
www.robustengineers.com.au  
suresh@robustengineers.com.au

**STRUCTURAL ENGINEERING COMPUTATIONS**

PROJECT: Raine & Horne A/HL-1350  
Letter Signage (1.35x1.197)

CLIENT: TBP

ADDRESS: Generic Computation for  
Australia (Wind Region A-C)  
(To be used in conjunction with Design Compliance Certificate)

REVISION: 0

PROJECT CODE: TBP126  
PREPARED BY: BB

**CERTIFIED BY**  
*Suresh Hada*

**Suresh Hada**  
FIEAust, CPEng, NER, IPENZ  
Chartered Professional Engineer  
Membership No. 2621329  
AUSTRALIA

Vic: Registered Professional Engineer, Civil Engineer – PE0002632  
NSW: Registered Structural Engineer Reg No. BPB 2816  
Qld: Registered Professional Engineer of Qld, Div Structural RPEQ 15255  
Tas: Accredited Certifier, Div. Civil (Building Act 2000, Tas) CC6337  
NT: Certifying Engineer (Structural) Reg No. 227617ES


Date: 27/June/2024

This document contains confidential information and intellectual property owned by Robust Consulting Engineering Pty Ltd and are subject to copyright, patents and intellectual property rights. Copying, disclosing or using any part of this document is expressly prohibited without written permission from Robust Consulting Engineering Pty Ltd.

Raine & Horne A/HL-1350		Project Code: TBP126																																																							
Scope: Provide engineering design and details for wall mounted sign as per drawing/sketch in this computation sheet																																																									
<ol style="list-style-type: none"> <li>Design loads to be considered           <ul style="list-style-type: none"> <li>DL Sign dead load [self weight]</li> <li>WL Wind load</li> <li>EL Earthquake load as applicable</li> </ul> </li> <li>Design and detail letter structural arrangement</li> <li>Design and detail support frame structure</li> <li>Design and detail fixings to existing wall structure</li> </ol>																																																									
Assumptions: Computation is based on the drawing submitted by the client																																																									
<table border="1"> <thead> <tr> <th>Materials:</th> <th>f<sub>y</sub> (Mpa)</th> <th>f<sub>u</sub> (MPa)</th> </tr> </thead> <tbody> <tr> <td>Hot Rolled</td> <td>UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)</td> <td>300</td> <td>440</td> </tr> <tr> <td></td> <td>Plate: Grade 250 (AS/NZS 3678 - 2011)</td> <td>250</td> <td>410</td> </tr> <tr> <td>Cold Formed</td> <td>SHS: Grade C450 (AS1163 - 2009)</td> <td>450</td> <td>500</td> </tr> <tr> <td></td> <td>RHS: Grade C450 (AS 1163 - 2009)</td> <td>450</td> <td>500</td> </tr> <tr> <td></td> <td>CHS: Grade C350 (AS 1163 - 2009)</td> <td>350</td> <td>430</td> </tr> <tr> <td></td> <td>CA: Cold-formed angle (Duragal)</td> <td>350</td> <td>400</td> </tr> <tr> <td></td> <td>CC: Cold formed channels (Duragal)</td> <td>400</td> <td>450</td> </tr> <tr> <td></td> <td>CF: Cold-formed flats (Duragal)</td> <td>350</td> <td>400</td> </tr> <tr> <td>Bolts</td> <td>Bolts (4.6/5) - [Commercial]</td> <td>240</td> <td>400</td> </tr> <tr> <td></td> <td>Bolts (8.8/5) - [High Strength Structural]</td> <td>660</td> <td>830</td> </tr> <tr> <td>Welds</td> <td>Welding - Category: General Purpose</td> <td>GP</td> <td>410</td> </tr> <tr> <td></td> <td>Welding - Category: Structural Purpose</td> <td>SP</td> <td>410</td> </tr> <tr> <td>Concrete:</td> <td>Grade N25 [f'c @ 28 days]</td> <td>25</td> <td>MPa</td> </tr> </tbody> </table>			Materials:	f <sub>y</sub> (Mpa)	f <sub>u</sub> (MPa)	Hot Rolled	UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)	300	440		Plate: Grade 250 (AS/NZS 3678 - 2011)	250	410	Cold Formed	SHS: Grade C450 (AS1163 - 2009)	450	500		RHS: Grade C450 (AS 1163 - 2009)	450	500		CHS: Grade C350 (AS 1163 - 2009)	350	430		CA: Cold-formed angle (Duragal)	350	400		CC: Cold formed channels (Duragal)	400	450		CF: Cold-formed flats (Duragal)	350	400	Bolts	Bolts (4.6/5) - [Commercial]	240	400		Bolts (8.8/5) - [High Strength Structural]	660	830	Welds	Welding - Category: General Purpose	GP	410		Welding - Category: Structural Purpose	SP	410	Concrete:	Grade N25 [f'c @ 28 days]	25	MPa
Materials:	f <sub>y</sub> (Mpa)	f <sub>u</sub> (MPa)																																																							
Hot Rolled	UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)	300	440																																																						
	Plate: Grade 250 (AS/NZS 3678 - 2011)	250	410																																																						
Cold Formed	SHS: Grade C450 (AS1163 - 2009)	450	500																																																						
	RHS: Grade C450 (AS 1163 - 2009)	450	500																																																						
	CHS: Grade C350 (AS 1163 - 2009)	350	430																																																						
	CA: Cold-formed angle (Duragal)	350	400																																																						
	CC: Cold formed channels (Duragal)	400	450																																																						
	CF: Cold-formed flats (Duragal)	350	400																																																						
Bolts	Bolts (4.6/5) - [Commercial]	240	400																																																						
	Bolts (8.8/5) - [High Strength Structural]	660	830																																																						
Welds	Welding - Category: General Purpose	GP	410																																																						
	Welding - Category: Structural Purpose	SP	410																																																						
Concrete:	Grade N25 [f'c @ 28 days]	25	MPa																																																						
Regulation & Codes: BCA - 2024: Building Code of Australia - 2024 AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles. AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed & other actions. AS/NZS 1170.2 - 2011: Structural design actions Part 2: Wind actions. AS 1170.4 - 2007: Structural design actions Part 4: Earthquake actions in Australia. AS 3600 - 2018: Concrete structures. AS 4100 - 2020: Steel structures. AS/NZS 4600 - 2018: Cold-formed steel structures.																																																									

Page: 2

## Engineering A/HL-1350



<b>Raine &amp; Horne A/HL-1350</b>		<b>Project Code: TBP126</b>	
<b>Sign Dimension &amp; Wind Pressure</b>			
Description	Parameter	Value	Unit
Signage face height	$h_s$	1.35	m
Signage total height	$h$	1.35	m
Signage average width	$b$	1.20	m
Proportion of cladded area	$A_c$	1.00	-
Signage total area	$A_s$	1.62	$m^2$
Height of datum above NGL (z = 0)	$h_d$	3.90	m
Height above NGL (rounded up)	$z$	6	m
<b>Select sign location</b>		Windward wall	
Wind region	WR	C	-
Importance Level	IL	2	-
Terrain Category	TC	3	-
Average Recurrence Interval	R	500	-
Regional wind speed	$V_R$	69.0	m/s
Dynamic response factor	$C_{dyn}$	1.00	-
Area reduction factor	$k_a$	1.00	-
Combination factor	$k_c$	1.00	-
Local pressure factor	$k_l \times C_{pe}$	0.80	-
Porous cladding factor	$k_p$	1.00	-
Aerodynamic Factor ( $C_{fig} = C_{pe} \cdot k_a \cdot k_c \cdot k_l \cdot k_p$ )	$C_{fig}$	0.80	-
Terrain & height multiplier	$M_z$	0.83	-
Pressure at ht z	$p_z$	1.97	kPa
Strength design pressure	$p_d$	1.57	kPa
Serviceability design pressure	$p_s$	1.05	kPa
<b>Total wind load on entire signage</b>	$W_s$	<b>2.6</b>	kN
<b>Signage self weight</b>	<b>G</b>	<b>0.4</b>	kN

## Engineering A/HL-1350


Raine & Horne A/HL-1350		Project Code: TBP126		
<b>Bolt letter fixing</b>				
Description	Parameter	Value	Unit	
Assume calculation is per letter, and shape rectangular				
Letter Height	h	1.35	m	
Letter Width	b	1.20	m	
Letter Area	A	1.62	$m^2$	
Ultimate wind load on whole sign	WL <sub>uls</sub>	2.55	kN	
Deadload per letter (factor of 1.3)	DL	3.32	kN	
Average number of bolt connection	n	3		
Tension per bolt	N <sub>t</sub>	0.85	kN	
Shear per bolt	V <sub>b</sub>	1.11	kN	
<b>Using, M10 (SS Class 50)</b>				
Bolt tensile strength	$\phi N_{uc}$	18.56	kN	
Bolt shear strength	$\phi V_{us}$	10.38	kN	
N / $\phi N_{uc}$	$\eta_t$	0.05	$\leq 1$ OK	
V / $\phi V_{us}$	$\eta_v$	0.11	$\leq 1$ OK	
Check unity	$c_u$	0.15	$\leq 1.2$ OK	
2xM10 (SS Class 50) bolts for each letter fixing to metal façade (0.48BMT) as shown in page 7. along with additional 7 screws .				
M8 Coach screw's to timber for Emb depth 30mm. Pull-out capacity = 16.21kN. OK				
M10 bolt's to concrete for Emb depth 90mm. Pull-out capacity = 13.6kN. OK				
<u>See recommended fixings in the next page (6).</u>				

Page: 5

Raine & Horne A/HL-1350		Project Code: TBP126	
<b>Connection Specifications to various Strata:</b>			
<b>Strata</b>			<b>Fixing requirement for Region A,B &amp; C</b>
1) Metal wall			Minimum 3xM10 bolts to either Girt or stud + Minimum of 7-ST 5.8 (#12) screws to metal façade 0.48 BMT (uniformly distributed).
2) Timber			Minimum 3xM8 coach screws to either Gurt or stud + Minimum of 7-ST 5.8 (#12) screws to metal façade.
3) Concrete			7xM10(4.6/5) Chemset bolts. Embedment depth= 90mm.
4) Structural tube sections			Steel SHS or RHS minimum thickness of 3mm. Minimum 3 x M16x75mm Hollow bolts + Minimum of 7-ST 5.8 (#12) screws to metal facade (uniformly distributed).

Page: 6

## Engineering A/HL-1350



**Building Act 1993**  
**Section 238(1)(a)**  
**Building Regulations 2018**  
**Regulation 126**

**CERTIFICATE OF COMPLIANCE FOR PROPOSED BUILDING WORK**

**This certificate is issued to** Relevant building surveyor

**Postal address (if applicable)**

**Email**

**This certificate is issued in relation to the proposed building work at:**

**Address of** Generic Computation for  
**State** Australia (Wind Region A-C)

**Nature of proposed building work**

**Construction of:** a new signage  
**Height:**  
**Type of Construction:** Steel, Concrete or Timber Strata

**Version of BCA applicable to certificate**

**Building classification**  
**Part of building:** Signage      **BCA Classification:** Class 10b

**Prescribed class of building work for which this certificate is issued:**  
Design or part of the design of building work relating to      Signage

**Documents setting out the design that is certified by this certificate**

Document no.	Document date	Type of document (e.g. drawings, Computations, specifications, calculations etc.)	No. of pages	Prepared by
TBP126	6/27/2024	Structural Engineering Computations	7	BB

Approved by the Victorian Building Authority

Page 1 of 2

## Engineering A/HL-1350

<p>The design certified by this certificate complies with the following provisions of Building Act 1993, Building Regulations 2018 or National Construction Code</p>	
<b>Act, Regulation or NCC</b>	<b>Section, Regulation, Part, Performance Requirement or other provision</b>
NCC	National Construction Code 2022
Australian Standard	AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.
Australian Standard	AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed & other actions.
Australian Standard	AS/NZS 1170.2 - 2021: Structural design actions Part 2: Wind actions.
Australian Standard	AS 3600 - 2018: Concrete structures
Australian Standard	AS 4100 - 2020: Steel structures.
Australian Standard	AS/NZS 4600 - 2018: Cold-formed steel structures.
Australian Standard	AS/NZS 5131 - 2016: Structural steelwork-Fabrication and erections. -CC2

I prepared the design, or part of the design, set out in the documents listed above.

I certify that the design set out in the documents listed above complies with the provisions set out above.

I believe that I hold the required skills, experience and knowledge to issue this certificate and can demonstrate this if requested to do so.

**Engineer**  
 Name: **Suresh Hada**  
 Address **Suite 7, 750 Blackburn Rd, Clayton 3168**  
 Category and class: **Engineer Civil**  
 Registration No: **PE0002632**  
 Date of issue of certificate: **27/Jun/2024**  
 Signature:

*Suresh Hada*


**Suresh Hada**  
 FIEAust, CPEng, NER, IPENZ  
 Chartered Professional Engineer  
 Membership No. 2621329

Vic: Registered Professional Engineer, Civil Engineer – PE0002632  
 NSW: Registered Certifier- Structural Engineer Reg No. BPB 2816  
 Qld: Registered Professional Engineer of Qld, Div: Structural RPEQ 15255  
 Tas: Accredited Certifier, Div: Civil (Building Act 2000, Tas) CC6537  
 NT: Certifying Engineer (Structural) Reg No. 227617ES

Approved by the Victorian Building Authority

Page 2 of 2

## Engineering CA-750 &amp; CA-500

**RE** ROBUST Consulting Engineers Pty Ltd  
Civil & Structural, ABN 14 626 910 750

Suite 7, 750 Blackburn Rd, Clayton, Vic 3168  
0418133012, (+613) 85102535  
www.robustengineers.com.au  
suresh@robustengineers.com.au

**STRUCTURAL ENGINEERING COMPUTATIONS**

PROJECT: Raine & Horne CA750  
Cantilevered Sign (0.75x0.75)

CLIENT: Theblueprint

ADDRESS: Generic Computation for  
Australia (Wind Region A)  
(To be used in conjunction with Design Compliance Certificate)

REVISION: 1

PROJECT CODE: TBP126  
PREPARED BY: A.R

**CERTIFIED BY**

*Suresh Hada*

**Suresh Hada**  
FIEAust, CPEng, NER, IPENZ  
Chartered Professional Engineer  
Membership No. 2621329

Engineers Australia logo

Vic: Registered Professional Engineer, Civil Engineer – PE0002632  
NSW: Registered Certifier - Structural Engineer Reg No. BPB 2816  
Qld: Registered Professional Engineer of Qld, Div: Structural RPEQ 15255  
Tas: Accredited Certifier, Div: Civil Building Act 2000, Tas) CC6537  
NT: Certifying Engineer (Structural) Reg No. 227617ES


Date: 02/July/2024

This document contains confidential information and intellectual property owned by Robust Consulting Engineering Pty Ltd and are subject to copyright, patents and intellectual property rights. Copying, disclosing or using any part of this document is expressly prohibited without written permission from Robust Consulting Engineering Pty Ltd.

Raine & Horne A/HL-1350		Project Code: TBP126						
Scope:								
Provide engineering design and details for wall mounted sign as per drawing/sketch in this computation sheet								
<ol style="list-style-type: none"> <li>Design loads to be considered           <table> <tr> <td>DL</td> <td>Sign dead load [self weight]</td> </tr> <tr> <td>WL</td> <td>Wind load</td> </tr> <tr> <td>EL</td> <td>Earthquake load as applicable</td> </tr> </table> </li> <li>Design and detail letter structural arrangement</li> <li>Design and detail support frame structure</li> <li>Design and detail fixings to existing wall structure</li> </ol>			DL	Sign dead load [self weight]	WL	Wind load	EL	Earthquake load as applicable
DL	Sign dead load [self weight]							
WL	Wind load							
EL	Earthquake load as applicable							
Assumptions: Computation is based on the drawing submitted by the client								
<b>Materials:</b> Hot Rolled UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010) 300 440 Plate: Grade 250 (AS/NZS 3678 - 2011) 250 410 Cold Formed SHS: Grade C450 (AS1163 - 2009) 450 500 RHS: Grade C450 (AS 1163 - 2009) 450 500 CHS: Grade C350 (AS 1163 - 2009) 350 430 CA: Cold-formed angle (Duragal) 350 400 CC: Cold formed channels (Duragal) 400 450 CF: Cold-formed flats (Duragal) 350 400 Bolts (4.6/5) - [Commercial] 240 400 Bolts (8.8/5) - [High Strength Structural] 660 830 Welds Welding - Category: General Purpose GP 410 Welding - Category: Structural Purpose SP 410 Concrete: Grade N25 [f'c @ 28 days] 25 MPa								
<b>Regulation &amp; Codes:</b> BCA - 2024: Building Code of Australia - 2024 AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles. AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed & other actions. AS/NZS 1170.2 - 2011: Structural design actions Part 2: Wind actions. AS 1170.4 - 2007: Structural design actions Part 4: Earthquake actions in Australia. AS 3600 - 2018: Concrete structures. AS 4100 - 2020: Steel structures. AS/NZS 4600 - 2018: Cold-formed steel structures.								

Page: 2

# Engineering CA-750 & CA-500




## Engineering CA-750 &amp; CA-500

Raine & Horne CA750		Project Code: TBP126	
<b>Vertical Member (SHS), Base Plate &amp; Chemset Anchor</b>			
Description	Parameter	Value	Unit
Modulus of elasticity	E	70.0E+3	MPa
Total height of sign	h	0.80	m
Height to centre of area	$\bar{y}$	0.40	m
<i>Max design SF in one vertical support</i>	$V^*$	0.30	kN
<i>Max design Moment in one vertical support</i>	$M^*$	0.08	kNm
SF in one vertical support - Serviceability	$V_{ser}^*$	3.98	kN
Moment in one vertical support - Serviceability	$M_{ser}^*$	13.76	kNm
Designed Vertical Member: 40x20x3mm	Grade:	6060TS	
ChemSet REO 502 Plus			
Bolt lever arm	Bolt Spec	M12(5.8)	mm
Design tensile load per bolt	j	45.00	
Design shear load per bolt	N*	0.91	kN
	V*	0.06	kN
Output Description (Strength Limit State Design)		Output Data (per anchor)	
<b>DESIGN O.K.</b>		MIN. CRITERIA for a & b - O.K.	
Des.Pullout & CONC.Tensile Capacity	$\phi N_{sr} =$	12.3	kN
Design STEEL Tensile Capacity	$\phi N_{sr} =$	18.9	kN
Design CONC. Edge Shear Capacity	$\phi V_{sr} =$	69.4	kN
Design STEEL Shear Capacity	$\phi V_{sr} =$	11.8	kN
Design Pryout Failure	$\phi V_{sr} =$	22.2	kN
Drill hole diameter	$d_h =$	12	mm
<b>TENSION O.K.</b>			
Design Tensile Capacity	$\phi N_{sr} =$	12.3	kN
Tension Design Check	$N^*/\phi N_{sr} =$	0.08	< 1
<b>shear O.K.</b>			
Design Shear Capacity	$\phi V_{sr} =$	11.8	kN
Shear Design Check	$V^*/\phi V_{sr} =$	0.08	< 1
<b>COMBINED TENSION SHEAR O.K.</b>			
Combined Check - $N^*/\phi N_{sr} + V^*/\phi V_{sr} =$		0.17	< 1.2
Depth of vertical section	d	40	mm
Width of vertical section	b	40	mm
Base plate length	$l_p$	90	mm
Base plate width	$B_p$	650	mm
Base plate thickness	$t_p$	16	mm
Yield Stress for base plate	$f_y$	100	MPa
Reduced yield stress value	$0.9*f_y$	90	MPa
Plastic moment on base plate	$m_p$	0.00	kNm
Base plate minimum thickness	$t_{p,min}$	0	mm
Ratio plate plastic moment design	$t_p/t_{p,min}$	0.03	$\leq 1$ OK
Designed Bolts: Adopt 5x ChemSet REO 502 Plus M12(5.8) Emb = 110 (galvanised)			
Designed Plate: Adopt 16Pl x 90 x 650 Grade 100			
Therefore 40 x 20 x 3mm use as horizontal sign frame is OKAY			

Page: 5

Page: 6

# Engineering CA-750 & CA-500



# Engineering CA-750 & CA-500

<b>Building Act 1993</b> <i>Section 238(1)(a)</i> <b>Building Regulations 2018</b> <i>Regulation 126</i>				
<b>CERTIFICATE OF COMPLIANCE FOR PROPOSED BUILDING WORK</b>				
<b>This certificate is issued to</b>	Relevant building surveyor			
Postal address (if applicable)				
Email				
<b>This certificate is issued in relation to the proposed building work at:</b>				
Address of	Generic Computation for			
State	Australia (Wind Region A)			
<b>Nature of proposed building work</b>				
Construction of:	a new signage			
Height:				
Type of Construction:	Bolts and frame			
Version of BCA applicable to certificate:	NCC 2022			
<b>Building classification</b>				
Part of building:	Signage	NCC Classification:	Class 10b	
<b>Prescribed class of building work for which this certificate is issued:</b>				
Design or part of the design of building work relating to Signage				
<b>Documents setting out the design that is certified by this certificate</b>				
Document no.	Document date	Type of document (e.g. drawings, Computations, specifications, calculations etc.)	No. of pages	Prepared by
TBP126	2/07/2024	Structural Engineering Computations	8	A.R
Approved by the Victorian Building Authority		Page 1 of 2		

The design certified by this certificate complies with the following provisions of Building Act 1993, Building Regulations 2018 or National Construction Code

Act, Regulation or NCC	Section, Regulation, Part, Performance Requirement or other provision
NCC	National Construction Code 2022
Australian Standard	AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.
Australian Standard	AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed & other actions.
Australian Standard	AS/NZS 1170.2 - 2021: Structural design actions Part 2: Wind actions.
Australian Standard	AS 3600 - 2018: Concrete structures
Australian Standard	AS 4100 - 2020: Steel structures.
Australian Standard	AS/NZS 4600 - 2018: Cold-formed steel structures.
Australian Standard	AS/NZS 5131 - 2016: Structural steelwork-Fabrication and erections. -CC2

I prepared the design, or part of the design, set out in the documents listed above.

I certify that the design set out in the documents listed above complies with the provisions set out above.

I believe that I hold the required skills, experience and knowledge to issue this certificate and can demonstrate this if requested to do so.

**Engineer**  
Name: **Suresh Hada**  
Address Suite 7, 750 Blackburn Rd, Clayton 3168  
Category and class: **Engineer Civil**  
Registration No: **PE0002632**  
Date of Issue of certificate: **2/Jul/2024**  
Signature: 



**Suresh Hada**  
FIEAust, CPEng, NER, IPENZ  
Chartered Professional Engineer  
Membership No. 2621329

Vic: Registered Professional Engineer, Civil Engineer – PE0002632  
NSW: Registered Certifier- Structural Engineer Reg No. BPB 2816  
Qld: Registered Professional Engineer of Qld, Div: Structural RPEQ 15255  
Tas: Accredited Certifier, Div: Civil (Building Act 2000, Tas) CCE6537  
NT: Certifying Engineer (Structural) Reg No. 227617ES

Approved by the Victorian Building Authority	Page 2 of 2
--	-------------


# Engineering Fascia & Transom

<div style="text-align: center; padding: 10px;">  <b>ROBUST Consulting Engineers Pty Ltd</b>          Civil &amp; Structural, ABN 14 626 910 750         <hr/> <p><b>STRUCTURAL ENGINEERING COMPUTATIONS</b></p> <p>PROJECT: Raine &amp; Horne FA-225-N &amp; TR-225-N Fascia Signage (2.4mx0.65m)      CLIENT: TBP</p> <p>ADDRESS: Generic computation for Australia (Wind Region A-C) (To be used in conjunction with Design Compliance Certificate)      REVISION: 0</p> <p>PROJECT CODE: TBP126      PREPARED BY: BB</p> <hr/> <p><b>CERTIFIED BY</b></p> <p><i>Suresh Hada</i></p> <div style="border: 1px solid black; padding: 5px; text-align: center;">  <b>Suresh Hada</b>          FIEAust, CPEng, NER, IPENZ          Chartered Professional Engineer          Membership No. 2621329  <small>AUSTRALIA</small> </div> <p>Vic: Registered Professional Engineer, Civil Engineer – PE0002632          NSW: Registered Structural Engineer Reg No. BPB 2816          Qld: Registered Professional Engineer of Qld, Div Structural RPEQ 15255          Tas: Accredited Certifier, Div. Civil (Building Act 2000, Tas) CC6337          NT: Certifying Engineer (Structural) Reg No. 227617ES</p> <p>Date: 28/June/2024</p> </div> <div style="border: 1px solid black; padding: 10px; margin-top: 10px;"> <p><b>RE</b> Suite 7, 750 Blackburn Rd, Clayton, Vic 3168          0418133012, (+613) 85102535  <a href="http://www.robustengineers.com.au">www.robustengineers.com.au</a>  <a href="mailto:suresh@robustengineers.com.au">suresh@robustengineers.com.au</a></p> </div>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; padding: 5px;"> <b>Raine &amp; Horne FA-225-N &amp; TR-225-N</b> </td> <td style="width: 50%; padding: 5px;"> <b>Project Code: TBP126</b> </td> </tr> <tr> <td colspan="2" style="padding: 5px;"> <b>Scope:</b>          Provide engineering design and details for wall mounted sign as per drawing/sketch in this computation sheet       </td> </tr> <tr> <td colspan="2" style="padding: 5px;">         1. Design loads to be considered          DL Sign dead load [self weight]          WL Wind load          EL Earthquake load as applicable          2. Design and detail letter structural arrangement          3. Design and detail support frame structure          4. Design and detail fixings to existing wall structure       </td> </tr> <tr> <td colspan="2" style="padding: 5px;"> <b>Assumptions:</b> Computation is based on the drawing submitted by the client       </td> </tr> <tr> <td colspan="2" style="padding: 5px;"> <b>Materials:</b> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;"></td> <td style="width: 40%; text-align: left;">fy (Mpa)</td> <td style="width: 40%; text-align: left;">fu (MPa)</td> </tr> <tr> <td>Hot Rolled</td> <td>UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)</td> <td>300 440</td> </tr> <tr> <td></td> <td>Plate: Grade 250 (AS/NZS 3678 - 2011)</td> <td>250 410</td> </tr> <tr> <td></td> <td>SHS: Grade C450 (AS1163 - 2009)</td> <td>450 500</td> </tr> <tr> <td></td> <td>RHS: Grade C450 (AS 1163 - 2009)</td> <td>450 500</td> </tr> <tr> <td></td> <td>CHS: Grade C350 (AS 1163 - 2009)</td> <td>350 430</td> </tr> <tr> <td></td> <td>CA: Cold-formed angle (Duragal)</td> <td>350 400</td> </tr> <tr> <td></td> <td>CC: Cold formed channels (Duragal)</td> <td>400 450</td> </tr> <tr> <td></td> <td>CF: Cold-formed flats (Duragal)</td> <td>350 400</td> </tr> <tr> <td>Bolts</td> <td>Bolts (4.6/5) - [Commercial]</td> <td>240 400</td> </tr> <tr> <td></td> <td>Bolts (8.8/5) - [High Strength Structural]</td> <td>660 830</td> </tr> <tr> <td>Welds</td> <td>Welding - Category: General Purpose</td> <td>GP 410</td> </tr> <tr> <td></td> <td>Welding - Category: Structural Purpose</td> <td>SP 410</td> </tr> <tr> <td>Concrete:</td> <td>Grade N25 [f'c @ 28 days]</td> <td>25 MPa</td> </tr> </table> </td> </tr> <tr> <td colspan="2" style="padding: 5px;"> <b>Regulation &amp; Codes:</b> <ul style="list-style-type: none"> <li>BCA - 2024: Building Code of Australia - 2024</li> <li>AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.</li> <li>AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed &amp; other actions.</li> <li>AS/NZS 1170.2 - 2011: Structural design actions Part 2: Wind actions.</li> <li>AS 1170.4 - 2007: Structural design actions Part 4: Earthquake actions in Australia.</li> <li>AS 3600 - 2018: Concrete structures.</li> <li>AS 4100 - 2020: Steel structures.</li> <li>AS/NZS 4600 - 2018: Cold-formed steel structures.</li> </ul> </td> </tr> </table>	<b>Raine &amp; Horne FA-225-N &amp; TR-225-N</b>	<b>Project Code: TBP126</b>	<b>Scope:</b> Provide engineering design and details for wall mounted sign as per drawing/sketch in this computation sheet		1. Design loads to be considered DL Sign dead load [self weight] WL Wind load EL Earthquake load as applicable 2. Design and detail letter structural arrangement 3. Design and detail support frame structure 4. Design and detail fixings to existing wall structure		<b>Assumptions:</b> Computation is based on the drawing submitted by the client		<b>Materials:</b> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;"></td> <td style="width: 40%; text-align: left;">fy (Mpa)</td> <td style="width: 40%; text-align: left;">fu (MPa)</td> </tr> <tr> <td>Hot Rolled</td> <td>UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)</td> <td>300 440</td> </tr> <tr> <td></td> <td>Plate: Grade 250 (AS/NZS 3678 - 2011)</td> <td>250 410</td> </tr> <tr> <td></td> <td>SHS: Grade C450 (AS1163 - 2009)</td> <td>450 500</td> </tr> <tr> <td></td> <td>RHS: Grade C450 (AS 1163 - 2009)</td> <td>450 500</td> </tr> <tr> <td></td> <td>CHS: Grade C350 (AS 1163 - 2009)</td> <td>350 430</td> </tr> <tr> <td></td> <td>CA: Cold-formed angle (Duragal)</td> <td>350 400</td> </tr> <tr> <td></td> <td>CC: Cold formed channels (Duragal)</td> <td>400 450</td> </tr> <tr> <td></td> <td>CF: Cold-formed flats (Duragal)</td> <td>350 400</td> </tr> <tr> <td>Bolts</td> <td>Bolts (4.6/5) - [Commercial]</td> <td>240 400</td> </tr> <tr> <td></td> <td>Bolts (8.8/5) - [High Strength Structural]</td> <td>660 830</td> </tr> <tr> <td>Welds</td> <td>Welding - Category: General Purpose</td> <td>GP 410</td> </tr> <tr> <td></td> <td>Welding - Category: Structural Purpose</td> <td>SP 410</td> </tr> <tr> <td>Concrete:</td> <td>Grade N25 [f'c @ 28 days]</td> <td>25 MPa</td> </tr> </table>			fy (Mpa)	fu (MPa)	Hot Rolled	UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)	300 440		Plate: Grade 250 (AS/NZS 3678 - 2011)	250 410		SHS: Grade C450 (AS1163 - 2009)	450 500		RHS: Grade C450 (AS 1163 - 2009)	450 500		CHS: Grade C350 (AS 1163 - 2009)	350 430		CA: Cold-formed angle (Duragal)	350 400		CC: Cold formed channels (Duragal)	400 450		CF: Cold-formed flats (Duragal)	350 400	Bolts	Bolts (4.6/5) - [Commercial]	240 400		Bolts (8.8/5) - [High Strength Structural]	660 830	Welds	Welding - Category: General Purpose	GP 410		Welding - Category: Structural Purpose	SP 410	Concrete:	Grade N25 [f'c @ 28 days]	25 MPa	<b>Regulation &amp; Codes:</b> <ul style="list-style-type: none"> <li>BCA - 2024: Building Code of Australia - 2024</li> <li>AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.</li> <li>AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed &amp; other actions.</li> <li>AS/NZS 1170.2 - 2011: Structural design actions Part 2: Wind actions.</li> <li>AS 1170.4 - 2007: Structural design actions Part 4: Earthquake actions in Australia.</li> <li>AS 3600 - 2018: Concrete structures.</li> <li>AS 4100 - 2020: Steel structures.</li> <li>AS/NZS 4600 - 2018: Cold-formed steel structures.</li> </ul>	
<b>Raine &amp; Horne FA-225-N &amp; TR-225-N</b>	<b>Project Code: TBP126</b>																																																						
<b>Scope:</b> Provide engineering design and details for wall mounted sign as per drawing/sketch in this computation sheet																																																							
1. Design loads to be considered DL Sign dead load [self weight] WL Wind load EL Earthquake load as applicable 2. Design and detail letter structural arrangement 3. Design and detail support frame structure 4. Design and detail fixings to existing wall structure																																																							
<b>Assumptions:</b> Computation is based on the drawing submitted by the client																																																							
<b>Materials:</b> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;"></td> <td style="width: 40%; text-align: left;">fy (Mpa)</td> <td style="width: 40%; text-align: left;">fu (MPa)</td> </tr> <tr> <td>Hot Rolled</td> <td>UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)</td> <td>300 440</td> </tr> <tr> <td></td> <td>Plate: Grade 250 (AS/NZS 3678 - 2011)</td> <td>250 410</td> </tr> <tr> <td></td> <td>SHS: Grade C450 (AS1163 - 2009)</td> <td>450 500</td> </tr> <tr> <td></td> <td>RHS: Grade C450 (AS 1163 - 2009)</td> <td>450 500</td> </tr> <tr> <td></td> <td>CHS: Grade C350 (AS 1163 - 2009)</td> <td>350 430</td> </tr> <tr> <td></td> <td>CA: Cold-formed angle (Duragal)</td> <td>350 400</td> </tr> <tr> <td></td> <td>CC: Cold formed channels (Duragal)</td> <td>400 450</td> </tr> <tr> <td></td> <td>CF: Cold-formed flats (Duragal)</td> <td>350 400</td> </tr> <tr> <td>Bolts</td> <td>Bolts (4.6/5) - [Commercial]</td> <td>240 400</td> </tr> <tr> <td></td> <td>Bolts (8.8/5) - [High Strength Structural]</td> <td>660 830</td> </tr> <tr> <td>Welds</td> <td>Welding - Category: General Purpose</td> <td>GP 410</td> </tr> <tr> <td></td> <td>Welding - Category: Structural Purpose</td> <td>SP 410</td> </tr> <tr> <td>Concrete:</td> <td>Grade N25 [f'c @ 28 days]</td> <td>25 MPa</td> </tr> </table>			fy (Mpa)	fu (MPa)	Hot Rolled	UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)	300 440		Plate: Grade 250 (AS/NZS 3678 - 2011)	250 410		SHS: Grade C450 (AS1163 - 2009)	450 500		RHS: Grade C450 (AS 1163 - 2009)	450 500		CHS: Grade C350 (AS 1163 - 2009)	350 430		CA: Cold-formed angle (Duragal)	350 400		CC: Cold formed channels (Duragal)	400 450		CF: Cold-formed flats (Duragal)	350 400	Bolts	Bolts (4.6/5) - [Commercial]	240 400		Bolts (8.8/5) - [High Strength Structural]	660 830	Welds	Welding - Category: General Purpose	GP 410		Welding - Category: Structural Purpose	SP 410	Concrete:	Grade N25 [f'c @ 28 days]	25 MPa												
	fy (Mpa)	fu (MPa)																																																					
Hot Rolled	UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)	300 440																																																					
	Plate: Grade 250 (AS/NZS 3678 - 2011)	250 410																																																					
	SHS: Grade C450 (AS1163 - 2009)	450 500																																																					
	RHS: Grade C450 (AS 1163 - 2009)	450 500																																																					
	CHS: Grade C350 (AS 1163 - 2009)	350 430																																																					
	CA: Cold-formed angle (Duragal)	350 400																																																					
	CC: Cold formed channels (Duragal)	400 450																																																					
	CF: Cold-formed flats (Duragal)	350 400																																																					
Bolts	Bolts (4.6/5) - [Commercial]	240 400																																																					
	Bolts (8.8/5) - [High Strength Structural]	660 830																																																					
Welds	Welding - Category: General Purpose	GP 410																																																					
	Welding - Category: Structural Purpose	SP 410																																																					
Concrete:	Grade N25 [f'c @ 28 days]	25 MPa																																																					
<b>Regulation &amp; Codes:</b> <ul style="list-style-type: none"> <li>BCA - 2024: Building Code of Australia - 2024</li> <li>AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.</li> <li>AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed &amp; other actions.</li> <li>AS/NZS 1170.2 - 2011: Structural design actions Part 2: Wind actions.</li> <li>AS 1170.4 - 2007: Structural design actions Part 4: Earthquake actions in Australia.</li> <li>AS 3600 - 2018: Concrete structures.</li> <li>AS 4100 - 2020: Steel structures.</li> <li>AS/NZS 4600 - 2018: Cold-formed steel structures.</li> </ul>																																																							

Page: 2

This document contains confidential information and intellectual property owned by Robust Consulting Engineering Pty Ltd and are subject to copyright, patents and intellectual property rights. Copying, disclosing or using any part of this document is expressly prohibited without written permission from Robust Consulting Engineering Pty Ltd.

# Engineering Fascia & Transom



# Engineering Fascia & Transom

Raine & Horne FA-225-N & TR-225-N		Project Code: TBP126	
<b>Sign Dimension &amp; Wind Pressure</b>			
Description	Parameter	Value	Unit
Signage face height	$h_s$	0.23	m
Signage total height	$h$	0.65	m
Signage average width	$b$	2.40	m
Proportion of cladded area	$A_c$	1.00	-
Signage total area	$A_s$	0.54	$m^2$
Height of datum above NGL (z = 0)	$h_d$	3.00	m
Height above NGL (rounded up)	$z$	4	m
<b>Select sign location</b>			
Wind region	WR	C	-
Importance Level	IL	2	-
Terrain Category	TC	3	-
Average Recurrence Interval	R	500	-
Regional wind speed	$V_R$	69.0	m/s
Dynamic response factor	$C_{dyn}$	1.00	-
Area reduction factor	$k_a$	1.00	-
Combination factor	$k_c$	1.00	-
Local pressure factor	$k_l \times C_{pe}$	0.80	-
Porous cladding factor	$k_p$	1.00	-
Aerodynamic Factor (Cfig=Cpe.ka.kc.kl.k)	$C_{fig}$	0.80	-
Terrain & height multiplier	$M_z$	0.83	-
Pressure at ht z	$p_z$	1.97	kPa
Strength design pressure	$p_d$	1.57	kPa
Serviceability design pressure	$p_s$	1.05	kPa
<b>Total wind load on entire signage</b>	$W_s$	<b>0.9</b>	<b>kN</b>
Signage self weight	G	0.1	kN

Page: 5

Raine & Horne FA-225-N & TR-225-N		Project Code: TBP126	
<b>Horizontal Sign Frame Rail Check (SHS)</b>			
Description	Parameter	Value	Unit
Modulus of elasticity	E	70.0E+3	MPa
Height of the sign	H	0.65	m
Effective width of the rail member	LW	0.325	m
Ultimate wind load on the member	WL	0.33	kN/m
Take horizontal member as one piece	L	1.20	m
Length of the rail member			
Moment on the rail member	M*	0.059	kNm
Shear on the rail member	V*	0.20	kN
<b>Section Chosen: 40x40x3 SHS Aluminium</b>		<b>6060 T5</b>	
Shear Capacity of section	$\phi V_{rx}$	14.140	kN
Moment capacity of section	$\phi M_{sx}$	0.470	kNm
Moment of Inertia	$I_x$	0.102	$\times 10^6 \text{ mm}^4$
Shear Ratio $V^* / \phi V_{rx}$	$r_v$	0.01	$\leq 1 \text{ OK}$
Moment Ratio $M^* / \phi M_{sx}$	$r_m$	0.12	$\leq 1 \text{ OK}$
Check unity	$c_u$	0.10	$\leq 1 \text{ OK}$
Deflection at the top of sign	$\Delta$	0.7	mm
Height to deflection ratio	$h/\Delta$	1843	$\geq 50 \text{ OK}$
Therefore 40x40x3 SHS used as horizontal sign frame is OKAY			

Page: 6

# Engineering Fascia & Transom


Raine & Horne FA-225-N & TR-225-N		Project Code: TBP126		
Bolt fixing for concrete strata				
Description	Parameter	Value	Unit	
Assume calculation is per rectangular frame				
Fascia Height	h	0.65	m	
Fascia Width	b	2.40	m	
Fascia Area	A	1.56	m <sup>2</sup>	
Ultimate wind load on whole sign	WL <sub>uls</sub>	2.46	kN	
Deadload per letter (factor of 1.3)	DL	1.60	kN	
Average number of screw connection	n	8		
Tension per bolt	N <sub>t</sub>	0.31	kN	
Shear per bolt	V <sub>b</sub>	0.20	kN	
<b>Using, M10 (SS/Class 50) Bolt</b>				
Screw tensile strength	φN <sub>uc</sub>	18.56	kN	
Screw shear strength	φV <sub>us</sub>	10.38	kN	
N / φN <sub>uc</sub>	η <sub>t</sub>	0.02	≤ 1 OK	
V / φV <sub>us</sub>	η <sub>v</sub>	0.02	≤ 1 OK	
Check unity	c <sub>u</sub>	0.04	≤ 1.2 OK	
Minimum of 10xM10 bolts to either Girt or stud + ST 5.8 (#12) screws @500 c/c to metal façade (0.48BMT) (uniformly distributed)				
M8 Coach screws to timber Emb depth 30mm. Pull-out capacity = 16.21 kN. OK [Timber Fixing]				
M10 bolts to concrete for Emb depth 90mm. Pull-out capacity = 13.6 kN. OK [Concrete Fixing]				
See recommended fixings in the next page				

Page: 7

Raine & Horne FA-225-N & TR-225-N		Project Code: TBP126
Connection Specifications to various Strata		
Strata	Fixing requirement for Region A, B & C	
1) Metal Wall	Minimum of 10xM10 bolts to either Girt or stud + ST 5.8 (#12) screws @500 c/c to metal façade 0.48 BMT (uniformly distributed)	
2) Timber	Minimum of 10xM8 coach screws to either Girt or stud + ST 5.8 (#12) screws @500 c/c to metal façade	
3) Concrete	10xM10 (4.6/5) Chemset Bolts. Embedment depth = 90mm.	
4) Structural tube sections	Steel SHS or RHS with minimum wall thickness of 3mm. Minimum 8 x M12x75mm Hollow bolts + ST 5.8 (#12) screws @500c/c to metal facade (uniformly distributed).	

Page: 8

## Engineering Fascia &amp; Transom



# Engineering Fascia & Transom

<p><b>Building Act 1993</b> Section 238(1)(a)</p> <p><b>Building Regulations 2018</b> Regulation 126</p> <p><b>CERTIFICATE OF COMPLIANCE FOR PROPOSED BUILDING WORK</b></p> <p><b>This certificate is issued to</b> Relevant building surveyor</p> <p>Postal address (if applicable)</p> <p>Email</p> <p><b>This certificate is issued in relation to the proposed building work at:</b></p> <p>Address of State Generic computation for Australia (Wind Region A-C)</p> <p><b>Nature of proposed building work</b></p> <p>Construction of: a new signage</p> <p>Height:</p> <p>Type of Construction: Steel, Timber, and Concrete Strata</p> <p>Version of BCA applicable to certificate</p> <p><b>Building classification</b></p> <p>Part of building: Signage BCA Classification: Class 10b</p> <p><b>Prescribed class of building work for which this certificate is issued:</b></p> <p>Design or part of the design of building work relating to Signage</p> <p><b>Documents setting out the design that is certified by this certificate</b></p> <table border="1"> <tr> <th>Document no.</th> <th>Document date</th> <th>Type of document (e.g. drawings, Computations, specifications, calculations etc.)</th> <th>No. of pages</th> <th>Prepared by</th> </tr> <tr> <td>TBP126</td> <td>6/28/2024</td> <td>Structural Engineering Computations</td> <td>10</td> <td>BB</td> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table> <p>Approved by the Victorian Building Authority</p> <p>Page 1 of 2</p>					Document no.	Document date	Type of document (e.g. drawings, Computations, specifications, calculations etc.)	No. of pages	Prepared by	TBP126	6/28/2024	Structural Engineering Computations	10	BB																														
Document no.	Document date	Type of document (e.g. drawings, Computations, specifications, calculations etc.)	No. of pages	Prepared by																																								
TBP126	6/28/2024	Structural Engineering Computations	10	BB																																								

<p>The design certified by this certificate complies with the following provisions of Building Act 1993, Building Regulations 2018 or National Construction Code</p> <table border="1"> <thead> <tr> <th>Act, Regulation or NCC</th> <th>Section, Regulation, Part, Performance Requirement or other provision</th> </tr> </thead> <tbody> <tr> <td>NCC</td> <td>National Construction Code 2022</td> </tr> <tr> <td>Australian Standard</td> <td>AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.</td> </tr> <tr> <td>Australian Standard</td> <td>AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed &amp; other actions.</td> </tr> <tr> <td>Australian Standard</td> <td>AS/NZS 1170.2 - 2021: Structural design actions Part 2: Wind actions.</td> </tr> <tr> <td>Australian Standard</td> <td>AS 3600 - 2018: Concrete structures</td> </tr> <tr> <td>Australian Standard</td> <td>AS 4100 - 2020: Steel structures.</td> </tr> <tr> <td>Australian Standard</td> <td>AS/NZS 4600 - 2018: Cold-formed steel structures.</td> </tr> <tr> <td>Australian Standard</td> <td>AS/NZS 5131 - 2016: Structural steelwork-Fabrication and erections. -CC2</td> </tr> </tbody> </table> <p>I prepared the design, or part of the design, set out in the documents listed above.</p> <p>I certify that the design set out in the documents listed above complies with the provisions set out above.</p> <p>I believe that I hold the required skills, experience and knowledge to issue this certificate and can demonstrate this if requested to do so.</p> <p><b>Engineer</b> Name: Suresh Hada Address: Suite 7, 750 Blackburn Rd, Clayton 3168 Category and class: Engineer Civil Registration No: PE0002632 Date of issue of certificate: 28/Jun/2024 Signature:</p> <p><i>Suresh Hada</i></p> <table border="1"> <tr> <td></td> <td><b>Suresh Hada</b> FIEAust, CPEng, NER, IPENZ Chartered Professional Engineer Membership No. 2621329</td> </tr> </table> <p>Vic: Registered Professional Engineer, Civil Engineer – PE0002632 NSW: Registered Certifier- Structural Engineer Reg No. BPB 2816 Qld: Registered Professional Engineer of Qld, Div: Structural RPEQ 15255 Tas: Accredited Certifier, Div: Civil (Building Act 2000, Tas) CC6537 NT: Certifying Engineer (Structural) Reg No. 227617ES</p> <p>Approved by the Victorian Building Authority</p> <p>Page 2 of 2</p>					Act, Regulation or NCC	Section, Regulation, Part, Performance Requirement or other provision	NCC	National Construction Code 2022	Australian Standard	AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.	Australian Standard	AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed & other actions.	Australian Standard	AS/NZS 1170.2 - 2021: Structural design actions Part 2: Wind actions.	Australian Standard	AS 3600 - 2018: Concrete structures	Australian Standard	AS 4100 - 2020: Steel structures.	Australian Standard	AS/NZS 4600 - 2018: Cold-formed steel structures.	Australian Standard	AS/NZS 5131 - 2016: Structural steelwork-Fabrication and erections. -CC2		<b>Suresh Hada</b> FIEAust, CPEng, NER, IPENZ Chartered Professional Engineer Membership No. 2621329
Act, Regulation or NCC	Section, Regulation, Part, Performance Requirement or other provision																							
NCC	National Construction Code 2022																							
Australian Standard	AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.																							
Australian Standard	AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed & other actions.																							
Australian Standard	AS/NZS 1170.2 - 2021: Structural design actions Part 2: Wind actions.																							
Australian Standard	AS 3600 - 2018: Concrete structures																							
Australian Standard	AS 4100 - 2020: Steel structures.																							
Australian Standard	AS/NZS 4600 - 2018: Cold-formed steel structures.																							
Australian Standard	AS/NZS 5131 - 2016: Structural steelwork-Fabrication and erections. -CC2																							
	<b>Suresh Hada</b> FIEAust, CPEng, NER, IPENZ Chartered Professional Engineer Membership No. 2621329																							

## Engineering UA1800

**RE** ROBUST Consulting Engineers Pty Ltd  
Civil & Structural, ABN 14 626 910 750

Suite 7, 750 Blackburn Rd, Clayton, Vic 3168  
0418133012, (+613) 85102535  
www.robustengineers.com.au  
suresh@robustengineers.com.au

**STRUCTURAL ENGINEERING COMPUTATIONS**

PROJECT: Raine & Horne\_UA1800  
Awning Signage (1.8x0.42)

CLIENT: Theblueprint

ADDRESS: Generic Computation for  
Australia (Wind Region A)  
(To be used in conjunction with Design Compliance Certificate)

REVISION: 0

PROJECT CODE: TBP126  
PREPARED BY: A.R

**CERTIFIED BY**  
  
**Suresh Hada**  
FIEAust, CPEng, NER, IPENZ  
Chartered Professional Engineer  
Membership No. 2621329  
AUSTRALIA

Vic: Registered Professional Engineer, Civil Engineer - PE0002632  
NSW: Registered Certifier- Structural Engineer Reg No. BPB 2816  
Qld: Registered Professional Engineer of Qld, Div. Structural RPEQ 15257  
Tas: Accredited Certifier, Div. Civil (Building Act 2000, Tas) CC6537  
NT: Certifying Engineer (Structural) Reg No. 227617ES


Date: 13/June/2024

This document contains confidential information and intellectual property owned by Robust Consulting Engineers Pty Ltd and are subject to copyright, patents and intellectual property rights. Copying, disclosing or using any part of this document is expressly prohibited without written permission from Robust Consulting Engineers Pty Ltd.

Raine & Horne_UA1800		Project Code: TBP126																																										
Scope:																																												
Provide engineering design and details for wall mounted sign as per drawing/sketch in this computation sheet																																												
<ol style="list-style-type: none"> <li>Design loads to be considered           <table> <tr> <td>DL</td> <td>Sign dead load [self weight]</td> </tr> <tr> <td>WL</td> <td>Wind load</td> </tr> <tr> <td>EL</td> <td>Earthquake load as applicable</td> </tr> </table> </li> <li>Design and detail fixings to existing wall structure</li> </ol>			DL	Sign dead load [self weight]	WL	Wind load	EL	Earthquake load as applicable																																				
DL	Sign dead load [self weight]																																											
WL	Wind load																																											
EL	Earthquake load as applicable																																											
Assumptions: Computation is based on the drawing submitted by the client																																												
Exclusion: The strata where the sign is connected shall be checked by other engineers before installation. This computation excludes checking of sign support structure.																																												
<b>Materials:</b> <table> <thead> <tr> <th></th> <th><math>f_y</math> (MPa)</th> <th><math>f_u</math> (MPa)</th> </tr> </thead> <tbody> <tr> <td>Hot Rolled UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)</td> <td>300</td> <td>440</td> </tr> <tr> <td>Plate: Grade 250 (AS/NZS 3678 - 2011)</td> <td>250</td> <td>410</td> </tr> <tr> <td><b>Cold Formed</b> SHS: Grade C450 (AS1163 - 2009)</td> <td>450</td> <td>500</td> </tr> <tr> <td>RHS: Grade C450 (AS 1163 - 2009)</td> <td>450</td> <td>500</td> </tr> <tr> <td>CHS: Grade C350 (AS 1163 - 2009)</td> <td>350</td> <td>430</td> </tr> <tr> <td>CA: Cold-formed angle (Duragal)</td> <td>350</td> <td>400</td> </tr> <tr> <td>CC: Cold formed channels (Duragal)</td> <td>400</td> <td>450</td> </tr> <tr> <td>CF: Cold-formed flats (Duragal)</td> <td>350</td> <td>400</td> </tr> <tr> <td>Bolts (4.6/S) - [Commercial]</td> <td>240</td> <td>400</td> </tr> <tr> <td>Bolts (8.8/S) - [High Strength Structural]</td> <td>660</td> <td>830</td> </tr> <tr> <td><b>Welds</b> Welding - Category: General Purpose</td> <td>GP</td> <td>410</td> </tr> <tr> <td>Welding - Category: Structural Purpose</td> <td>SP</td> <td>410</td> </tr> <tr> <td><b>Concrete:</b> Grade N25 [<math>f'_c</math> @ 28 days]</td> <td>25</td> <td>MPa</td> </tr> </tbody> </table>				$f_y$ (MPa)	$f_u$ (MPa)	Hot Rolled UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)	300	440	Plate: Grade 250 (AS/NZS 3678 - 2011)	250	410	<b>Cold Formed</b> SHS: Grade C450 (AS1163 - 2009)	450	500	RHS: Grade C450 (AS 1163 - 2009)	450	500	CHS: Grade C350 (AS 1163 - 2009)	350	430	CA: Cold-formed angle (Duragal)	350	400	CC: Cold formed channels (Duragal)	400	450	CF: Cold-formed flats (Duragal)	350	400	Bolts (4.6/S) - [Commercial]	240	400	Bolts (8.8/S) - [High Strength Structural]	660	830	<b>Welds</b> Welding - Category: General Purpose	GP	410	Welding - Category: Structural Purpose	SP	410	<b>Concrete:</b> Grade N25 [ $f'_c$ @ 28 days]	25	MPa
	$f_y$ (MPa)	$f_u$ (MPa)																																										
Hot Rolled UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)	300	440																																										
Plate: Grade 250 (AS/NZS 3678 - 2011)	250	410																																										
<b>Cold Formed</b> SHS: Grade C450 (AS1163 - 2009)	450	500																																										
RHS: Grade C450 (AS 1163 - 2009)	450	500																																										
CHS: Grade C350 (AS 1163 - 2009)	350	430																																										
CA: Cold-formed angle (Duragal)	350	400																																										
CC: Cold formed channels (Duragal)	400	450																																										
CF: Cold-formed flats (Duragal)	350	400																																										
Bolts (4.6/S) - [Commercial]	240	400																																										
Bolts (8.8/S) - [High Strength Structural]	660	830																																										
<b>Welds</b> Welding - Category: General Purpose	GP	410																																										
Welding - Category: Structural Purpose	SP	410																																										
<b>Concrete:</b> Grade N25 [ $f'_c$ @ 28 days]	25	MPa																																										
<b>Regulation &amp; Codes:</b> <ul style="list-style-type: none"> <li>BCA - 2024: Building Code of Australia - 2024</li> <li>AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.</li> <li>AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed &amp; other actions.</li> <li>AS/NZS 1170.2 - 2011: Structural design actions Part 2: Wind actions.</li> <li>AS 1170.4 - 2007: Structural design actions Part 4: Earthquake actions in Australia.</li> <li>AS 3600 - 2018: Concrete structures.</li> <li>AS 4100 - 2020: Steel structures.</li> <li>AS/NZS 4600 - 2018: Cold-formed steel structures.</li> </ul>																																												

Page: 2

## Engineering UA1800



## Engineering UA1800

Raine & Horne_UA1800		Project Code: TBP126	
<b>Sign Dimension &amp; Wind Pressure</b>			
Description	Parameter	Value	Unit
Signage face height	$h_s$	0.42	m
Signage total height	$h$	0.42	m
Signage average width	$b$	1.80	m
Proportion of cladded area	$A_c$	1.00	-
Signage total area	$A_s$	0.76	$m^2$
Height of datum above NGL (z = 0)	$h_d$	2.40	m
Height above NGL (rounded up)	$z$	3	m
<b>Select sign location</b>			
Wind region	WR	A	-
Importance Level	IL	2	-
Terrain Category	TC	3	-
Average Recurrence Interval	R	500	-
Regional wind speed	$V_R$	45.0	m/s
Dynamic response factor	$C_{dyn}$	1.00	-
Area reduction factor	$k_a$	1.00	-
Combination factor	$k_c$	1.00	-
Local pressure factor	$k_x \times C_{pe}$	1.30	-
Porous cladding factor	$k_p$	1.00	-
Aerodynamic Factor (Cfig=Cpe.ka.kc.kl.k)	$C_{fig}$	1.30	-
Terrain & height multiplier	$M_z$	0.83	-
Pressure at ht z	$p_z$	0.84	kPa
Strength design pressure	$p_d$	1.09	kPa
Serviceability design pressure	$p_s$	0.73	kPa
<b>Total wind load on entire signage</b>	$W_s$	<b>0.8</b>	<b>kN</b>
Signage self weight	G	0.2	kN

Page: 5

Raine & Horne_UA1800		Project Code: TBP126	
<b>Horizontal Sign Frame Rail Check (RHS)</b>			
Description	Parameter	Value	Unit
Modulus of elasticity	E	70.0E+3	MPa
Height of the Sign	H	0.42	m
Effective width of the rail member	LW	0.21	m
Ultimate wind load on the member	WL	0.23	kN/m
Take horizontal member as one piece	L	0.90	m
Length of the rail member			
Moment on the rail member	M*	0.023	kNm
Shear on the rail member	V*	0.10	kN
<b>Section Chosen: 40 x 25 x 3mm</b>	<b>Grade: 6060TS</b>		
Shear Capacity of section	$\phi V_{vx}$	14.100	kN
Moment capacity of section	$\phi M_{sx}$	0.317	kNm
Moment of Inertia	$I_z$	0.071	$\times 10^5 \text{ mm}^4$
Shear Ratio $V^* / \phi V_{vx}$	$r_v$	0.01	$\leq 1 \text{ OK}$
Moment Ratio $M^* / \phi M_{sx}$	$r_m$	0.07	$\leq 1 \text{ OK}$
Check unity	$c_u$	0.06	$\leq 1 \text{ OK}$
Deflection at the top of sign	$\Delta$	0.2	mm
Height to deflection ratio	$h/\Delta$	4324	$\geq 50 \text{ OK}$
Therefore 40 x 25 x 3mm use as horizontal sign frame is OKAY			


Page: 6

## Engineering UA1800

Raine & Horne_UA1800		Project Code: TBP126		
<b>Vertical Sign Frame Check (RHS)</b>				
Description	Parameter	Value	Unit	
Modulus of elasticity	E	70.0E+3	MPa	
Height of the Sign	H	0.42	m	
Effective width of the vertical member	LW	0.900	m	
Ultimate wind load on the member	WL	0.98	kN/m	
Take vertical member as one piece	L	0.42	m	
Length of the rail member				
Moment on the rail member	M*	0.022	kNm	
Shear on the rail member	V*	0.21	kN	
<b>Section Chosen: 40 x 25 x 3mm</b>		<b>Grade: 6060TS</b>		
Shear Capacity of section	$\phi V_{vx}$	14.100	kN	
Moment capacity of section	$\phi M_{ux}$	0.317	kNm	
Moment of Inertia	$I_x$	0.071	$\times 10^6 \text{ mm}^4$	
Shear Ratio $V^* / \phi V_{vx}$	$r_v$	0.01	$\leq 1 \text{ OK}$	
Moment Ratio $M^* / \phi M_{ux}$	$r_m$	0.07	$\leq 1 \text{ OK}$	
Check unity	$c_u$	0.06	$\leq 1 \text{ OK}$	
Deflection at the top of sign	$\Delta$	0.04	mm	
Height to deflection ratio	$h/\Delta$	9928	$\geq 50 \text{ OK}$	
Therefore 40 x 25 x 3mm use as vertical sign frame is OKAY				

Raine & Horne_UA1800				
<b>Ceiling Fixing (Steel Strata)</b>				
Description	Parameter	Value	Unit	
Sign Height	h	0.42	m	
Sign Width	b	1.80	m	
Sign Area	A	0.76	$\text{m}^2$	
Ultimate wind load on whole sign	$WL_{us}$	0.82	kN	
Deadload per letter (assumed weight = 0.20 kPa, factor of 1.3)	DL	0.34	kN	
Average number of bolt connection	n	2		
Tension per bolt	$N_t$	0.41	kN	
Shear per bolt	$N_b$	0.17	kN	
<b>Using, M10 threaded rod (Class 4.6)</b>				
Bolt tensile strength	$\phi N_{uc}$	23.20	kN	
Bolt shear strength	$\phi V_{us}$	12.60	kN	
$N_t / \phi N_{uc}$	$\eta_t$	0.02	$\leq 1 \text{ OK}$	
$N_b / \phi V_{us}$	$\eta_b$	0.01	$\leq 1 \text{ OK}$	
Check unity	$c_u$	0.03	$\leq 1.2 \text{ OK}$	
Provide Nominal galvanised 2 x M10 threaded rod bolted to top of lightbox and anchored or bolted to ceiling structure are SATISFACTORY.				

## Engineering UA1800



**Building Act 1993**  
**Section 238(1)(a)**  
**Building Regulations 2018**  
**Regulation 126**

**CERTIFICATE OF COMPLIANCE FOR PROPOSED BUILDING WORK**

**This certificate is issued to** Relevant building surveyor  
**Postal address (if applicable)**  
**Email**

**This certificate is issued in relation to the proposed building work at:**

Address of Generic Computation for  
State Australia (Wind Region A)

**Nature of proposed building work**

Construction of: a new signage  
Height:  
Type of Construction: Steel strata  
Version of BCA applicable to certificate

**Building classification**  
Part of building: Signage      BCA Classification: Class 10b

**Prescribed class of building work for which this certificate is issued:**  
Design or part of the design of building work relating to Signage

**Documents setting out the design that is certified by this certificate**

Document no.	Document date	Type of document (e.g. drawings, Computations, specifications, calculations etc.)	No. of pages	Prepared by
TBP126	13/06/2024	Structural Engineering Computations	9	A.R

Approved by the Victorian Building Authority

Page 1 of 2

# Engineering UA1800

<p>The design certified by this certificate complies with the following provisions of Building Act 1993, Building Regulations 2018 or National Construction Code</p>	
<b>Act, Regulation or NCC</b>	<b>Section, Regulation, Part, Performance Requirement or other provision</b>
NCC	National Construction Code 2022
Australian Standard	AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.
Australian Standard	AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed & other actions.
Australian Standard	AS/NZS 1170.2 - 2021: Structural design actions Part 2: Wind actions.
Australian Standard	AS 3600 - 2018: Concrete structures
Australian Standard	AS 4100 - 2020: Steel structures.
Australian Standard	AS/NZS 4600 - 2018: Cold-formed steel structures.
Australian Standard	AS/NZS 5131 - 2016: Structural steelwork-Fabrication and erections. -CC2

I prepared the design, or part of the design, set out in the documents listed above.

I certify that the design set out in the documents listed above complies with the provisions set out above.

I believe that I hold the required skills, experience and knowledge to issue this certificate and can demonstrate this if requested to do so.

**Engineer**  
 Name: **Suresh Hada**  
 Address: **Suite 7, 750 Blackburn Rd, Clayton 3168**  
 Category and class: **Engineer Civil**  
 Registration No: **PE0002632**  
 Date of Issue of certificate: **13/Jun/2024**  
 Signature:

*Suresh Hada*


**Suresh Hada**  
 PEng, CPEng, NER, IPENZ  
 Chartered Professional Engineer  
 Membership No. 2621329



Vic: Registered Professional Engineer, Civil Engineer – PE0002632  
 NSW: Registered Certifier- Structural Engineer Reg No. BPB 2816  
 Qld: Registered Professional Engineer of Qld, Div: Structural RPEQ 15255  
 Tas: Accredited Certifier, Div: Civil (Building Act 2000, Tas) CC6537  
 NT: Certifying Engineer (Structural) Reg No. 227617ES

## Engineering WM/HL-500

<div style="text-align: center; padding: 10px;">  <b>ROBUST Consulting Engineers Pty Ltd</b>          Civil &amp; Structural, ABN 14 626 910 750         <p><b>STRUCTURAL ENGINEERING COMPUTATIONS</b></p> <p>PROJECT: Raine &amp; Horne WM/HL-500 Fascia Signage (1.78x6.5)</p> <p>CLIENT: TBP</p> <p>ADDRESS: Generic computation for Australia (Wind Region A-C) (To be used in conjunction with Design Compliance Certificate)</p> <p>REVISION: 0</p> <p>PROJECT CODE: TBP126</p> <p>PREPARED BY: BB</p> <p><b>CERTIFIED BY</b>   <b>Suresh Hada</b>  <small>FIEAust, CPEng, NER, IPENZ Chartered Professional Engineer Membership No. 2621329</small> <p>Vic: Registered Professional Engineer, Civil Engineer – PE0002632 NSW: Registered Structural Engineer Reg No. BPB 2816 Qld: Registered Professional Engineer of Qld, Div Structural RPEQ 15255 Tas: Accredited Certifier, Div. Civil (Building Act 2000, Tas) CC6337 NT: Certifying Engineer (Structural) Reg No. 227617ES</p> <p>Date: 27/June/2024</p> </p></div> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <small>This document contains confidential information and intellectual property owned by Robust Consulting Engineering Pty Ltd and are subject to copyright, patents and intellectual property rights. Copying, disclosing or using any part of this document is expressly prohibited without written permission from Robust Consulting Engineering Pty Ltd.</small> </div>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; padding: 5px;"> <b>Raine &amp; Horne WM/HL-500</b> </td> <td style="width: 50%; padding: 5px;"> <b>Project Code: TBP126</b> </td> </tr> <tr> <td colspan="2" style="padding: 5px;"> <b>Scope:</b>  <small>Provide engineering design and details for wall mounted sign as per drawing/sketch in this computation sheet</small> </td> </tr> <tr> <td colspan="2" style="padding: 5px;"> <ol style="list-style-type: none"> <li>1. Design loads to be considered           <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">DL</td> <td>Sign dead load [self weight]</td> </tr> <tr> <td>WL</td> <td>Wind load</td> </tr> <tr> <td>EL</td> <td>Earthquake load as applicable</td> </tr> </table> </li> <li>2. Design and detail letter structural arrangement</li> <li>3. Design and detail support frame structure</li> <li>4. Design and detail fixings to existing wall structure</li> </ol> </td> </tr> <tr> <td colspan="2" style="padding: 5px;"> <b>Assumptions:</b> Computation is based on the drawing submitted by the client       </td> </tr> <tr> <td colspan="2" style="padding: 5px;"> <b>Materials:</b> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">Hot Rolled</td> <td>UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)</td> <td style="text-align: right;">f<sub>y</sub> (Mpa)</td> <td style="text-align: right;">f<sub>u</sub> (MPa)</td> </tr> <tr> <td>Plate: Grade 250 (AS/NZS 3678 - 2011)</td> <td>300</td> <td style="text-align: right;">440</td> </tr> <tr> <td>SHS: Grade C450 (AS1163 - 2009)</td> <td>250</td> <td style="text-align: right;">410</td> </tr> <tr> <td>RHS: Grade C450 (AS 1163 - 2009)</td> <td>450</td> <td style="text-align: right;">500</td> </tr> <tr> <td>CHS: Grade C350 (AS 1163 - 2009)</td> <td>350</td> <td style="text-align: right;">430</td> </tr> <tr> <td>CA: Cold-formed angle (Duragal)</td> <td>350</td> <td style="text-align: right;">400</td> </tr> <tr> <td>CC: Cold formed channels (Duragal)</td> <td>400</td> <td style="text-align: right;">450</td> </tr> <tr> <td>CF: Cold-formed flats (Duragal)</td> <td>350</td> <td style="text-align: right;">400</td> </tr> <tr> <td>Bolts (4.6/5) - [Commercial]</td> <td>240</td> <td style="text-align: right;">400</td> </tr> <tr> <td>Bolts (8.8/5) - [High Strength Structural]</td> <td>660</td> <td style="text-align: right;">830</td> </tr> <tr> <td>Welds</td> <td>Welding - Category: General Purpose</td> <td style="text-align: right;">GP</td> <td style="text-align: right;">410</td> </tr> <tr> <td>Concrete:</td> <td>Welding - Category: Structural Purpose</td> <td style="text-align: right;">SP</td> <td style="text-align: right;">410</td> </tr> <tr> <td></td> <td>Grade N25 [f'c @ 28 days]</td> <td style="text-align: right;">25</td> <td style="text-align: right;">MPa</td> </tr> </table> </td> </tr> <tr> <td colspan="2" style="padding: 5px;"> <b>Regulation &amp; Codes:</b> <ul style="list-style-type: none"> <li>BCA - 2024: Building Code of Australia - 2024</li> <li>AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.</li> <li>AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed &amp; other actions.</li> <li>AS/NZS 1170.2 - 2011: Structural design actions Part 2: Wind actions.</li> <li>AS 1170.4 - 2007: Structural design actions Part 4: Earthquake actions in Australia.</li> <li>AS 3600 - 2018: Concrete structures.</li> <li>AS 4100 - 2020: Steel structures.</li> <li>AS/NZS 4600 - 2018: Cold-formed steel structures.</li> </ul> </td> </tr> </table>	<b>Raine &amp; Horne WM/HL-500</b>	<b>Project Code: TBP126</b>	<b>Scope:</b> <small>Provide engineering design and details for wall mounted sign as per drawing/sketch in this computation sheet</small>		<ol style="list-style-type: none"> <li>1. Design loads to be considered           <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">DL</td> <td>Sign dead load [self weight]</td> </tr> <tr> <td>WL</td> <td>Wind load</td> </tr> <tr> <td>EL</td> <td>Earthquake load as applicable</td> </tr> </table> </li> <li>2. Design and detail letter structural arrangement</li> <li>3. Design and detail support frame structure</li> <li>4. Design and detail fixings to existing wall structure</li> </ol>		DL	Sign dead load [self weight]	WL	Wind load	EL	Earthquake load as applicable	<b>Assumptions:</b> Computation is based on the drawing submitted by the client		<b>Materials:</b> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">Hot Rolled</td> <td>UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)</td> <td style="text-align: right;">f<sub>y</sub> (Mpa)</td> <td style="text-align: right;">f<sub>u</sub> (MPa)</td> </tr> <tr> <td>Plate: Grade 250 (AS/NZS 3678 - 2011)</td> <td>300</td> <td style="text-align: right;">440</td> </tr> <tr> <td>SHS: Grade C450 (AS1163 - 2009)</td> <td>250</td> <td style="text-align: right;">410</td> </tr> <tr> <td>RHS: Grade C450 (AS 1163 - 2009)</td> <td>450</td> <td style="text-align: right;">500</td> </tr> <tr> <td>CHS: Grade C350 (AS 1163 - 2009)</td> <td>350</td> <td style="text-align: right;">430</td> </tr> <tr> <td>CA: Cold-formed angle (Duragal)</td> <td>350</td> <td style="text-align: right;">400</td> </tr> <tr> <td>CC: Cold formed channels (Duragal)</td> <td>400</td> <td style="text-align: right;">450</td> </tr> <tr> <td>CF: Cold-formed flats (Duragal)</td> <td>350</td> <td style="text-align: right;">400</td> </tr> <tr> <td>Bolts (4.6/5) - [Commercial]</td> <td>240</td> <td style="text-align: right;">400</td> </tr> <tr> <td>Bolts (8.8/5) - [High Strength Structural]</td> <td>660</td> <td style="text-align: right;">830</td> </tr> <tr> <td>Welds</td> <td>Welding - Category: General Purpose</td> <td style="text-align: right;">GP</td> <td style="text-align: right;">410</td> </tr> <tr> <td>Concrete:</td> <td>Welding - Category: Structural Purpose</td> <td style="text-align: right;">SP</td> <td style="text-align: right;">410</td> </tr> <tr> <td></td> <td>Grade N25 [f'c @ 28 days]</td> <td style="text-align: right;">25</td> <td style="text-align: right;">MPa</td> </tr> </table>		Hot Rolled	UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)	f <sub>y</sub> (Mpa)	f <sub>u</sub> (MPa)	Plate: Grade 250 (AS/NZS 3678 - 2011)	300	440	SHS: Grade C450 (AS1163 - 2009)	250	410	RHS: Grade C450 (AS 1163 - 2009)	450	500	CHS: Grade C350 (AS 1163 - 2009)	350	430	CA: Cold-formed angle (Duragal)	350	400	CC: Cold formed channels (Duragal)	400	450	CF: Cold-formed flats (Duragal)	350	400	Bolts (4.6/5) - [Commercial]	240	400	Bolts (8.8/5) - [High Strength Structural]	660	830	Welds	Welding - Category: General Purpose	GP	410	Concrete:	Welding - Category: Structural Purpose	SP	410		Grade N25 [f'c @ 28 days]	25	MPa	<b>Regulation &amp; Codes:</b> <ul style="list-style-type: none"> <li>BCA - 2024: Building Code of Australia - 2024</li> <li>AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.</li> <li>AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed &amp; other actions.</li> <li>AS/NZS 1170.2 - 2011: Structural design actions Part 2: Wind actions.</li> <li>AS 1170.4 - 2007: Structural design actions Part 4: Earthquake actions in Australia.</li> <li>AS 3600 - 2018: Concrete structures.</li> <li>AS 4100 - 2020: Steel structures.</li> <li>AS/NZS 4600 - 2018: Cold-formed steel structures.</li> </ul>	
<b>Raine &amp; Horne WM/HL-500</b>	<b>Project Code: TBP126</b>																																																													
<b>Scope:</b> <small>Provide engineering design and details for wall mounted sign as per drawing/sketch in this computation sheet</small>																																																														
<ol style="list-style-type: none"> <li>1. Design loads to be considered           <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">DL</td> <td>Sign dead load [self weight]</td> </tr> <tr> <td>WL</td> <td>Wind load</td> </tr> <tr> <td>EL</td> <td>Earthquake load as applicable</td> </tr> </table> </li> <li>2. Design and detail letter structural arrangement</li> <li>3. Design and detail support frame structure</li> <li>4. Design and detail fixings to existing wall structure</li> </ol>		DL	Sign dead load [self weight]	WL	Wind load	EL	Earthquake load as applicable																																																							
DL	Sign dead load [self weight]																																																													
WL	Wind load																																																													
EL	Earthquake load as applicable																																																													
<b>Assumptions:</b> Computation is based on the drawing submitted by the client																																																														
<b>Materials:</b> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">Hot Rolled</td> <td>UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)</td> <td style="text-align: right;">f<sub>y</sub> (Mpa)</td> <td style="text-align: right;">f<sub>u</sub> (MPa)</td> </tr> <tr> <td>Plate: Grade 250 (AS/NZS 3678 - 2011)</td> <td>300</td> <td style="text-align: right;">440</td> </tr> <tr> <td>SHS: Grade C450 (AS1163 - 2009)</td> <td>250</td> <td style="text-align: right;">410</td> </tr> <tr> <td>RHS: Grade C450 (AS 1163 - 2009)</td> <td>450</td> <td style="text-align: right;">500</td> </tr> <tr> <td>CHS: Grade C350 (AS 1163 - 2009)</td> <td>350</td> <td style="text-align: right;">430</td> </tr> <tr> <td>CA: Cold-formed angle (Duragal)</td> <td>350</td> <td style="text-align: right;">400</td> </tr> <tr> <td>CC: Cold formed channels (Duragal)</td> <td>400</td> <td style="text-align: right;">450</td> </tr> <tr> <td>CF: Cold-formed flats (Duragal)</td> <td>350</td> <td style="text-align: right;">400</td> </tr> <tr> <td>Bolts (4.6/5) - [Commercial]</td> <td>240</td> <td style="text-align: right;">400</td> </tr> <tr> <td>Bolts (8.8/5) - [High Strength Structural]</td> <td>660</td> <td style="text-align: right;">830</td> </tr> <tr> <td>Welds</td> <td>Welding - Category: General Purpose</td> <td style="text-align: right;">GP</td> <td style="text-align: right;">410</td> </tr> <tr> <td>Concrete:</td> <td>Welding - Category: Structural Purpose</td> <td style="text-align: right;">SP</td> <td style="text-align: right;">410</td> </tr> <tr> <td></td> <td>Grade N25 [f'c @ 28 days]</td> <td style="text-align: right;">25</td> <td style="text-align: right;">MPa</td> </tr> </table>		Hot Rolled	UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)	f <sub>y</sub> (Mpa)	f <sub>u</sub> (MPa)	Plate: Grade 250 (AS/NZS 3678 - 2011)	300	440	SHS: Grade C450 (AS1163 - 2009)	250	410	RHS: Grade C450 (AS 1163 - 2009)	450	500	CHS: Grade C350 (AS 1163 - 2009)	350	430	CA: Cold-formed angle (Duragal)	350	400	CC: Cold formed channels (Duragal)	400	450	CF: Cold-formed flats (Duragal)	350	400	Bolts (4.6/5) - [Commercial]	240	400	Bolts (8.8/5) - [High Strength Structural]	660	830	Welds	Welding - Category: General Purpose	GP	410	Concrete:	Welding - Category: Structural Purpose	SP	410		Grade N25 [f'c @ 28 days]	25	MPa																		
Hot Rolled	UB, UC, PFC: Grade 300 (AS/NZS 3679.1 - 2010)	f <sub>y</sub> (Mpa)	f <sub>u</sub> (MPa)																																																											
Plate: Grade 250 (AS/NZS 3678 - 2011)	300	440																																																												
SHS: Grade C450 (AS1163 - 2009)	250	410																																																												
RHS: Grade C450 (AS 1163 - 2009)	450	500																																																												
CHS: Grade C350 (AS 1163 - 2009)	350	430																																																												
CA: Cold-formed angle (Duragal)	350	400																																																												
CC: Cold formed channels (Duragal)	400	450																																																												
CF: Cold-formed flats (Duragal)	350	400																																																												
Bolts (4.6/5) - [Commercial]	240	400																																																												
Bolts (8.8/5) - [High Strength Structural]	660	830																																																												
Welds	Welding - Category: General Purpose	GP	410																																																											
Concrete:	Welding - Category: Structural Purpose	SP	410																																																											
	Grade N25 [f'c @ 28 days]	25	MPa																																																											
<b>Regulation &amp; Codes:</b> <ul style="list-style-type: none"> <li>BCA - 2024: Building Code of Australia - 2024</li> <li>AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.</li> <li>AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed &amp; other actions.</li> <li>AS/NZS 1170.2 - 2011: Structural design actions Part 2: Wind actions.</li> <li>AS 1170.4 - 2007: Structural design actions Part 4: Earthquake actions in Australia.</li> <li>AS 3600 - 2018: Concrete structures.</li> <li>AS 4100 - 2020: Steel structures.</li> <li>AS/NZS 4600 - 2018: Cold-formed steel structures.</li> </ul>																																																														

Page: 2

# Engineering WM/HL-500



## Engineering WM/HL-500

Raine & Horne WM/HL-500		Project Code: TBP126	
<b>Sign Dimension &amp; Wind Pressure</b>			
Description	Parameter	Value	Unit
Signage face height	$h_s$	0.50	m
Signage total height	$h$	1.78	m
Signage average width	$b$	6.50	m
Proportion of cladded area	$A_c$	1.00	-
Signage total area	$A_s$	3.25	$m^2$
Height of datum above NGL (z = 0)	$h_d$	3.00	m
Height above NGL (rounded up)	$z$	5	m
Select sign location		Windward wall	
Wind region	WR	C	-
Importance Level	IL	2	-
Terrain Category	TC	3	-
Average Recurrence Interval	R	500	-
Regional wind speed	$V_R$	69.0	m/s
Dynamic response factor	$C_{dyn}$	1.00	-
Area reduction factor	$k_a$	1.00	-
Combination factor	$k_c$	1.00	-
Local pressure factor	$k_l \times C_{pe}$	0.80	-
Porous cladding factor	$k_p$	1.00	-
Aerodynamic Factor (Cfig=Cpe.ka.kc.kl.k)	$C_{fig}$	0.80	-
Terrain & height multiplier	$M_z$	0.83	-
Pressure at ht z	$p_z$	1.97	kPa
Strength design pressure	$p_d$	1.57	kPa
Serviceability design pressure	$p_s$	1.05	kPa
<b>Total wind load on entire signage</b>	$W_s$	<b>5.1</b>	<b>kN</b>
Signage self weight	G	0.8	kN


Raine & Horne WM/HL-500		Project Code: TBP126	
<b>Bolt letter fixing for concrete strata</b>			
Description	Parameter	Value	Unit
Assume calculation is per letter, and shape rectangular			
Letter Height	$h$	0.50	m
Letter Width	$b$	0.45	m
Letter Area	$A$	0.23	$m^2$
Ultimate wind load on whole sign	$WL_{uls}$	0.35	kN
Deadload per letter (assumed weight = 0.20 kPa, factor of 1.3)	DL	0.46	kN
Average number of bolt connection	n	2	
Tension per bolt	$N_t$	0.18	kN
Shear per bolt	$V_b$	0.23	kN
<b>Using, M10 (SS Class 50)</b>			
Bolt tensile strength	$\phi N_{uc}$	18.56	kN
Bolt shear strength	$\phi V_{us}$	10.38	kN
$N / \phi N_{uc}$	$\eta_t$	0.01	≤ 1 OK
$V / \phi V$	$\eta_v$	0.02	≤ 1 OK
Check unity	$c_u$	0.03	≤ 1.2 OK
Provide 2xM10 (SS Class 50) bolts for each letter fixing to concrete Emb depth 90 mm.			
M8 Coach screws to timber for Emb depth 30mm. Pull-out capacity = 16.21 kN. OK			
M10 bolts to concrete for Emb depth 90mm. Pull-out capacity = 13.6 kN. OK			
see recommended fixings in the next page			

# Engineering WM/HL-500

Raine & Horne WM/HL-500		Project Code: TBP126
Connection Specifications to various Strata:		
Strata	Fixing requirement for Region A,B & C	
1) Metal Wall	Minimum of 2xM10 bolts to either Grit or stud + ST 5.8 (#12) screws to 0.48 BMT metal façade as per page 9.	
2) Timber	Minimum of 2xM8 coach screws to either Gurt or stud + ST 5.8 (#12) screws as per page 9.	
3) Concrete	M10 (4.6/5) Chemset bolts. Embedment depth = 90 mm. See page 10 for fixing positions.	
4) Structural tube sections	Steel SHS or RHS with minimum wall thickness of 3 mm. Minimum 2 x M16x75mm Hollow bolts + ST 5.8 (#12) screws to metal facade as per page 9.	

Page: 7


Raine & Horne WM/HL-500	Project Code: TBP126
Robust's letter fixing diagram 1	



Side View

Page: 8

## Engineering WM/HL-500



## Engineering WM/HL-500

<p><b>Building Act 1993</b> Section 238(1)(a)</p> <p><b>Building Regulations 2018</b> Regulation 126</p> <p><b>CERTIFICATE OF COMPLIANCE FOR PROPOSED BUILDING WORK</b></p> <p><b>This certificate is issued to</b> Relevant building surveyor</p> <p>Postal address (if applicable)</p> <p>Email</p> <p><b>This certificate is issued in relation to the proposed building work at:</b></p> <p>Address of State Generic computation for Australia (Wind Region A-C)</p> <p><b>Nature of proposed building work</b></p> <p>Construction of: a new signage</p> <p>Height:</p> <p>Type of Construction: Steel Timber, and Concrete Strata</p> <p>Version of BCA applicable to certificate</p> <p><b>Building classification</b></p> <p>Part of building: Signage BCA Classification: Class 10b</p> <p><b>Prescribed class of building work for which this certificate is issued:</b></p> <p>Design or part of the design of building work relating to Signage</p> <p><b>Documents setting out the design that is certified by this certificate</b></p> <table border="1"> <tr> <th>Document no.</th> <th>Document date</th> <th>Type of document (e.g. drawings, Computations, specifications, calculations etc.)</th> <th>No. of pages</th> <th>Prepared by</th> </tr> <tr> <td>TBP126</td> <td>6/27/2024</td> <td>Structural Engineering Computations</td> <td>10</td> <td>BB</td> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table> <p>Approved by the Victorian Building Authority</p> <p>Page 1 of 2</p>					Document no.	Document date	Type of document (e.g. drawings, Computations, specifications, calculations etc.)	No. of pages	Prepared by	TBP126	6/27/2024	Structural Engineering Computations	10	BB																														
Document no.	Document date	Type of document (e.g. drawings, Computations, specifications, calculations etc.)	No. of pages	Prepared by																																								
TBP126	6/27/2024	Structural Engineering Computations	10	BB																																								

<p>The design certified by this certificate complies with the following provisions of Building Act 1993, Building Regulations 2018 or National Construction Code</p> <table border="1"> <thead> <tr> <th>Act, Regulation or NCC</th> <th>Section, Regulation, Part, Performance Requirement or other provision</th> </tr> </thead> <tbody> <tr> <td>NCC</td> <td>National Construction Code 2022</td> </tr> <tr> <td>Australian Standard</td> <td>AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.</td> </tr> <tr> <td>Australian Standard</td> <td>AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed &amp; other actions.</td> </tr> <tr> <td>Australian Standard</td> <td>AS/NZS 1170.2 - 2021: Structural design actions Part 2: Wind actions.</td> </tr> <tr> <td>Australian Standard</td> <td>AS 3600 - 2018: Concrete structures</td> </tr> <tr> <td>Australian Standard</td> <td>AS 4100 - 2020: Steel structures.</td> </tr> <tr> <td>Australian Standard</td> <td>AS/NZS 4600 - 2018: Cold-formed steel structures.</td> </tr> <tr> <td>Australian Standard</td> <td>AS/NZS 5131 - 2016: Structural steelwork-Fabrication and erections. -CC2</td> </tr> </tbody> </table> <p>I prepared the design, or part of the design, set out in the documents listed above.</p> <p>I certify that the design set out in the documents listed above complies with the provisions set out above.</p> <p>I believe that I hold the required skills, experience and knowledge to issue this certificate and can demonstrate this if requested to do so.</p> <p><b>Engineer</b> Name: Suresh Hada Address: Suite 7, 750 Blackburn Rd, Clayton 3168 Category and class: Engineer Civil Registration No: PE0002632 Date of issue of certificate: 27/Jun/2024 Signature:</p> <p><i>Suresh Hada</i></p> <table border="1"> <tr> <td></td> <td><b>Suresh Hada</b> FIEAust, CPEng, NER, IPENZ Chartered Professional Engineer Membership No. 2621329</td> </tr> </table> <p>Vic: Registered Professional Engineer, Civil Engineer – PE0002632 NSW: Registered Certifier- Structural Engineer Reg No. BPB 2816 Qld: Registered Professional Engineer of Qld, Div: Structural RPEQ 15255 Tas: Accredited Certifier, Div: Civil (Building Act 2000, Tas) CC6537 NT: Certifying Engineer (Structural) Reg No. 227617ES</p> <p>Approved by the Victorian Building Authority</p> <p>Page 2 of 2</p>					Act, Regulation or NCC	Section, Regulation, Part, Performance Requirement or other provision	NCC	National Construction Code 2022	Australian Standard	AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.	Australian Standard	AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed & other actions.	Australian Standard	AS/NZS 1170.2 - 2021: Structural design actions Part 2: Wind actions.	Australian Standard	AS 3600 - 2018: Concrete structures	Australian Standard	AS 4100 - 2020: Steel structures.	Australian Standard	AS/NZS 4600 - 2018: Cold-formed steel structures.	Australian Standard	AS/NZS 5131 - 2016: Structural steelwork-Fabrication and erections. -CC2		<b>Suresh Hada</b> FIEAust, CPEng, NER, IPENZ Chartered Professional Engineer Membership No. 2621329
Act, Regulation or NCC	Section, Regulation, Part, Performance Requirement or other provision																							
NCC	National Construction Code 2022																							
Australian Standard	AS/NZS 1170.0 - 2002: Structural design actions Part 0: General principles.																							
Australian Standard	AS/NZS 1170.1 - 2002: Structural design actions Part 1: Permanent, imposed & other actions.																							
Australian Standard	AS/NZS 1170.2 - 2021: Structural design actions Part 2: Wind actions.																							
Australian Standard	AS 3600 - 2018: Concrete structures																							
Australian Standard	AS 4100 - 2020: Steel structures.																							
Australian Standard	AS/NZS 4600 - 2018: Cold-formed steel structures.																							
Australian Standard	AS/NZS 5131 - 2016: Structural steelwork-Fabrication and erections. -CC2																							
	<b>Suresh Hada</b> FIEAust, CPEng, NER, IPENZ Chartered Professional Engineer Membership No. 2621329																							

Raine&Horne<sup>®</sup>

[rh.com.au](http://rh.com.au)