



National Auto Parts Depot Pty Ltd
20 Production Drive, Campbellfield 3061
P: (03) 9357 6100 F: (03) 9357 0531
www.naparts.com.au

MATERIAL SAFETY DATA SHEET

Identification

<u>Product Name:</u>	Flame Laminating Foam.	<u>U.N. Number:</u>	None
<u>Other Names:</u>	Flexible Polyurethane Foam Combustion Modified Polyether- / Polyester- urethane Foam	<u>Dangerous Goods Class/</u> and Subsidiary Risk:	None
		<u>Hazchem Code:</u>	None
		<u>Poisons Schedule :</u>	None

Manufacturer's Codes:

N27-140FL, N28-130FL, N28-130FL Bifenthrin (BF), N32-170CMFL, N38-220FL.

Uses: Textile lamination and automotive applications.

Physical Descriptions/Properties

Appearance: Flexible, cellular structure, white to off white, natural colour, or specified colour. (Shade will change slowly on exposure to air).

Boiling Point: Not applicable.

Melting, Thermal

Decomposition Ranges: 335 - 370°C

Vapour Pressure: None

Percent Volatiles: None

Specific Gravity: Apparent density of 15 - 100 kg/m³

Flash Point (°C): >250°C

Flammability Limits: Material can be ignited by an open flame or by a source for smouldering ignition.

Autoignition

Temperature (°C): >260°C short term. Avoid long-term exposures over 135°C.

Ingredients (includes all hazardous chemicals)

<u>Chemical Entity</u>	<u>CAS No.</u>	<u>Proportion</u>
Polyurethane Foam	9009-54-5	High Content (>60%)
Halophosphate		Low Content (<10%)

Note: As polyurethane foam is classified as an "article" it is not required to be listed on the Australian Inventory of Chemical Substances.

Health Hazard Information

Health Effects: None expected from normal handling. The polymer is essentially inert with

low oral or dermal toxicity. Inhalation of foam dust should be avoided. Temperatures in excess of 135°C encountered in any processing or other use will produce irritating or toxic fumes.



National Auto Parts Depot Pty Ltd
20 Production Drive, Campbellfield 3061
P: (03) 9357 6100 F: (03) 9357 0531
www.naparts.com.au

First Aid: In case of overexposure to fumes, vapours or smoke, remove victim to fresh air. Render breathing assistance if needed and consult a physician. In case of eye irritation from contact of foam dust, fume, vapour and smoke, flush with ample quantities of water of suitable eyewash for 15 minutes. Consult a physician.

Precautions for Use

Exposure Limits Not applicable.

Ventilation None required under normal conditions. Ventilation required where material is processed with flame or hot cutting wires.

Personal Protection

Respiratory Protection: None required unless fumes or dust is involved.

Protective Gloves: None required.

Eye Protection: As appropriate around moving machine parts during fabrication or if dust protection required.

Flammability The material should be kept away from sparks, smokers' materials, open flame and from excessive heat. Smoking should be forbidden in areas where material is stored or processed. Foam may burn rapidly with high heat and evolution of black smoke. Flammability ratings of small-scale laboratory tests are not to be taken as an indication of the material's behaviour in an actual full-scale fire.

Safe Handling Information

Storage & Transport Maintain adequate fire protection where large volumes of foam are kept, eg. warehouse, fabrication areas and storage rooms. Check for compliance with insurance regulations, local building codes or other legal requirements.

Spills & Disposal Waste may be shredded or baled for re-use. Dispose or landfill or incineration as required by local or state regulation.

Fire/Explosion Hazard If ignited the product may melt, producing flammable liquids. Burning produces toxic gases, such as carbon monoxide, oxides of nitrogen and hydrogen cyanide and intense heat, dense smoke.

Extinguishing media Dry chemical, water, carbon dioxide.

Special fire fighting procedures Wear self-contained breathing apparatus.



National Auto Parts Depot Pty Ltd
20 Production Drive, Campbellfield 3061
P: (03) 9357 6100 F: (03) 9357 0531
www.naparts.com.au

Other Information

Refer to Plastics Industry Association publication:

- "Flexible Polyurethane Foams - Its Uses and Misuses"

Contact Point: (02) 9821 8777 **Date:** May 2012

The information supplied herein is presented in good faith and believed to be accurate to the best knowledge of the supplier.

However, since conditions of use are beyond our control we make no warranties, expressed or implied as to the use of this information or the suitability of the product for a particular purpose.