



HARMONY TIMBER FLOORS

SPEC SHEET ENGINEERED SPOTTED GUM



AUSTRALIAN SPOTTED GUM :	ORIGIN: AUSTRALIA
GRADE: STANDARD ENGINEERED	BOARD SPEC SIZE: ALL BOARD SIZES APPLY 12/2 13.5/3 20/6 RANDOM BOARDS 30% MULTI-PLYWOOD BASE
CUT: CROWN CUT – GRAIN CUT- SAWN OR SLICED	PROFILE: TONGUE & GROOVE – SQUARE EDGE
COLOUR: NATURAL	FINISH: BONA TRAFFIC: UV LACQUER INVISIBLE COATING
SAPWOOD : NO LIMITATION	HOLES: <1MM IN DIAMETER: CONCENTRATION <40 IN ANY 100 CM 2 SPREAD<AVERAGE OF 4 PER 100CM2
TIGHT KNOTS & ASSOCIATED VIODS : <=40MM OR 1/3W<=2/ANY 1M SPREAD	HOLES: >3MM IN DIAMETER: CONCENTRATION <20 IN ANY 100 CM 2 SPREAD<AVERAGE OF 30PER 100CM2 OVER THE LENGTH
TIGHT GUM VEINS: QUARTER SAWN STRAIGHT LINE <=3MM WIDE AGGR.<=1/2L	TIGHT GUM VEINS: BACK SAWN , BLOTCH 2MM DEEP<1000MM LONG AGGR<2/3 OF LENGTH< 3/4 OF FACE WIDTH
LOOSE GUM VEINS: <3=MMWIDE, AGGREGATE <=1/6 L	GUM POCKETS – OVER-GROWTH OF INJURY OTHER POCKETS: <=500MM2 <3MM DEEP
KNOT CHECKS: <2MM WIDE	CHECKS: <=2MM WIDE, IND.<=250MM
STAINS NATURAL MARKS DISCOLOURATION: NO LIMITATION	BLACK SPECKS: NO LIMITATION
OVERWOOD: ALLOWABLE TO STANDARDS	

TECHNICAL PRODUCT DESCRIPTION

Color is a characteristic of NATURAL TIMBER each piece is an individual and variations will occur, this is what gives it, it's natural appearance and beauty. Gum Veins, Checking, visible cracks, worm holes, insect trials, knots, Stains, Colour variations, It is also important to realize that grading rules do not cover either colour or colour variation, even when a single species is chosen there can be a wide variation in colour

- The timber flooring is UV coated for additional surface protection
- The grain is straight & bold & dramatic, sapwood occurs naturally in the Timber which is a distinctive feature of spotted gum
- Spotted Gum is a very popular floor choice for Australians, they love the natural variations and character of the timber
- **JANKA RATING: 11**



HARMONY
TIMBER FLOORS