

V5 / V6

Height Gauges for the Workshop



1.

INTRODUCTION

The vertical measuring instruments V5 and V6 are the descendants of the legendary V+ line, from which thousands of units have already been sold in workshops all over the world and are universally recognized for their easy use and their high quality.

Trimos was the first to offer vertical measuring instruments on the market more than 40 years ago. The V5 and V6 represent a consolidation of know-how accumulated over the years. The very legible display and the user-friendly functions offer exceptional comfort use. But that's not it: The V5 and V6 are equipped with a revolutionary displacement handwheel which offers its user the choice of the displacement mode of the measuring carriage, either manual or motor-driven. Each one of these modes, suffers from no compromise, which means that the user who prefers a manual instrument will not notice a difference with a classic manual instrument and the same applies to the motor-driven displacement. This innovation avoids having to make a difficult choice during the purchase and can accommodate multiple potential users with the same instrument.

- Measuring ranges 400, 700 and 1100 mm
- Extremely easy to use
- Electronically adjustable measuring force
- Manual or motor-driven displacement
- Larger than 300 mm probes as standard
- Vast range of accessories
- All adjustments possible without tools
- RS232 and USB interfaces

- A** Cast iron base for optimal stability
- B** Horizontal displacement handle with buttons for functions and air cushion
- C** Measuring carriage displacement handwheel. Manual or motor-driven mode.
- D** Interchangeable insert holder and probe
- E** Additional probe holder
- F** "Black Mask" display with user-friendly functions
- G** Easy balance adjustment system



2.

DIFFERENCES

V5

The design of the V5 with its side probe holders revives an old Trimos tradition: It enables measuring with long, robust probes guaranteeing an excellent repeatability.

V6

The V6 is of the same calibre as the V5. It's equipped with a more precise measuring system and enables the use of an electronic perpendicular probe.

3.

APPLICATIONS AND FUNCTIONALITIES



Height Measurements

Height, thickness and chain of dimensions measurements



Diameter Measurements

Simultaneous display of diameter and centerline



Min/Max/Delta

The motorization guarantees a perfectly constant measuring force




Perpendicularity

Squareness measurements with electronic probe (V6)



Long Probes

Standard measuring inserts up to 400 mm, with excellent repeatability




Handwheel

Instant switch from the manual to the motor-driven mode



Accessoires

Very large range of accessoires for any type of measurement



Interface

The data transfer via the USB or RS232 port is very easy

4.

DONNEES TECHNIQUES

V5		400	700	1100
Measuring range	mm (in)	407 (16)	711 (28)	1110 (44)
Measuring range with extension	mm (in)	719 (28)	1023 (40)	1422 (56)
Max. permissible errors, B _{MPE}	µm	2.5 + L(mm)/300		
Repeatability, R _{MPE} (2s)	µm	2		
Frontal squareness deviation, S _{MPE}	µm	5	8	11
Maximal Resolution	mm (in)	0.001 (0.00005)		
Measuring force	N	0.75 ÷ 1.5		
Autonomy	h	40		
Interfaces		USB / RS232		
Air cushion		Yes		
Weight	kg	21	24	33

V6		400	700	1100
Measuring range	mm (in)	407 (16)	711 (28)	1110 (44)
Measuring range with extension	mm (in)	719 (28)	1023 (40)	1422 (56)
Max. permissible errors, B _{MPE}	µm	2 + L(mm)/400		
Repeatability, R _{MPE} (2s)	µm	1 (Ø: 2)		
Frontal squareness deviation, S _{MPE}	µm	5	8	11
Maximal Resolution	mm (in)	0.0001 (0.000005)		
Measuring force	N	0.75 ÷ 1.5		
Autonomy	h	20		
Interfaces		USB / RS232		
Air cushion		Yes		
Weight	kg	21	24	33

Note: The above values have been determined according to ISO 13225. They are valid with the standard measuring insert (TA-MI-101), at a temperature of 20 ± 0.5 °C and relative humidity of 50 ± 5%.

STANDARD INSTRUMENT

The V5 and V6 are supplied as follows:

Instrument according to specifications	Charging unit (TA-EL-132)
Measuring insert with ruby ball Ø 4 mm (TA-MI-101)	Calibration certificate
Setting Gauge (TA-MG-104)	User's manual (750 50 0045 03)
Protection cover (TA-TO-114/115/116)	

CODE NUMBERS

V5	V6	
V5-400 700 110 10 05	V6-400 700 110 10 06	Measuring range 400 mm
V5-700 700 110 20 05	V6-700 700 110 20 06	Measuring range 700 mm
V5-1100 700 110 30 05	V6-1100 700 110 30 06	Measuring range 1100 mm

Trimos S.A.

Av. de Longemalle 5
CH-1020 Renens
T. +41 21 633 01 01
info@trimos.ch
www.trimos.ch

