

MULE SX



SPECS

POWER

Maximum Power	9.2 kW {13 PS} / 3,800 rpm
Maximum Torque	27.9 Nm {2.8 kgfm} / 2,200 rpm
Engine	4-stroke Single
Displacement	401 cc
Bore x Stroke	82.0 x 76.0 mm
Compression Ratio	8.3:1
Valve System	OVH
Fuel System	Carburettor
Ignition	Magneto & transistor
Starting	Electric
Cooling	Air-cooled
Lubrication	Forced lubrication, wet sump
Transmission	Automatic, forward/reverse
Primary Reduction Ratio	3.653 ~ 0.794 (belt converter)
Gear Ratio: Forward (High)	2.916 (35/24 x 36/18)
Gear Ratio: Reverse	3.750 (30/16 x 36/18)
Final Reduction Ratio: Front	-
Final Reduction Ratio: Rear	4.000 (64/16)
Final Drive	Gear, dual-mode differential

CAPABILITY

Frame	Ladder type, tubular steel
Front Suspension	Independent, MacPherson strut
Rear Suspension	Unit swing axle
Front Wheel Travel	78 mm
Rear Wheel Travel	79 mm
Steering	Rack and pinion
Rake	9°
Trail	40 mm
Steering Angle (L/R)	43° (IN) / 38° (OUT), 43° (IN) / 38° (OUT)
Front Tyres	22 x 9.00-10
Rear Tyres	22 x 11.00-10
Front Brakes	Dual hydraulic drums
Rear Brake/s	Dual hydraulic drums
Parking Brake	Mechanical, on rear wheels

DETAILS

Dimensions (LxWxH)	2,710 x 1,335 x 1,780 mm
Wheelbase	1,780 mm
Road Clearance	155 mm
Seat Height	765 mm
Curb Weight*	439 kg
Estimated Dry Weight**	421 kg
Fuel Capacity	16 litres
Tread Front / Rear	1,055 mm / 1,000 mm
Turning Radius	3.3 m
Cargo Bed Dimensions (LxWxH)	905 x 1,040 x 245 mm
Cargo Bed Capacity	181 kg
Seating Capacity	2
Vehicle Load Capacity	415 kg
Towing Capacity	500 kg
Lighting	2x halogen headlights
Model Code	KAF400JTFNN