

TECHNICAL SPECIFICATIONS

2026 KTM 1390 SUPER DUKE R

ENGINE

Design	2-CYLINDER, 4-STROKE, V 75°
Displacement	1350 CM ³
Power	190 PS
Torque	145 NM
Transmission	6-SPEED
CO ₂ emissions	139 G/KM
Cooling	LIQUID COOLED WITH WATER/OIL HEAT EXCHANGER
Engine cylinder	TWIN CYLINDER
EMS	KEIHIN EMS WITH RBW AND CRUISE CONTROL, DOUBLE IGNITION
Engine oil	MOTOREX, SAE 10W-50
Engine stroke	4-STROKE
Silencer	STAINLESS STEEL PRIMARY AND SECONDARY SILENCER WITH TWO CATALYTIC CONVERTERS

CHASSIS

Front brake disc diameter **320 MM**

Rear brake disc diameter **240 MM**

Front brake **2 X BREMBO STYLEMA MONOBLOC FOUR PISTON, RADIALLY MOUNTED CALIPER**

Rear brake **BREMBO TWIN-PISTON FIXED CALLIPER, BRAKE DISC**

Chain **525 X-RING**

Frame design **CHROMIUM-MOLYBDENUM-STEEL TRELIS FRAME, POWDER COATED**

Steering head angle **65.3 °**

Rear subframe design **CAST ALUMINIUM / COMPOSITE**

Trail **101 MM**

Wheelbase **1491 MM**

SUSPENSION

Front suspension **WP APEX-USD Ø 48 MM**

Rear suspension **WP APEX-LINKAGE SHOCK**

Suspension travel (front) **125 MM**

Suspension travel (rear) **140 MM**

Front suspension adjustment **COMPRESSION AND REBOUND ADJUSTABLE**

DIMENSIONS

Seat height	834 MM
-------------	---------------

Wheelbase	1491 ± 15 MM
-----------	---------------------

Tank capacity (approx.)	17.5 L
-------------------------	---------------

Ground clearance	149 MM
------------------	---------------

Weight (without fuel)	200.5 KG
-----------------------	-----------------

Weight fully fueled	212.5 KG
---------------------	-----------------

Wheelbase tolerance	15 MM
---------------------	--------------

Front wheel diameter	17 "
----------------------	-------------

Rear wheel diameter	17 "
---------------------	-------------

Front wheel width	3.50 "
-------------------	---------------

Rear wheel width	6 "
------------------	------------

Wheels	3.50 X 17"; 6 X 17"
--------	----------------------------

Wheels	CAST ALUMINIUM WHEELS
--------	------------------------------