

# MULE PRO-DX DIESEL



## SPECS

### POWER

|                              |  |
|------------------------------|--|
| Maximum Power                | 17.8 kW {24 PS} / 3,600 rpm            |
| Maximum Torque               | 52.1 Nm {5.3 kgfm} / 2,400 rpm         |
| Engine                       | 4-stroke In-Line 3-cylinder diesel     |
| Displacement                 | 993 cc                                 |
| Bore x Stroke                | 74.0 x 77.0 mm                         |
| Compression Ratio            | 23.5:1                                 |
| Valve System                 | OHV                                    |
| Fuel System                  | In-line injection pump                 |
| Starting                     | Electric                               |
| Cooling                      | Liquid-cooled                          |
| Lubrication                  | Forced lubrication, wet sump           |
| Transmission                 | Dual range (high/low) CVT with reverse |
| Primary Reduction Ratio      | 3.334 ~ 0.756 (belt converter)         |
| Gear Ratio: Forward (High)   | 1.952 (34/33 x 36/19)                  |
| Gear Ratio: Forward (Low)    | 3.876 (45/22 x 36/19)                  |
| Gear Ratio: Reverse          | 3.009 (27/17 x 36/19)                  |
| Final Reduction Ratio: Front | 6.382 (31/17 x 35/10)                  |
| Final Reduction Ratio: Rear  | 6.245 (31/21 x 55/13)                  |
| Final Drive                  | 2WD/4WD, shaft, dual-mode differential |

### CAPABILITY

|                      |  |
|----------------------|--|
| Frame                | Ladder type, tubular steel                   |
| Front Suspension     | Double wishbone                              |
| Rear Suspension      | Double wishbone                              |
| Front Wheel Travel   | 222 mm                                       |
| Rear Wheel Travel    | 217 mm (left), 220 mm (right)                |
| Steering             | Rack and pinion with Electric Power Steering |
| Rake                 | 4.4°   |
| Steering Angle (L/R) | 40° (IN) / 31° (OUT), 40° (IN) / 31° (OUT)   |
| Front Tyres          | 26 x 9.00-12 4PR                             |
| Rear Tyres           | 26 x 11.00-12 4PR                            |
| Front Brakes         | Dual ø212 mm discs                           |
| Front Calipers       | Two-piston                                   |
| Rear Brake/s         | Dual ø212 mm discs                           |
| Rear Caliper/s       | Single-piston                                |

Parking Brake Dual discs (mechanical)

## DETAILS

|                              |                          |
|------------------------------|--------------------------|
| Dimensions (LxWxH)           | 3,385 x 1,625 x 2,015 mm |
| Wheelbase                    | 2,345 mm                 |
| Road Clearance               | 265 mm                   |
| Seat Height                  | 885 mm                   |
| Curb Weight*                 | 856 kg                   |
| Estimated Dry Weight**       | 817 kg                   |
| Fuel Capacity                | 30 litres                |
| Tread Front / Rear           | 1,385 mm / 1,315 mm      |
| Turning Radius               | 4.8 m                    |
| Cargo Bed Dimensions (LxWxH) | 1,375 x 1,355 x 280 mm   |
| Cargo Bed Capacity           | 453 kg                   |
| Seating Capacity             | 3                        |
| Vehicle Load Capacity        | 695 kg                   |
| Towing Capacity              | 907 kg                   |
| Lighting                     | 2x halogen headlights    |
| Model Code                   | KDF1000ATFNN             |