

People (Inc. driver)

22 or 25

Length

7.0_M or 7.7_M

Power/Torque

110kw/441nm




BEST SELLING BUS IN ITS CLASS



SPECIFICATIONS

	MODEL	LENGTH
Α	Standard LWB 25 Seat Manual (BE64DJRMBFAE)	7.7M
В	Standard LWB 25 Seat Automatic (BE64DJRMBFAF)	7.7M
С	Deluxe SWB 22 Seat Manual (BE64DGRMDFAE)	7.0M
D	Deluxe SWB 22 Seat Automatic (BE64DGRMDFAF)	7.0M
Е	Deluxe LWB 25 Seat Manual (BE64DJRMDFAE)	7.7M
F	Deluxe LWB 25 Seat Automatic (BE64DJRMDFAF)	7.7M

ENGINE	
Engine Version	FUSO 4M50-4AT4 Diesel
Configuration	4 Cyl. In-line DOHC, 4-Valve
Туре	Waste-gate Turbocharged & Air to Air Intercooled
Displacement	4.9 litre (4899cc)
Bore	114mm
Stroke	120mm
Power (ECE R85-00)	110kW @ 2700 rpm
Torque (ECE R85-00)	441Nm @ 1600 rpm
Maximum Engine Speed	2900 rpm
Compression Ratio	17.5:1
Cooling System / Oil Cooler	Water cooled, 17.0L capacity/ Plate type engine oil cooler
Air Cleaner	Dry Paper Element. Forward Mounted Intake System
Emission Control	Silicon Carbide DPF & Catalytic Converter
Emission Level	ADR 80/03 - JP05



FUEL	
Injection System	Bosch Common Rail Electronic Direct Injection
Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity *	100 Litres
Filtration	Main Filter with Water Separator Function
Speed Limiter	Speed Limited 100km/h
Notes	*Max Fill to approx 95% of Air Capacity

COOLING	
Fan Drive	Thermo modulated continuous control (Viscous)
Radiator	Corrugated Fin with Expansion Tank

ELECTRICAL	
Voltage	24V Negative Earth
Alternator Capacity	24V-80 amp
Battery Capacity	2x12V, 52Ah/5hr in Parallel
Headlamp Capacity	Low beam 2x70W
	High beam 2x70W

CLUTCH		
_	ACE	BDF
Clutch Model	FUSO C5W33	N/A
Туре	Single dry plate	N/A
Operation/Specification	Hydraulic Control with Pedal Power Booster	N/A

CONFIGURATION

Low Back Vinyl Bench Seats with Lap Seat Belt Low Back Vinyl Bench Seats with Lap Seat Belt High Back Fabric Seats with Lap/Sash Seat Belt

TRANSMISSION			
Version	A C E FUSO Manual M036S6	B D F Aisin Seiki Co.,Ltd. Automatic M036A6	
Type/Speeds	6 Speed	6 Speed	
Features	Synchromesh 1st-6th	Torque Convertor Ratio: 1.65:1. Lock-up clutch 2nd~6th. Chassis Mounted Transmission Cooler.	
Ratios	1st: 5.175 2nd: 2.913 3rd: 1.682 4th: 1.000 5th: 0.793 6th: 0.669 Rev. 5.1759	1st: 3.742 2nd: 2.003 3rd: 1.343 4th: 1.000 5th: 0.773 6th: 0.643 Rev. 3.539	
Park Interlock	N/A	Ignition Key (On) & Foot Brake Activated	

FRONT SUSPENSION			
Туре	Independent Double Wishbone with Coil springs, Tranverse Leaf Spring and Double Acting Shock Absorbers		

REAR AXLE	
Туре	Full Floating Hypoid
Capacity*	3800kg
Ratio	4.875:1
Notes	*See MAX LOADING for vehicle capacity.

REAR SUSPENSION			
Туре	Steel Suspension		
Details	Long Taper with Stabiliser Bar and Shock Absorbers		

MAX LOADING		
Front	A B E F 2600kg	C D 2440kg
Rear	3800kg	3600kg
Total	6285kg	5900kg

Total	ozoong	oooong	
OPTIONS			
Options	Deluxe Model Op	tion Only (R13): High Back	Vinyl

Type Rack & Pinion with Integral Power Assistance
Thank at minor min mografic and reconstance
Steering Column Tilt Adjustable with Steering Lock

DIVARIES	
Туре	Dual Circuit Vacuum/Hydraulic with ABS Front: Twin Caliper Ventilated Disc with Visual Wear Indicators
	Rear: Drum with Automatic Adjustment
Park Brake	Transmission

WHEELS & TYRES		
Wheel Type	Steel Disc 16x5.5K	
Tyre Size All	Michelin Tyres XJE4 Mix Energy 205/85R16LT 117/115L	
Spare Tyre Carrier	Provided	

SPECIFICATIONS

	MODEL	LENGTH	CONFIGURATION
Α	Standard LWB 25 Seat Manual (BE64DJRMBFAE)	7.7M	Low Back Vinyl Bench Seats with Lap Seat Belt
В	Standard LWB 25 Seat Automatic (BE64DJRMBFAF)	7.7M	Low Back Vinyl Bench Seats with Lap Seat Belt
С	Deluxe SWB 22 Seat Manual (BE64DGRMDFAE)	7.0M	High Back Fabric Seats with Lap/Sash Seat Belt
D	Deluxe SWB 22 Seat Automatic (BE64DGRMDFAF)	7.0M	High Back Fabric Seats with Lap/Sash Seat Belt
Ε	Deluxe LWB 25 Seat Manual (BE64DJRMDFAE)	7.7M	High Back Fabric Seats with Lap/Sash Seat Belt
F	Deluxe LWB 25 Seat Automatic (BE64DJRMDFAF)	7.7M	High Back Fabric Seats with Lap/Sash Seat Belt

CHASSIS		
Туре	Parallel Tapered Channel	with Cross Members
INSTRUMENTS		
Gauges	Speedometer with LCD Odometer & Dual Tripmeter Tachometer (Yellow Zone indicates safe exhaust operating zone) Fuel Level Water Temperature	
Warning Lamps	ABS & Front Disc Wear. Oil Pressure. DPF Indicator.	C D E F ABS & Front Disc Wear. Oil Pressure. DPF Indicator. Door Interlock.

MULTI-MEDIA PACKAGE		
Maps with heavy vehicle weight, length, height & hazardous material selectable restrictions with 3 years of Map updates		
6.1 inch LCD with touch screen control		
Bluetooth® hands free		
CD/DVD player Digital radio DAB+ (also AM/FM for areas not covered by DAB+) USB port for iPod® * & other devices		
1 Reverse Camera fitted as standard Display can accept up to 2 additional cameras#		
* iPod® compatibility requires an additional licenced cable # Cameras available through spare parts		

EXTERIOR	
Windscreen Side Windows	Laminated Tinted with Darker Upper Band Fixed Type with Dark Tint
Body Colour	Rising White with Colour Code Bumpers Black Side Window Sash
Towing Hook	Front

INTERIOR		
Lighting	Access Step Light & 3 Interior Lights	
Floor	Heavy Duty Vinyl Floor Covering	

SAFETY (ACTIVE)	
Brakes	ABS Exhaust Brake Disc Brake Front End
Reverse Warning	Buzzer
Passenger Access Door	Accelerator Interlock & Pre-Warning Buzzer

SAFETY (PASSIVE)	
Body Strength	Fully ADR59/00 Roll Strength Compliant
Emergency Exits	4 Exits (1 LH & 2 RH Windows with Emergency Hammers)
Emergency Operational Decals	Internal & External
Rear Swing Door Direction	Outward Opening
Rear Door Locking	Automatic when Ignition Key in Off Position
Seat Belts - Driver & Driver Assistant	3 Point ERL Lap Sash
Fire Extinguisher	Provided

DRIVER COMFORT & FEATURES		
Driver's Seat	Low Back Sliding with Head Rest Adjustable Height & Back Angle	
Visibility Mirrors	LH & RH External Rear View Additional Front Left Clearance Internal Rear Vision Rear Mounted Reversing	
General	Power Driver's Window. Integrated PA System with Microphone. Cup Holder. Sun Visors (Driver and Front Passenger). Central Locking. Accessory Power Outlet / Cigar Lighter Ashtray.	

AIR CONDITIONING (SEPARATE UNIT)		
Control	Manual	
Capacity	10800 kcal/hr	
Distribution	Integrated Roof Ducts located throughout Cab	
Intake	Switchable Fresh Air Duct on Roof at Rear of Cab	

CABIN HEATI	CABIN HEATING / DEMISTING	
Heaters	Forward Cabin plus Passenger Units throughout Cab	
Demisters	Forward and Rear Cabin	

PASSENGER ACCESS & SEATING				
Passenger Door	A B Bi Fold Vacuum Automatic	C D E F Swing Type Electric Automatic with Step Illumination light & Dash Interlock Warning		
Passenger Seats	Fixed Low Back	Fixed High Back		
Passenger Seat Type	LH single, RH Bench	All Individual (6 Child Restraint Anchorage Points included)		
Seat Belts	ERL 3 Point Drivers Assistant Only ERL 2 Point for Other Seats	ERL 3 Point Lap Sash (ADR68/00)		
Trim	Vinyl	Fabric, Colour Medium Beige		
Grip Handles	Rear Seat (Except above Wheel Arch)	N/A		
Interior	Semi-trimmed	Fully trimmed including Side Windows, Rear Pillars & Emergency Door surrounds		
Other	N/A	Black Exterior Front & RH Door Panel Inserts		
External Trim	N/A	O/Head Storage above Windscreen with Centrally Mounted Clock		
Modesty Panel - Front Passenger Seat	Front Passenger Seat			

SERVICE INTERVALS		
Interval*	10,000km, 12 Months or 200 Hours (whichever occurs first)	
Notes	* based on normal operating conditions and may be reduced when operating under severe conditions.	

SPECIFICATIONS

	MODEL	LENGTH
Α	Standard LWB 25 Seat Manual (BE64DJRMBFAE)	7.7M
В	Standard LWB 25 Seat Automatic (BE64DJRMBFAF)	7.7M
С	Deluxe SWB 22 Seat Manual (BE64DGRMDFAE)	7.0M
D	Deluxe SWB 22 Seat Automatic (BE64DGRMDFAF)	7.0M
Е	Deluxe LWB 25 Seat Manual (BE64DJRMDFAE)	7.7M
F	Deluxe LWB 25 Seat Automatic (BE64DJRMDFAF)	7.7M

CONFIGURATION


Low Back Vinyl Bench Seats with Lap Seat Belt Low Back Vinyl Bench Seats with Lap Seat Belt High Back Fabric Seats with Lap/Sash Seat Belt

WARRANTY	
Basic/Powertrain	3 Years, 100,000kms or 2,000 operating hours (whichever occurs first)
Cab Perforation/Anti Corrosion	3 Years

ATM (TOWING CAPACITY)					
Without Trailer Brakes	715kg				
With Trailer Brakes	A E 1615kg	C 2000kg	D 1100kg	B F 715kg	

PERFORMANCE		
Turning Circle (kerb to kerb) A B E F	CD	
14.4m	12.8m	

DIMENSIONS (MM)			
	АВ	C D	EF
Width Overall (excluding	2070	2070	2070
mirrors)			
Width Front Track	1655	1655	1655
Width Rear Track	1495	1495	1495
A - Length Overall (B+C+D)	7730	6990	7730
B - Length Front Overhang	940	940	940
C - Length Wheelbase	4550	3995	4550
D - Length Rear Overhang	2240	2040	2240
E - Length Passenger Seat Pitch Approx	725	720	720
F - Height Overall	2755	2755	2755
G - Height Floor to Headliner	1860	1860	1860
H - Height Access Door	1755	1690	1755
I - Height Emergency Exit	1480	1480	1480
J - Height First Access Door Step to Ground	380	395	380
K - Height Second Access Door Step to Floor	290	270	290
L - Width Door Access	665	600	615
M - Height Passenger Seat - Right Hand Bench	900	N/A	N/A
N - Height Single	450	465	465
O - Height Driver's Seat	500	500	500
P - Height Passenger Aisle	445	401	401



CALL 1300 429 134

or visit fuso.com.au



Unless specified in writing herein the accessories, applications, bodies or equipment depicted in this document are for illustration purposes only and may not be available from Mercedes-Benz Australia/Pacific Pty Ltd (ABN 23 004 411 410) ("MBAuP"). No representation or warranty whatsoever is given in relation to any accessories, applications, bodies or equipment or suitability of same that are shown herein that may be manufactured, supplied or fitted by a party other than MBAuP. MBAuP reserves the right without notice or obligation to discontinue or make changes to the colour, designs, materials and specifications of the products and options referred to herein at any time. For the most current information and in order to ascertain which accessories, applications, bodies and equipment are available from MBAuP please contact your authorised Mitsubishi FUSO truck and bus dealer. Fuso is a registered trademark of Mitsubishi Fuso Truck & Bus Corporation. Copyright © MBAuP. Reproduction in whole or part prohibited without written approval. "Rosa best selling bus in its class" claim based on Vfacts sales volumes (2004-2015). Part Number TSR70E-SSV1. Valid from 01-Aug-16.