



4010 4WD GEAR OR HST [38HP] / 6110 CAB 4WD SHUTTLE (60HP)

4010/6110 4WD Series Tractors



**FREE 3 YEAR
WARRANTY[^]**

No.1 TRACTOR
COMPANY
IN THE WORLD
BY VOLUME[^]

Mahindra
Rise.

4010 4WD GEAR OR HST [38HP]

These easy to own and operate tractors offer a durable compact design and best-in-class manoeuvrability that are perfect to tackle mowing, tilling, light construction, landscaping and grading. Available in Gear or Hydrostatic Drive Transmission.

KEY FEATURES:

- A quiet engine
- An easy push button PTO
- Easy on/off platform & tilt steering wheel
- Suspension seat, modern dash, switches & controls
- Tractor weight 1390kgs
- Dimensions: 3030mm (l) x 1520mm (w)
- No tools loader removal & convenient loader control



BACKHOE MODEL ANBH76 SPECIFICATIONS	
TRANSPORT	
Transport Height	1905 mm
Transport Overhang	1143 mm
OPERATIONAL	
Maximum Digging Depth	2337 mm
Digging Depth (610mm) Flat Bottom	2286 mm
Overall Operating Height - Fully Raised	3099 mm
Loading Height (bucket @ 60°)	1727 mm
Loading Reach (bucket @ 60°)	1600 mm
Reach From Swing Post	2845 mm
Bucket Rotation	140°
Swing Arc	180°
Stabiliser Spread Operating Position	2311 mm
Stabiliser Down Below Grade	254 mm
System Relief Valve Setting	2248 psi
Digging Force - Bucket	3080 lbs
Digging Force - Dipper	2160 lbs



6110 CAB 4WD SHUTTLE [60HP]

60 horsepower in a cabin tractor with air-conditioning and heating enables working all year round in all climate conditions. The 6110 Shuttle Cab features Synchro-shuttle with 12 forward and 12 reverse speeds, and a 1600 kgs hydraulic lift capacity on the linkage. New standard features on all 10 series Cab models include ergonomic and spacious cabs with flat operator's station for comfort. Standard features on the 6110 include one remote valve, tilt steering wheel and a suspension seat.

The 10 series offers heavy-duty performance at a no-nonsense price. The fuel-efficient engines will help you reduce your operating costs and save money with the value-pricing of these new models.

KEY FEATURES:

- 12F+ 12R Synchro Shuttle
- 1600kgs lift capacity on linkage
- Air conditioning and heating standard
- Agricultural tyres standard
- Tractor weight 2200kgs
- Dimensions: length 3590mm x width 1817mm

Synchro Shuttle Lever



Telescopic Lower Links on 6110



JAPAN
QUALITY
MEDAL
WINNER

FOR MORE INFORMATION ON MAHINDRA PRODUCTS, VISIT:

WWW.MAHINDRA.COM.AU



SPECIFICATIONS

TRACTOR SPECIFICATIONS

ENGINE	4010 4WD	6110 4WD
Type	Indirect Fuel Injection	Fuel Injected Turbo Diesel
Cylinders	3	4
Displacement cc	1826	2435
Engine HP (kW) @ rpm	38 @ 2700	60 @ 2600
TRANSMISSION		
Type	Gear HST	Gear
Number of Gears	3 (range 3) Infinite (3)	12 F/12 R
CLUTCH		
Type	Dry Single Plate	Dry
BRAKES		
Type	Wet Disc	Wet Disc
HYDRAULICS AND LINKAGES		
Type	Dual Gear Pump Open Centre	Dual Gear Pump
Max Lifting Capacity (Kgs)	1200	1600
Implement Pump Flow	31.2 lpm	41.6 lpm
Three Point Linkage	Cat 1	Cat 2
Auxiliary Remotes	1 Optional	1 Standard
PTO		
PTO Type	Independent with Electro-hydraulic engagement	Independent with Electric-hydraulic engagement
Max PTO HP	31	48.5
PTO RPM	540	540
GROUND CLEARANCE		
Min. Ground Clearance (mm)	325	400
STEERING		
Steering Type	Hydrostatic	Hydrostatic/Tiltable
OPERATING WEIGHT		
Total (Kgs)	1390	2200
DIMENSIONS		
Overall Length (mm)	3030	3590
Overall Width (mm)	1520	1817
Turning Radius with Brakes (mm)	2400	3815
TYRES	Industrial	Ag
Front/Rear	10x16.5/43x16.0x20 Standard	9.5 x 20/14.9 x 28 Standard

LOADER SPECIFICATIONS

LOADER	ML401	ML611
TRACTOR MODEL	4010 4WD	6110 4WD
Self Level Mechanism	Yes	Yes
Maximum Lift Height	2587 mm	2932 mm
Clearance Attachment Level	2322 mm	2670 mm
Clearance Bucket Dumped	1854 mm	2091 mm
Reach at Maximum Height	555 mm	543 mm
Maximum Dump Angle	42°	69°
Reach with Attachment on Ground	1800mm	1912 mm
Attachment Rollback Angle	35°	39°
Digging Depth Below Grade	122 mm	131 mm
Overall Height Carry Position	1550 mm	1689 mm
Depth of Attachment (to back of inner shell)	579 mm	579 mm
Height Attachment	563 mm	563 mm
Length Attachment (to pivot pin)	801 mm	801 mm
Lift Capacity Full Height Pivot Pins	926 kgf	1416 kgf
Breakout Force Ground Level, Pivot Pins	1556 kgf	2370 kgf
Relief Valve Setting (Loader Control Valve)	165 kg/cm2	175 kg/cm2
Bucket Width	1675 mm	1830 mm
Bucket Capacity	0.305 cu.m	0.363 cu.m
Hydraulic System	Tractor pump with loader control valve	Tractor pump with loader control valve
Bucket Level indicator	Standard	Standard
Optional Attachments	Grill guard, bale spikes, pallet forks and 4-in-1 buckets	Grill guard, bale spikes, pallet forks and 4-in-1 buckets

Photographs may show overseas models or illustrate non-standard equipment. Please read your Mahindra Tractor manual carefully prior to operation. ^3 Year Engine & Powertrain warranty. #Mahindra & Mahindra Ltd is the No.1 Tractor company in the world by volume.



Mahindra Ag and Auto Australia

4/20 Buttonwood Place,
Willawong QLD 4110 Australia

Phone: +61 7 3213 1211

Toll Free: 1800 45 95 75 (within Australia)

Fax: +61 7 3213 1215

www.mahindra.com.au/ag

Dealer Details:

 FIND US ON FACEBOOK
[FACEBOOK.COM/MAHINDRAAG](https://www.facebook.com/MAHINDRAAG)