

DAILY 4X4 MINIBUS



IVECO BUS

Your partner for sustainable transport

DAILY 4X4 MINIBUS SPECIFICATIONS

DIMENSIONS (mm)

	Wheelbase	3400
	Overall length	6257
H	Overall height	3020
	Front track	1670
	Rear track	1670
	Front ground clearance	255
	Rear ground clearance	255
	Rear overhang	1957
	Turning circle: kerb to kerb	13406
X°	Approach angle	55°
Z°	Departure angle	20°

BODY DIMENSIONS (mm)

Maximum body width	2350
--------------------	------

MASS (kg)

GVM	4495 (opt. 5500)
Towing capacity with braked trailer*	3500*
Front axle capacity	2450
Rear axle capacity	3700

* Subject to individual state regulations and requirements.

All weights with oil, coolant, spare wheel and tyre but not fuel. Subject to manufacturer's tolerance of +/-2%. All above measurements are referred to models with the standard 9.5" x 17.5" on road tyres.

ENGINE

IVECO EURO 6 FIC 3.0i – 4 stroke diesel with direct-injection, variable geometry turbine and intercooler. Water-cooled with electromagnetic fan. Cast-iron engine block with aluminium cylinder head. New generation unijet common rail injection system. The new **EGR+SCR system** of the Euro VI Heavy Duty engine is designed to achieve **the best performances in terms of No_x emissions.**

Basic data

Number of cylinders:	4 (16 valves) in line
Bore x stroke:	95.8 mm x 104 mm
Total displacement:	2998 cm ³
Engine:	3.0L HPT*

*HPT: High Performance Turbine with VGT – Variable Geometry Turbo.

FRAME

Box type steel longitudinal side members with square ends and tubular cross members

Wheelbase (mm):	3400
Side member height (mm):	144
Side member width (mm):	60
Side member thickness (mm):	5

TRANSMISSION

Six speed synchromesh overdrive manual transmission

Type: 6S400 OD – **1st** 5.373, **2nd** 3.154, **3rd** 2.041, **4th** 1.365, **5th** 1.000, **6th** 0.791, **Rev. 1st** 4.838

CLUTCH

Single dry plate. Hydraulically controlled.

External diameter: 280 mm (11")

AXLES

Front: IVECO HS6.07 independent, 2450 kg capacity – Driver Controlled Differential Lock

Rear: IVECO HS8.09 full-floating single reduction, 3700 kg capacity – Driver Controlled Differential Lock

Reduction ratio: 4.87:1

TRANSFER BOX

IVECO 32019 – Permanent all wheel drive torque distribution

Front 32%, Rear 68%, Driver Controlled Differential Lock On Road Ratio

Normal 1:1, Low 1:1.244, Off Road Ratio, Normal 1:3.115, Low 1:3.866

SUSPENSION

Front: Parabolic 3 leaf springs with hydraulic telescopic shock absorbers and reinforced 24mm stabiliser bar

Rear: Parabolic 4 leaf springs, rubber rebound bump stops, hydraulic telescopic shock absorbers and reinforced 28mm stabiliser bar

LIGHTING AND SIGNALLING SYSTEM

Halogen headlamps; twin front and rear fog lamps, twin reverse lamps and engine fan deactivation for water crossing.

DRL Lights (Day Time Running Lights)

WHEELS / TYRES


Standard Wheels: Steel 6" x 17.5", **Option Wheels:** 6.5" x 16"

Tyres: 9.5R17.5 - 120km/h speed limited, **Tyres:** 255/100R16 - 100km/h speed limited

ELECTRICAL SYSTEM

Battery: 12V - 110 Ah, **Alternator:** 12V - 180 A

SINGLE CAB



BRAKING SYSTEM

ESP9 includes ABS, EBD, ASR and Hill Holder

Front / Diameter: Disc brakes / 297 mm

Rear / Diameter: Drum brakes / 270 mm

Parking brake: Manual brake operating on rear axle

Service brakes: Dual circuit with vacuum servo

STEERING

Power steering. Steering wheel diameter 420 mm. Three piece steering column, with connecting universal joints

DRIVER'S CABIN

- Seat belt pretensioners
- Heated, suspended and fully adjustable driver's seat with headrest
- Three point inertia reel belt on all seats
- Cruise control
- Electric windows
- Exterior mirror with integrated wide angle and direction indicators, heated and electronically adjustable
- Overhead console with storage shelf and standard space for additional equipment
- Large dual storage pockets in doors
- Underseat storage
- Document storage compartment
- Glove compartment with added storage
- Additional in-dash storage
- Kerb side observation mirror
- Adjustable steering column
- Driver's airbag

SALOON

- Large rear boot space
- Extra side bins
- 11 and 14 Seat options
- Passenger compartment air conditioner and heating
- Three point inertia reel belt on all seats
- Various levels of interior

DASHBOARD

- Soft-feeling anti-reflective material
- Analogue speedometer
- Analogue tachometer
- Fuel level indicator with reserve light indicator
- Coolant temperature gauge with high temperature indicator light
- Instrument light dimmer switch
- Dash-mounted gear lever with floor mounted transfer case levers
- LCD display panel includes: odometer, trip computer with distance, time, fuel consumption; headlamp orientation (dip/main); clock, vehicle diagnostics information, external temperature, service indicator
- Stereo radio/CD player with Bluetooth

SECURITY

- Central locking with remote control and door locking management
- Steering lock
- Engine immobilizer actuated by transponder on ignition key

CLIMATE CONTROL

Four speed electric fan with five different air distribution modes and cab recirculation. Windshield side window defroster and defogger through side and front fixed position air vents. Temperature-controlled air conditioned cab.

OTHER EQUIPMENT

- 90 litre Diesel fuel tank (Passenger side) + 25 litre Adblue tank (driver side)
- Front tow hook
- Bull bar (Optional)
- Fully mine compatible option

* For more information contact IVECO Bus on ivecobusenquiries@cnhind.com or 1800 602 287



iveco.com.au

**IVECO
BUS**

Your partner for sustainable transport