

ROSA SWB DELUXE

MANUAL or AUTO



People (Inc. driver)

22

Light rigid licence required

Length

7.0_M

Power/Torque

110_{kW} / 441_{Nm}



R
O
S
A
蔷薇



HIGH BACK PASSENGER SEATS WITH 3 POINT BELTS

Specifications

MODEL

A	Deluxe SWB 22 Seat Manual (BE64DGRMDFAE)
B	Deluxe SWB 22 Seat Automatic (BE64DGRMDFAF)


LENGTH

7.0M
7.0M

CONFIGURATION

High Back Fabric Seats with Lap/Sash Seat Belt
High Back Fabric Seats with Lap/Sash Seat Belt

Engine	
Engine Version	FUSO 4M50-4AT4 Diesel
Configuration	4 Cyl. In-line DOHC, 4-Valve
Type	Waste-gate Turbocharged & Air to Air Intercooled
Displacement	4.9 litre (4899cc)
Bore	114mm
Stroke	120mm
Power (ECE R85-00)	110kW @ 2700 rpm
Torque (ECE R85-00)	441Nm @ 1600 rpm
Maximum Engine Speed	2900 rpm
Compression Ratio	17.5:1
Cooling System / Oil Cooler	Water cooled, 17.0L capacity/ Plate type engine oil cooler
Air Cleaner	Dry Paper Element. Forward Mounted Intake System
Emission Control	Silicon Carbide DPF & Catalytic Converter
Emission Level	ADR 80/03 - JP05



Fuel	
Injection System	Bosch Common Rail Electronic Direct Injection
Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity *	100 Litres
Filtration	Main Filter with Water Separator Function
Speed Limiter	Speed Limited 100km/h
Notes	*Max Fill to approx 95% of Air Capacity

Cooling	
Fan Drive	Thermo modulated continuous control (Viscous)
Radiator	Corrugated Fin with Expansion Tank

Electrical	
Voltage	24V Negative Earth
Alternator Capacity	24V-80 amp
Battery Capacity	2x12V, 52Ah/5hr in Parallel
Headlamp Capacity	Low beam 2x70W High beam 2x70W
Fog Light	Halogen

Clutch		
Clutch Model	A FUSO C5W33	B N/A
Type	A Single Dry Plate	B N/A
Operation/Specification	A Hydraulic Control with Pedal Power Booster	B N/A

Transmission		
Version	A FUSO Manual M036S6	B Aisin Seiki Co.,Ltd. Automatic M036A6
Type/Speeds	6 Speed	
Features	A Synchronesh 1st-6th	B Torque Converter Ratio: 1.65:1. Lock-up clutch 2nd-6th. Chassis Mounted Transmission Cooler.
Ratios	A 1st: 5.175 2nd: 2.913 3rd: 1.682 4th: 1.000 5th: 0.793 6th: 0.669 Rev. 5.1759	B 1st: 3.742 2nd: 2.003 3rd: 1.343 4th: 1.000 5th: 0.773 6th: 0.643 Rev. 3.539
Park Interlock	A N/A	B Ignition Key (On) & Foot Brake Activated

Front Suspension	
Type	Independent Double Wishbone with Coil springs, Transverse Leaf Spring and Double Acting Shock Absorbers

Rear Axle	
Type	Full Floating Hypoid
Capacity*	3800kg
Ratio	4.875:1
Notes	*See MAX LOADING for vehicle capacity.

Rear Suspension	
Type	Steel Suspension
Details	Long Taper with Stabiliser Bar and Shock Absorbers

Max Loading	
Front	2440kg
Rear	3600kg
Total	5900kg

Options	
Options	Deluxe Model Option Only (R13): High Back Vinyl Passenger Seats & Seatbelts

Steering	
Type	Rack & Pinion with Integral Power Assistance
Steering Column	Tilt Adjustable with Steering Lock

Brakes	
Type	Dual Circuit Vacuum/Hydraulic with ABS Front: Twin Caliper Ventilated Disc with Visual Wear Indicators Rear: Drum with Automatic Adjustment
Park Brake	Transmission

Wheels & Tyres	
Wheel Type	Alloy Disc 16x5.5K
Tyre Size All	Michelin Tyres XJE4 Mix Energy 205/85R16LT 117/115L
Spare Tyre Carrier	Provided

Specifications

MODEL

A	Deluxe SWB 22 Seat Manual (BE64DGRMDFAE)
B	Deluxe SWB 22 Seat Automatic (BE64DGRMDFAF)

LENGTH

7.0M
7.0M

CONFIGURATION

High Back Fabric Seats with Lap/Sash Seat Belt
High Back Fabric Seats with Lap/Sash Seat Belt

Chassis

Type	Parallel Tapered Channel with Cross Members
------	---

Instruments

Gauges	Speedometer with LCD Odometer & Dual Tripmeter Tachometer (Yellow Zone indicates safe exhaust operating zone) Fuel Level Water Temperature
Warning Lamps	ABS & Front Disc Wear. Oil Pressure. DPF Indicator. Door Interlock.

Multi-Media Package

Satellite Navigation	Maps with heavy vehicle weight, length, height & hazardous material selectable restrictions with 3 years of Map updates				
Colour Display	<table><tr><td>A</td><td>7 inch LCD with touch screen control</td><td>B</td><td>6.2 inch LCD with touch screen control</td></tr></table>	A	7 inch LCD with touch screen control	B	6.2 inch LCD with touch screen control
A	7 inch LCD with touch screen control	B	6.2 inch LCD with touch screen control		
Phone Connectivity	Bluetooth® hands free				
Audio Visual Entertainment	Bluetooth® music streaming compatible Digital radio DAB+ (also AM/FM for areas not covered by DAB+) USB & 3.5mm/AUX port				
Reversing Camera Compatible	<table><tr><td>A</td><td>1 Reverse Camera fitted as standard Display can accept up to 4 additional cameras#</td><td>B</td><td>1 Reverse Camera fitted as standard Display can accept up to 4 additional cameras#</td></tr></table>	A	1 Reverse Camera fitted as standard Display can accept up to 4 additional cameras#	B	1 Reverse Camera fitted as standard Display can accept up to 4 additional cameras#
A	1 Reverse Camera fitted as standard Display can accept up to 4 additional cameras#	B	1 Reverse Camera fitted as standard Display can accept up to 4 additional cameras#		
Optional Accessories (available at additional cost)	Rear Mounted Parking Sensor Kit (High or Low) USB Quick Charge Kit Qi Wireless Charging Pocket for Mobile Devices Tyre Pressure Monitoring System				
Notes	# Cameras available through spare parts				

Exterior

Windscreen	Laminated Tinted with Darker Upper Band
Side Windows	Fixed Type with Dark Tint
Body Colour	Rising White with Colour Code Bumpers Black Side Window Sash
Towing Hook	Front

Interior

Lighting	Access Step Light & 3 Interior Lights
Floor	Heavy Duty Vinyl Floor Covering

Safety (active)

Brakes	ABS Exhaust Brake Disc Brake Front End
Reverse Warning	Buzzer
Passenger Access Door	Accelerator Interlock & Pre-Warning Buzzer

Safety (passive)

Body Strength	Fully ADR59/00 Roll Strength Compliant
Emergency Exits	4 Exits (1 LH & 2 RH Windows with Emergency Hammers)
Emergency Operational Decals	Internal & External
Rear Swing Door - Opening Direction	Outward
Rear Door Locking	Automatic when Ignition Key in Off Position
Seat Belts - Driver & Driver Assistant	3 Point ERL Lap Sash
Fire Extinguisher	Provided

Driver Comfort & Features

Driver's Seat	Low Back Sliding with Head Rest Adjustable Height & Back Angle
Visibility Mirrors	LH & RH External Rear View Additional Front Left Clearance Internal Rear Vision Rear Mounted Reversing
General	Power Driver's Window. Integrated PA System with Microphone. Cup Holder. Sun Visors (Driver and Front Passenger). Central Locking. Accessory Power Outlet / Cigar Lighter Ashtray.

Air Conditioning (Separate Unit)

Control	Full Auto
Capacity	10800 kcal/hr
Distribution	Integrated Roof Ducts located throughout Cab
Intake	Switchable Fresh Air Duct on Roof at Rear of Cab

Cabin Heating / Demisting

Heaters	Forward Cabin plus Passenger Units throughout Cab
Demisters	Forward and Rear Cabin

Passenger Access & Seating

Passenger Door	Swing Type Electric Automatic with Step Illumination light & Dash Interlock Warning
Passenger Seats	Fixed High Back
Passenger Seat Type	All Individual (6 Child Restraint Anchorage Points included)
Seat Belts	ERL 3 Point Lap Sash (ADR68/00)
Trim	Fabric, Colour Medium Beige
Grip Handles	N/A
Interior	Fully trimmed including Side Windows, Rear Pillars & Emergency Door surrounds
External Trim	Black Exterior Front & RH Door Panel Inserts
Other	O/Head Storage above Windscreen with Centrally Mounted Clock
Modesty Panel - Front Passenger Seat	Front Passenger Seat

Service Intervals

Interval*	10,000km or 12 Months (whichever occurs first)
Notes	* based on normal operating conditions and may be reduced when operating under severe conditions.

Warranty

Basic/Powertrain	5 Years or 200,000kms (whichever occurs first)
Cab Perforation/Anti Corrosion	5 Years

ATM (towing capacity)

Without Trailer Brakes	715kg
With Trailer Brakes	2000kg

Performance

Turning Circle (kerb to kerb)	12.8m
-------------------------------	-------

Specifications

MODEL

- A Deluxe SWB 22 Seat Manual (BE64DGRMDFAE)
- B Deluxe SWB 22 Seat Automatic (BE64DGRMDFAF)

LENGTH

- 7.0M
- 7.0M

CONFIGURATION

- High Back Fabric Seats with Lap/Sash Seat Belt
- High Back Fabric Seats with Lap/Sash Seat Belt


Mass (estimated)*

Total*	A	B
	4145kg	4235kg

Note: * Mass (est.) includes oil and water but excludes spare wheel, tools & fuel. Weights provided are subject to 3.5% variation (+/-)

Dimensions (mm)

Width Overall (excluding mirrors)	2070
Width Front Track	1655
Width Rear Track	1495
A - Length Overall (B+C+D)	6990
B - Length Front Overhang	940
C - Length Wheelbase	3995
D - Length Rear Overhang	2040
E - Length Passenger Seat Pitch Approx	720
F - Height Overall	2755
G - Height Floor to Headliner	1860
H - Height Access Door	1690
I - Height Emergency Exit	1480
J - Height First Access Door Step to Ground	395
K - Height Second Access Door Step to Floor	270
L - Height Door Access	600
M - Height Passenger Seat - Right Hand Bench	n/a
N - Height Single	465
O - Height Driver's Seat	500
P - Height Passenger Aisle	401



Call 1800 033 557

or visit fuso.com.au

Unless specified in writing herein the accessories, applications, bodies or equipment depicted in this document are for illustration purposes only and may not be available from Daimler Truck and Bus Australia Pacific Pty Ltd. (ABN 86 618 413 282) (DTB). No representation or warranty whatsoever is given in relation to any accessories, applications, bodies or equipment or suitability of same that are shown herein that may be manufactured, supplied or fitted by a party other than DTB. DTB reserves the right without notice or obligation to discontinue or make changes to the colour, designs, materials and specifications of the products and options referred to herein at any time. For the most current information and in order to ascertain which accessories, applications, bodies and equipment are available from DTB please contact your authorised FUSO Truck and Bus dealer. Fuso is a registered trademark of Daimler Truck and Bus Australia Pacific Pty Ltd. Copyright DTB. Reproduction in whole or part prohibited without written approval. Part Number TSR72A-SSV2. Valid from 01-Oct-19.