

# Product Manual

Accent 100 IP Fixed Type 3



IILUS

# Accent 100 IP Fixed Type 3





Recessed ceiling luminaire with rotationally symmetrical flood or wide flood optics, high colour reproduction, fixed orientation, adjustable depth mechanism for optical assembly. Combine with optical lens and anti-glare accessories for oval, wide spread, or diffuse beam control. High pressure die-cast powdercoated facade from marine-grade aluminium with nano-ceramic pre-treatment and snoot detail. Includes direct fast connector to remote driver. Active power factor correction, current regulation, voltage spike protection.

## System

<b>Power</b>	8W / 7W / 14W
<b>Current</b>	180mA / 350mA
<b>Colour Temperature</b>	2700°K / 3000°K / 4000°K / 2700-1800°K Dim to Warm
<b>Lumen Maintenance</b>	L90 B10 50 000hr
<b>CRI</b>	Ra97
<b>Tm30</b>	R95 F103
<b>Chromacity</b>	<2 SCDM
<b>Articulation</b>	355° Rotation / 0° Tilt
<b>Cut-Out</b>	92mm Round x 95-115mm (7W/8W) / 135-155mm (14W) Depth
<b>Ingress Protection</b>	IP44

		<b>FL - 25°</b>	<b>MFL - 40°</b>	<b>WFL - 60°</b>
<b>8W</b>	<b>2700°K</b>	576lm	626lm	624lm
	<b>3000°K</b>	642lm	680lm	672lm
	<b>4000°K</b>	610lm	615lm	650lm
<b>7W</b>	<b>2700-1800°K</b>	454lm	493lm	492lm
<b>14W</b>	<b>2700°K</b>	874lm	863lm	882lm
	<b>3000°K</b>	952lm	931lm	965lm
	<b>4000°K</b>	1044lm	1020lm	1049lm







Accent IP

Fixed Type 3



Page — 04

# Model References

	FL - 25°	MFL - 40°	WFL - 60°			
<b>8W 2700°K</b>	100 10 006300.011	100 10 006301.011	100 10 006302.011	○	White	Fixed Output
	100 10 006300.021	100 10 006301.021	100 10 006302.021	●	Black	Fixed Output
	100 10 006300.012	100 10 006301.012	100 10 006302.012	○	White	Phase DIM
	100 10 006300.022	100 10 006301.022	100 10 006302.022	●	Black	Phase DIM
	100 10 006300.013	100 10 006301.013	100 10 006302.013	○	White	DALI
	100 10 006300.023	100 10 006301.023	100 10 006302.023	●	Black	DALI
<b>8W 3000°K</b>	100 10 006303.011	100 10 006304.011	100 10 006305.011	○	White	Fixed Output
	100 10 006303.021	100 10 006304.021	100 10 006305.021	●	Black	Fixed Output
	100 10 006303.012	100 10 006304.012	100 10 006305.012	○	White	Phase DIM
	100 10 006303.022	100 10 006304.022	100 10 006305.022	●	Black	Phase DIM
	100 10 006303.013	100 10 006304.013	100 10 006305.013	○	White	DALI
	100 10 006303.023	100 10 006304.023	100 10 006305.023	●	Black	DALI
<b>8W 4000°K</b>	100 10 006306.011	100 10 006307.011	100 10 006308.011	○	White	Fixed Output
	100 10 006306.021	100 10 006307.021	100 10 006308.021	●	Black	Fixed Output
	100 10 006306.012	100 10 006307.012	100 10 006308.012	○	White	Phase DIM
	100 10 006306.022	100 10 006307.022	100 10 006308.022	●	Black	Phase DIM
	100 10 006306.013	100 10 006307.013	100 10 006308.013	○	White	DALI
	100 10 006306.023	100 10 006307.023	100 10 006308.023	●	Black	DALI
<b>7W 2700-1800°K</b>	100 10 006309.011	100 10 006310.011	100 10 006311.011	○	White	Fixed Output
	100 10 006309.021	100 10 006310.021	100 10 006311.021	●	Black	Fixed Output
	100 10 006309.012	100 10 006310.012	100 10 006311.012	○	White	Phase DIM
	100 10 006309.022	100 10 006310.022	100 10 006311.022	●	Black	Phase DIM
	100 10 006309.013	100 10 006310.013	100 10 006311.013	○	White	DALI
	100 10 006309.023	100 10 006310.023	100 10 006311.023	●	Black	DALI
<b>14W 2700°K</b>	100 10 006312.011	100 10 006313.011	100 10 006314.011	○	White	Fixed Output
	100 10 006312.021	100 10 006313.021	100 10 006314.021	●	Black	Fixed Output
	100 10 006312.012	100 10 006313.012	100 10 006314.012	○	White	Phase DIM
	100 10 006312.022	100 10 006313.022	100 10 006314.022	●	Black	Phase DIM
	100 10 006312.013	100 10 006313.013	100 10 006314.013	○	White	DALI
	100 10 006312.023	100 10 006313.023	100 10 006314.023	●	Black	DALI
<b>14W 3000°K</b>	100 10 006315.011	100 10 006316.011	100 10 006317.011	○	White	Fixed Output
	100 10 006315.021	100 10 006316.021	100 10 006317.021	●	Black	Fixed Output
	100 10 006315.012	100 10 006316.012	100 10 006317.012	○	White	Phase DIM
	100 10 006315.022	100 10 006316.022	100 10 006317.022	●	Black	Phase DIM
	100 10 006315.013	100 10 006316.013	100 10 006317.013	○	White	DALI
	100 10 006315.023	100 10 006316.023	100 10 006317.023	●	Black	DALI
<b>14W 4000°K</b>	100 10 006318.011	100 10 006319.011	100 10 006320.011	○	White	Fixed Output
	100 10 006318.021	100 10 006319.021	100 10 006320.021	●	Black	Fixed Output
	100 10 006318.012	100 10 006319.012	100 10 006320.012	○	White	Phase DIM
	100 10 006318.022	100 10 006319.022	100 10 006320.022	●	Black	Phase DIM
	100 10 006318.013	100 10 006319.013	100 10 006320.013	○	White	DALI
	100 10 006318.023	100 10 006319.023	100 10 006320.023	●	Black	DALI
<b>Accessories</b>	980 00 004301.010	Hex Louvre 043				
	980 00 004302.000	Spreader Lens 043				
	980 00 004303.000	Linear Spreader Lens 043				
	980 00 004304.000	Diffuser Lens 043				

iilus.com