


The double header



- Distinctive double heads with unique oval trim design
- Tilt angle range from 0°- 30°
- Suitable for retail and commercial usage

Product info

System Lumen Range	2400lm — 7500lm
System Power	40W, 56W, 72W
Forward Current	500mA, 700mA, 900mA
System Efficacy Range	60lm/W to 104lm/W
Body/Trim Colour	White
Installation Method	Adjustable Recessed
LED Brand	Citizen
Dimming Type	Non-Dimmable
Accessories	Without Accessory
Custom Dimming Type	Available on request



164 x 350mm

Photometric info

Colour Rendering Index (CRI)	CRI90
Colour Temperature (CCT)	3000K, 3000K Vivid, 3500K, 4000K
Beam Angle	14°, 28°, 40°, 60°
Custom Colour Temperature (CCT)	Available on request
Revit Files	Please choose Beam Angle / Power within the Revit file

Compliance and Features




Packaging


Box Weight	2
Box Dimensions L x W x H mm	380 mm x 200 mm x 130 mm
Boxes per Carton	12
Carton Weight	24 KG
Carton Dimensions L x W x H mm	800 mm x 440 mm x 400 mm

Polar distribution diagrams


Callisto 14°



Callisto 28°



Callisto 36°



Callisto 60°

