





Elegant design, made practical

- Great angle control - rotation 0° - 350° and tilt 0° - 60°
- Anti-glare honeycomb louvre accessory available
- 3-circuit track mount and surface mount installation options

Product info

System Lumen Range	850lm
System Power	11W
Forward Current	500mA
System Efficacy Range	77lm/W
Input Voltage	240V
Body/Trim Colour	White, Black
Installation Method	3-Circuit Track Mounted, Surface Mounted
LED Brand	Bridgelux
IP Rating	IP20
Diffuser	Clear
Dimming Type	Phase-Cut Dimmable, Non-Dimmable
Maximum Tilt Angle	60°
Maximum Rotation Angle	350°
Accessories	Without Accessory, Honeycomb Louvre
Warranty	5 years (T&C apply)
Custom Dimming Type	Available on request



Photometric info

Colour Rendering Index (CRI)	CRI80
Colour Temperature (CCT)	3000K
Beam Angle	18°, 35°, 48°
Light Output Ratio (LOR)	>80%
Custom Colour Temperature (CCT)	Available on request

Compliance

RoHS



Packaging

Box Weight	1kg
Box Dimensions L x W x H mm	90 mm x 90 mm x 235 mm, 0 x 90 mm x 235 mm
Boxes per Carton	20, 26, 0
Carton Dimensions L x W x H mm	470 mm x 295 mm x 460 mm