



BONNEY ENERGY VICTORIA PTY LTD

ABN: 42 155 003 973

262 Princes Highway, CORIO VIC 3214

PO Box 191, GEELONG VIC 3220

Tel 61 3 5275 1151

Fax 61 3 5274 1276

BONNEY ENERGY 10W30 ENGINE OIL

PRODUCT DESCRIPTION

10W30 Engine Oil is the ultimate in protection and performance designed for the professional workshop. This superior quality engine oil is made using premium mineral base oils. It meets and exceeds the API SN/CF specifications and is suitable for most types of petrol and four stroke diesel engines, including those engines with small clearances and those operating under the most severe and varied operating conditions, such as high temperature motorway driving or low temperature stop-and-go driving.

10W30 Engine Oil is also ideal for cold starting situations because of excellent low temperature fluidity characteristics whilst also providing protection at operating temperatures. It provides increased engine life since the wear rates associated with older quality engine oils is decreased by up to 20% for cams and 13% for bearings.

10W30 Engine Oil contributes up to 21% less oxidation and more protection from piston deposits compared to older engine oils when tested under the Sequence IIIE test technique. The level of dispersant and detergent additives in **10W30 Engine Oil** contributes to the maintenance of the cleanliness of the engine under all service conditions. The special additives inhibit the formation of sludge especially under the constant cold temperature operation of urban motoring. The high temperature performance **10W30 Engine Oil** is enhanced by the selection of thermally stable base oils, oxidation inhibitors, viscosity improvers and detergents.

SPECIFICATIONS

10W30 Engine Oil meets or exceeds the following demanding performance requirements:

API: SN, SM, SL, SJ, SH, CF, CD

Always consult your vehicle owner's manual for the manufacturer's recommendations.

TYPICAL PROPERTIES

| Property ASTM | Method | Results |
|-------------------------|--------|---------|
| Density (kg/Lt) @ 15°C | D-1298 | 0.867 |
| Viscosity (cSt) @ 100°C | D-445 | 11.1 |
| @ 40°C | D-445 | 81.2 |
| Viscosity Index | D-2270 | 124 |
| Flash Point COC (°C) | D-92 | 216 |
| Pour Point (°C) | D-97 | -27 |

Available in: 205 Litres, 20 Litres, 5 Litres and 1 Litre.

"Bonney Energy has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at <https://www.bonneyenergy.com.au>. Bonney energy takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at <https://www.bonneyenergy.com.au/>

Item Code: BE10W30

Effective: February 2024

RS422051/1