Parallel Road Lot June 2018

This Summary Table is intended as a guide to the development standards for the construction of a new:

- 1 2 storey dwelling house;
- attached development; and
- alterations and additions to dwelling houses and attached development

as complying development on a parallel road lot in Zones R1, R2, R3, R4 and RU5.


Parallel Road Lot means a lot that has boundaries with 2 parallel roads, not including a lane.

Important Notes

- 1. Development standards under the Housing Code are determined by lot area, lot width or a combination of the two. All standards (reflected in all of the following tables) must be complied with.
- 2. The area of a parallel road lot must not be less than 200m² and the width of a lot must not be less than 6m measured at the primary road building line.
- 3. Only 1 dwelling house is permitted on the lot (excluding a secondary dwelling).
- 4. Development standards for excavation, fill, retaining walls and structural supports, drainage, protected tree requirements and protection of adjoining walls associated with dwelling houses are provided under Division 5.
- 5. Development standards for dwelling houses on bush fire prone land, flood control lots and land near the Siding Springs Observatory are provided under Clauses 3.4, 3.5 and 3.6.
- 6. This Table must be read with all clauses under the Housing Code.
- 7. EPI = Environmental Planning Instrument.
- 8. This Summary Table only applies to Part 3 Housing Code, and does not apply to the Transitional Housing Code or any other complying development codes.

For further information:

Codes Hotline – 13 77 88 codes@planning.nsw.gov.au



Example of a Parallel Road Lot

Disclaimer: The information provided, including Summary Tables, is intended to be general information only and does not constitute professional advice and should not be relied upon as such. No liability is accepted for reliance on any information that is provided. You should seek independent professional advice and refer to the relevant legislation, including the State Environmental Planning Policy (Exempt and Complying Development Codes) 2008 (http://www.legislation.nsw.gov.au/#/view/EPI/2008/572) before taking action.



Development Standards for a Parallel Road (based on lot area)

Clause	Built Form							Lot Ar	ea (m²)					
	Development Standards		200–250	>250-300	>300-350	>350-450	>450–560	>560-600	>600–740	>740–900	>900-920	>920-1000	>1000–1500	>1500
3.1	Maximum n storeys	umber of	2											
3.8	Maximum b	uilding	8.5m											
3.9	Maximum gross floor area (% = percentage of lot area) ¹		78%	75%	235m ²	25% + 150m ²	290m²	25% + 150m ²	335m ²	25% + 150m ²	380m²	25% + 150m ²	400m ²	400m ²
3.10 (1) & (3)	Minimum primary road setback	road houses ²												
		In the absence of are 2 dwelling houses within 40m of lot on the same side of the primary road	3m	3m	4.5m	4.5m	4.5m	4.5m	4.5m	4.5m	6.5m	6.5m	6.5m	10m

¹ Please note 1 car parking space is excluded from the calculation of gross floor area. ² Note that there are certain dwelling houses that are not to be included, such as dwelling houses on battle axe lots. See clause 3.10(2).



Clause	Built Form													
	Development Standards		200–250	>250-300	>300-350	>350-450	>450–560	>560-600	>600–740	>740–900	>900–920	>920-1000	>1000–1500	>1500
3.10 (12)	Minimum set parallel road		3m Note: Exce	3m Note: Exceptions to setbacks apply, see clause 3.11 (3), (4), (6) and (7)										
3.10 (13)	Minimum set back from classified road	If a classified road setback is specified in EPI	As specifie	ed by the EP	I									
		No setback specified in EPI	9m											
3.11 (6)								allel road³ fo	or up to or					
3.10 (14)	Minimum set		3m											
3.10 (10)	Minimum rear	Building Height	3m	3m	3m	3m	3m	3m	3m	3m	5m	5m	5m	10m
	setback for parts of building	0 - 4.5m												
	depending on height at that point: Note: Exceptions to side and rear setbacks apply. See	>4.5 - 8.5m	Lesser of 10m or average of 2 adjoinin g dwelling s measure d at 4.5m	8m	8m	8m	8m	8m	8m	8m	12m	12m	12m	15m

If the parallel road is not a classified road.
 Public reserve setback applies to a dwelling house, cabanas, cubby house, garden shed, gazebo, fernery, greenhouse or shed.



Clause	Built Form		Lot Area (m²)											
	Development Standards		200-250	>250–300	>300-350	>350-450	>450–560	>560-600	>600–740	>740–900	>900-920	>920-1000	>1000–1500	>1500
	clause 3.11 (1), (2), (5) and (7) for detail		above existing ground level											
3.11 (5)	Abutting a re	ear lane:	Despite 3.	10 (10), a dv	velling hous	se and attach	ed develop	ment may al	out a rear lar	ne for up to 5	50% of the le	ength of that	boundary	
3.12	Maximum	Setback												
(2)	floor level height of balconies,	<3m	Not permitted	Not permitted	2m	2m	2m	2m	2m	2m	2m	2m	2m	2m
	decks, patios, terraces and verandahs ⁵	3m – 6m	Not permitted	Not permitted	3m	3m	3m	3m	3m	3m	3m	3m	3m	3m
		>6m	Not permitted	Not permitted	4m	4m	4m	4m	4m	4m	4m	4m	4m	4m
3.12 (3)	3.12 Maximum area of 12m ²													
Clause	Landscape Developme Standards	ent						Lot Ar	ea (m²)					
			200-250	>250-300	>300-350	>350-450	>450-560	>560-600	>600-740	>740-900	>900-920	>920-1000	>1000- 1500	>1500
3.13 (1) & (2)	Minimum lar area (% of lo		10%	10%	15%	15%	20%	20%	30%	30%	40%	40%	40%	45%



 $^{^5\}text{Clause}$ 3.12 (1) prohibits side and rear balconies unless the lot area is >300m2 and width is >10m. 6 Minimum length and width of landscaped area is 1.5m x 1.5m.

Side Setbacks (based on lot width and height of development)

Clause	Built Form Development Standards	Lot width	Height of development nearest to the side setback	Minimum Side setback	
3.10	Side setback ⁷	6m - 10m	0m – 5.5m	900mm	
(4)	Built to boundary setbacks may apply for lot widths 6-12.5m		>5.5m – 8.5m	(Building height – 5.5m) ÷ 4 + 0.9m	
	(see below)	>10m - 18m	0m – 4.5m	900mm	
	Note: Exceptions to side and rear setbacks apply. See clause 3.11 (1) & (2) for detail		>4.5m - 8.5m	(Building height – 4.5m) ÷ 4 + 0.9m	
		>18 - 24m	0m – 4.5m	1.5m	
			>4.5m - 8.5m	(Building height – 4.5 m) ÷ $4 + 1.5$	
		>24m	0m – 8.5m	2.5m	

⁷ See clause 3.10(4)



Development Standards for a Parallel Road Lot (based on lot width)

Clause	Built Form Development Standards	Lot Width (at the building line)								
		6m - 8m	>8m -10m	>10m - 18m	>18m - 24m	>24m				
3.10 (5) & (6)	Built to boundary setback The development may be built to one side boundaries (depending on lot width) if: a) there is a wall of a building on the adjoining lot of masonry construction within 900mm of the boundary with no windows, doors or other openings; or b) there is no wall of a building on the adjoining lot within 900mm of the boundary See clause 3.10 (7) for maximum height of built to boundary wall requirements; and 3.10 (8) & (9) for maximum length	may build to 1 or both side boundaries	may be built to 1 side boundary	If lot not wider than 12.5m may build to 1 side boundary	Not permitted	Not permitted				
3.16 (6)	Maximum width of garage doors facing road	3.2m	3.2m	If lot not wider than 12m - 3.2m If lot >12m - 6m	6m	6m				
Clause	Amenity Development Standards	Lot width (at the building line)								
		6m - 8m	>8m -10m	>10m - 18m	>18m - 24m	>24m				
3.14 & 3.15	Refer to clause 3.14 Building design and 3.15 Privacy screens for windows, balconies, decks and patios for additional amenity requirements									
3.16 (1)	Car parking space required on lot	Not required	1 space required	1 space required	1 space required	1 space required				
	Note: See clause 3.16 for additional requirements. Please note exclusion of required car parking from calculation of gross floor area									



3.16	Primary road Garage and	Dwelling primary road	
(5)	carport setback	setback	
	Note: See clause 3.16 for	<4.5m	5.5m
	additional requirements		
	additional requirements	4.5m or greater	1m or more behind the building line

Landscaping Development Standards

Clause	Landscape Development Standards	Lot Area (m²)							
		6m – 8m	>8m - 10m	>10m -18m	>18m – 24m	>24m			
3.13 (2) & (3)	Minimum area forward of the building line to be landscaped ⁸	25% of area forward of building line	25% of area forward of building line	25% of area forward of building line	50% of area forward of building line	50% of area forward of building line			
3.13 (3)	Proportion of required landscaped area that must be behind the building line	50%							
3.13 (4)	Minimum area of principal private open space	16m ²	16m ²	24m²	24m ²	24m²			

 $^{^{8}}$ Minimum length and width of landscaped area is 1.5m x 1.5m.

