

Solis-1P(7-8)K-5G

Solis Single Phase Inverters



360 degree

Features:

- Max. efficiency 98.1%
- Complies with all state network requirements
- Integrate with adjustable Volt-Watt and Volt-Var function
- DRM integrated, fully comply with AS4777.2:2020
- Built-in DC-PV2 Switch, comply with AS/NZS 5033 requirements
- Support 24h consumption monitoring with a smart meter
- 2 MPPT design with precise MPPT algorithm
- Wide voltage range and low startup voltage
- AFCI protection, proactively reduces fire risk
- Integrated Export Power Manager(EPM)
- Voltage active power and reactive power
- Lightweight, only 13.3kg – easy installation
- Friendly and adaptable connection to the grid



Model:

Solis-1P7K-5G Solis-1P8K-5G

Datasheet

Model Name	Solis-1P7K-5G	Solis-1P8K-5G
Input DC		
Recommended max. PV power	9.3 kW	10.6 kW
Max. input voltage		600 V
Rated voltage		330 V
Start-up voltage		120 V
MPPT voltage range		90-520 V
Max. input current		12.5 A / 25 A
Max. short circuit current		19.5 A / 30 A
MPPT number/Max. input strings number		2/3
Output AC		
Rated output power	7 kW	8 kW
Rated apparent output power	7 kVA	8 kVA
Max. apparent output power	7 kVA	8 kVA
Max. output power	7 kW	8 kW
Rated grid voltage		1/N/PE, 230 V
Rated grid frequency		50 Hz
Rated grid output current	33.5 A	34.8 A
Max. output current	33.5 A	34.8 A
Power Factor		>0.99 (0.8 leading - 0.8 lagging)
THDi		<3%
Efficiency		
Max. efficiency		98.1%
EU efficiency		97.3%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Surge protection		Yes
Grid monitoring		Yes
Anti-islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Yes (PV2 Switch)
Integrated AFCI (DC arc-fault circuit protection)		Yes ⁽¹⁾
General Data		
Dimensions (W*H*D)		310*543*180 mm
Weight		13.3 kg
Topology		Transformerless
Self consumption (night)		<1 W
Operating ambient temperature range		-25 ~ +60°C
Relative humidity		0-100%
Ingress protection		IP65
Cooling concept		Natural convection
Max. operation altitude		2000 m
Grid connection standard		AS/NZS 4777.2:2020, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530
Safety/EMC standard		IEC 62109-1/-2, IEC 61000-6-1/-2/-3/-4
Features		
DC connection		MC4 connector
AC connection		Quick connection plug
Display		LCD
Communication		RS485, Optional: Wi-Fi, GPRS
Country of manufacture		China

(1) Activation required.