

DT Series

Dual MPPT, Three Phase



Technical Data

GW20K-DT

PV String Input Data

Max. DC Input Power (Wp)	26600
Max. DC Input Voltage (V)	1000
MPPT Range (V)	200~850
Start-up Voltage (V)	250
Min. Feed-in Voltage(V)	280
Nominal DC Input Voltage (V)	620
Max. Input Current (A)	22/22
Max. Short Current (A)	27.5/27.5
No. of MPP Trackers	2
No. of Input Strings Per MPP Tracker	2

AC Output Data

Nominal Output Power (W)	20000
Max. Output Apparent Power (VA)	20000
Nominal Output Voltage (V)	400, 3L/N/PE
Nominal Output Frequency (Hz)	50/60
Max. Output Current (A)	30
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)
Output THDi (@Nominal Output)	<1.5%

Efficiency

Max. Efficiency	98.4%
European Efficiency	>98.1%

Protection

PV String current Monitoring	Integrated
Anti-Islanding Protection	Integrated
Input Reverse Polarity Protection	Integrated
Insulation Resistor Detection	Integrated
Residual Current Monitoring Unit	Integrated
Output Over Current Protection	Integrated
Output Short Protection	Integrated
Output Over Voltage Protection	Integrated
DC SPD Protection	Integrated (Type III)
AC SPD Protection	Integrated (Type III)

General Data

Operating Temperature Range (°C)	-25~60
Relative Humidity	0~100%
Operating Altitude (m)	≤4000
Cooling	Fan Cooling
Noise (dB)	<45
User Interface	LCD & LED
Communication	RS485 or WiFi
Weight (kg)	39
Size (Width*Height*Depth mm)	516*650*203
Protection Degree	IP65
Night Self Consumption (W)	<1
Topology	Transformerless