

Product Guide	
<p>The Tas Oak vinyl plank flooring has a total thickness of 5 mm, with a 0.55 mm PUR wear layer, hence its high durability, resistance to wear and tear, provides supportive & warmer underfoot comfort, excellent acoustic properties, & most important of all that they are incredibly easy to clean and maintain.</p> <p>The Tas Oak Collection can be easily installed on top of almost any surface. Thanks to the loose lay system, the product can be easily removed and replaced. The Tas Oak Collection contains a fiberglass reinforcement layer throughout for superior stability.</p>	<p>The Tas Oak Collection is backed by a 15 year domestic Warranty and a 7 year Commercial Warranty.</p> <p>Experience unlimited design Possibilities and be inspired by the The Tas Oak vinyl planks.</p> <p>The Tas Oak Collection provides a wide variety of natural or abstract wood designs in a plank format, For instance, the Tas Oak range contains light to dark shades, natural to extravagant looks, and rustic to urban feels, so you can instantly modernise any space, or simply transform it into a homely feel.</p> <p>The Tas Oak Collection (The product) does not contain any harmful fillers and plasticizers and is free of VOC emissions and formaldehyde most important of all they are 100% recyclable</p>
Installation Guide	
<p>Loose lay for areas up to and including 5m2 ONLY.</p> <p>Anything over 5m2 either pressure sensitive or hard set adhesive to be used. On Stairs only use hard set adhesive.</p> <p>Product should acclimatise for 48 hours prior to installation.</p>	<p>Vinyl planks to be layed hard up against the perimeter of the room.</p> <p>Underfloor Heating , not recommended. For best results the floors should comply with the Australian Standards & Tolerance Guide 2015.</p> <p>Allow 5% for wastage and cutting. Check each plank for any manufacturing defects prior to installation.</p>