

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB600.11

Data Sheet No: DS501
Issue Date: 10th January 2020

Version No: 002
Page 1

1.0 – Identification of the substance/mixture and of the company/undertaking

1.1 – Product Identification

Trade name: Whiteboard Ink WB600.11
Substance name: n/a
Index No: n/a
CAS-No: n/a
EC-No: n/a

1.2 – Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture: Preparation for use in writing instruments
Recommended restrictions on use: No information available

1.3 – Details of the supplier of the safety data sheet

Supplier: Officeworks Ltd.
236-262 East Boundary Road
Bentleigh East VIC 3165
Australia
Tel: 1300 633 423
ABN: 36 004 763 526

1.4 – Emergency telephone number

POISONS INFORMATION CENTRE 13 11 26

2.0 - Hazards Identification

2.1 – Classification of the substance or mixture

Regulation (EC) No. 1272/2008			
Hazard class	Hazard category	Target organs	Hazard statements
Flammable liquids	2	n/a	H225
Serious eye damage/eye irritation	2	eyes	H319
Aquatic chronic	2	n/a	H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2 – Label Elements

Labelling according to Regulation (EC) No. 1272/2008

Hazard Symbols:



Signal word:

DANGER

Hazard statements:

H225 Highly flammable liquid and vapour
H319 Causes serious eye irritation
H411 Toxic to aquatic life with long lasting effects

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB600.11

Data Sheet No: DS501

Version No: 002

Issue Date: 10th January 2020

Page 2

Precautionary statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P243 Take precautionary measures against static discharge
- P280 Wear protective gloves/protective clothing/eye protection
- P305/P351/P338 IF IN EYES: rinse cautiously with water for several minutes
- Remove contact lenses, if present and easy to do. Continue rinsing
- P337/P313 If eye irritation persists: get medical advice/attention
- P273 Avoid release to the environment
- P403/P235 Store in a well-ventilated place. Keep cool.

2.3 – Other hazards

No other information available.

3.0 - Composition / information on ingredients

3.1 – Substances

Chemical nature: mixture

Chemical name	REACH Reg. No.	CAS No.	EC No.	Amount (%)
Ethanol	01-2119457610-43	64-17-5	200-578-6	<70%
Propan-2-ol	01-2119457558-25	67-63-0	200-661-7	<16%
Dioctyl maleate	01-2119524002-60	142-16-5	205-524-5	<10%

Chemical name	Classification according to Regulation (EC) No. 1272/2008
Ethanol	H225 (2), H319 (2)
Propan-2-ol	H225 (2), H319 (2), H336 (3)
Dioctyl maleate	H373(2), H410(1)

For the full text of the H-Statements mentioned in this Section, see Section 16.

4.0 - Description of first aid measures

4.1 – Description of first aid measures

General advice: Take off all contaminated clothing immediately

In case of inhalation: Remove to fresh air. If symptoms persist, seek medical advice. If unconscious place in recovery position

In case of skin contact: Wash off with plenty of water. If skin irritation persists, seek medical advice

In case of eye contact: Rinse thoroughly with plenty of water, also under the eyelids. Consult an eye specialist immediately

4.2 – Most important symptoms and effects, both acute and delayed

No information available

4.3 - Indication of immediate medical attention and special treatment needed

Treat symptomatically. No further information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB600.11

Data Sheet No: DS501

Version No: 002

Issue Date: 10th January 2020

Page 3

5.0 – Firefighting measures

5.1 – Extinguishing media

Suitable extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide
Unsuitable extinguishing media: High volume water jet

5.2 – Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Highly flammable. Vapours may form explosive mixtures with air. In case of fire hazardous decomposition products may be produced, such as carbon monoxide (CO) and carbon dioxide (CO₂).

5.3 - Advice for firefighter

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Wear appropriate body protection (full protective suit)

Further information: Cool closed containers exposed to fire with water spray. Heating will cause a pressure rise – with risk of bursting. Collect contaminated fire extinguishing water separately. This must not be discharged into drains

6.0 – Accidental release measures

6.1 – Personal precautions, protective equipment and emergency procedures

Personal precautions: Use personal protective equipment. Provide adequate ventilation. Keep away from heat and sources of ignition. Avoid contact with skin and eyes. Do not breathe vapours.

6.2 – Environmental precautions

Environmental precautions: Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration

6.3 – Methods and materials for containment and cleaning up

Procedure: Contain spillage, and then collect with non-combustible absorbent material (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see Section 13)

Further information: Treat recovered material as described in Section 13

6.4 – Reference to other sections

For personal protection see Section 8

7.0 – Handling and storage

7.1 – Precautions for safe handling

Advice on safe handling: Keep container tightly closed. Ensure adequate ventilation. Avoid contact with skin and eyes. Do not breathe vapours. Emergency eye wash fountains and emergency showers should be available in the immediate vicinity

Hygiene measures: Keep away from food, drink and animal feeding stuffs. Smoking, eating and drinking should be prohibited in the application area. Wash hands before

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB600.11

Data Sheet No: DS501

Version No: 002

Issue Date: 10th January 2020

Page 4

breaks and at the end of the working day. Take off all contaminated clothing immediately. Avoid contact with skin and eyes. Do not breathe vapours of spray mist

7.2 – Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers:	Keep in an area equipped with solvent resistant flooring. Store in original container
Advice on protection against fire and explosion:	Combustible liquid. Keep away from sources of ignition – no smoking. Take measures to prevent the build-up of electrostatic charge. Vapours may form explosive mixtures in air. Use only in an area containing explosion proof equipment
Further information on storage conditions:	Keep tightly closed in a dry and cool place. Keep in a well-ventilated place. Keep away from heat. Keep away from direct sunlight
Advice on common storage:	Incompatible with oxidizing agents. Keep away from food, drink and animal feeding stuffs

7.3 – Specific end uses

Specific uses(s): No information available

8.0 – Exposure controls/personal protection

8.1 – Control parameters

Ethanol (CAS No. 64-17-5)

Regulatory basis:	UK. EH40 Workplace Exposure Limits (WELs)
Regulatory list:	EH40 WEL
Value type:	Time Weighted Average (TWA)
Value:	1000 ppm
Value :	1920 mg/m ³

Propan-2-ol (CAS No. 67-63-0)

Regulatory basis:	UK. EH40 Workplace Exposure Limits (WELs)
Regulatory list:	EH40 WEL
Value type:	Time Weighted Average (TWA)
Value:	400 ppm
Value :	999 mg/m ³
Regulatory basis:	UK. EH40 Workplace Exposure Limits (WELs)
Regulatory list:	EH40 WEL
Value type:	Short Term Exposure Limit (STEL)
Value:	500 ppm
Value :	1250 mg/m ³

8.2 – Exposure controls

Engineering measures:	Refer to protective measures listed in Sections 7 and 8
Respiratory protection :	Required, if exposure limit is exceeded (e.g. OEL). Respirator with a gas filter. Recommended filter type: A

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB600.11

Data Sheet No: DS501

Version No: 002

Issue Date: 10th January 2020

Page 5

Hand protection:	Wear suitable gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Protective gloves should be replaced at first signs of wear Butyl rubber, 0.5mm, Fluorocarbon rubber, 0.4mm
Eye protection:	Tight fitting safety goggles
Skin and body protection:	Wear suitable protective clothing
Environmental protection:	Do not let product enter drains. If the product contaminates rivers and lakes or drains inform respective authorities

9.0 – Physical and chemical properties

9.1 – Information on basic physical and chemical properties

Appearance:	Various colours, liquid
Odour:	Alcohol-like
Odour threshold:	No data available
pH:	No data available
Melting point / freezing point:	-114.5°C
Initial boiling point/boiling range:	78.3°C
Flash point:	12°C
Evaporation rate:	No data available
Flammability:	No data available
Upper/lower flammability or explosive limits:	15% (V), 3.5% (V)
Vapour pressure:	No data available
Vapour density:	No data available
Relative density:	No data available
Solubility:	Miscible in water, readily miscible with solvents
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	425°C
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidising properties:	No data available

9.2 – Other information

No further information available

10.0 – Stability and reactivity

10.1 – Reactivity

Advice: Stable under recommended storage conditions

10.2 – Chemical Stability

Advice: Stable under normal conditions

10.3 – Possibility of hazardous reactions

Hazardous reactions: No information available

10.4 – Conditions to avoid

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB600.11

Data Sheet No: DS501

Version No: 002

Issue Date: 10th January 2020

Page 6

Conditions to avoid: Heat, flames and sparks

10.5 – Incompatible materials

Materials to avoid: Alkali metals, alkaline earth metals, strong oxidizing agents, nitric acid, sulphuric acid, peroxides (e.g. hydrogen peroxide)

10.6 – Hazardous decomposition products

Hazardous decomposition: Under fire conditions: carbon monoxide (CO), carbon dioxide (CO₂)

11.0 – Toxicological information

11.1 – Information on toxicological effects

Ethanol (CAS No. 64-17-5)

Oral

Value type: LD50
Value: >2000 mg/Kg
Species: rat

Inhalation

Value type: LC50
Value: >20 mg/L
Exposure time: 4 h
Species: mouse

Dermal

Value type: LD50
Value: >2000 mg/Kg
Species: rabbit

Propan-2-ol (CAS No. 67-63-0)

Oral

Value type: LD50
Value: 5840 mg/Kg
Species: rat

Inhalation

Value type: LC50
Value: >25 mg/L
Exposure time: 6 h
Species: rat

Dermal

Value type: LD50
Value: >13900 mg/Kg
Species: rabbit

Diethyl maleate (CAS No.142-16-5)

Oral

Value type: LD50
Value: >2000 mg/Kg
Species: rat

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB600.11

Data Sheet No: DS501

Version No: 002

Issue Date: 10th January 2020

Page 7

Dermal
Value type: LD50
Value: 15 mg/Kg
Species: rat

12.0 – Ecological information

12.1 – Toxicity

Ethanol (CAS No 64-17-5)

Fish

Species: Pimephales promelas (fathead minnow)

Value type: LC50

Value: 15300 mg/L

Exposure time: 96 h

Daphnia and other aquatic invertebrates

Species: daphnia magna

Value type: EC50

Value: 12340 mg/L

Exposure time: 48 h

Algae

Species: Chlorella vulgaris (Fresh water algae)

Value type: EC50

Value: 275 mg/L

Exposure time: 72 h

Bacteria

Species: Paramecium caudatum

Value type: EC50

Value: 5800 mg/L

Exposure time: 4 h

Propan-2-ol (CAS No 67-63-0)

Fish

Species: Pimephales promelas (fathead minnow)

Value type: LC50

Value: 9640 mg/L

Exposure time: 96 h

Daphnia and other aquatic invertebrates

Species: daphnia magna

Value type: EC50

Value: 9714 mg/L

Exposure time: 24 h

Algae

Species: Scenedesmus subspicatus

Value type: EC50

Value: >100 mg/L

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB600.11

Data Sheet No: DS501

Version No: 002

Issue Date: 10th January 2020

Page 8

Exposure time: 72 h
Bacteria
Value type: EC50
Value: >100 mg/L , no harming action

Dicotyl maleate (CAS No 142-16-5)

Fish
Value type: LC50
Value: 86 mg/L
Exposure time: 48 h
Daphnia and other aquatic invertebrates
Species: daphnia magna
Value type: EC50
Value: >0.76 mg/L
Exposure time: 48 h
Algae
Value type: IC50
Value: >100 mg/L
Exposure time: 72 h

12.2 – Persistence and biodegradability

No data available

12.3 – Bioaccumulative potential

No data available

12.4 – Mobility in soil

Mobile in water environment

12.5 – Results of PBT and vPvB assessment

No data available

12.6 – Other adverse effects

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

13.0 – Disposal considerations

13.1 – Waste treatment methods

Product: Disposal together with normal waste is not allowed. Special disposal required according to local regulations. Do not empty into drains. Contact waste disposal services

Contaminated packaging: Empty contaminated packaging thoroughly. They can be recycled after thorough and proper cleaning. Packaging that cannot be cleaned is to be disposed of in the same manner as the product. Do not burn, or use a cutting torch on the empty drum. Risk of explosion

14.0 – Transport Information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB600.11

Data Sheet No: DS501

Version No: 002

Issue Date: 10th January 2020

Page 9

14.1 – UN Number

1993

14.2 – UN proper shipping name

ADR: Flammable Liquid n.o.s (contains ethanol)
RID: Flammable Liquid n.o.s (contains ethanol)
IMDG: Flammable Liquid n.o.s (contains ethanol)
IATA-DGR : Flammable Liquid n.o.s (contains ethanol)

14.3 – Transport hazardous class(es)

Labels/classification code/ hazard identification number /tunnel restriction code

ADR: 3 ; F1 ; 33 : (D/E)
RID: 3 ; F1 ; 33
IMDG : 3 ; (F-E, S-E)
IATA-DGR : 3

14.4 – Packing group

ADR: II
RID: II
IMDG: II

14.5 – Environmental hazards

Labelling according to 5.2.1.8 ADR:

Labelling according to 5.2.1.8 RID:

Labelling according to 5.2.1.6.3 IMDG:

Labelling according to IATA-DGR :

Classification as environmentally hazardous according to 2.9.3 IMDG: Yes

Classified as 'P' according to 2.10 IMDG: Yes



14.6 – Special precautions for user

Not applicable

14.7 – Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IMDG: Not applicable

15.0 – Regulatory Information

15.1 – Safety, health and environmental regulations/legislation specific for the substance or mixture

All components are REACH registered or are exempt from REACH registration

Our inks do not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57)

All components are listed on TSCA list of active substances

15.2 – Chemical safety assessment

No information available

16.0 – Other Information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) and (EC) No. 1272/2008 (CLP)
Whiteboard Ink WB600.11

Data Sheet No: DS501

Version No: 002

Issue Date: 10th January 2020

Page 10

16.1 – Full text of H-Statements referred to under Sections 2 and 3

H225:	Highly flammable liquid and vapour
H319:	Causes serious eye irritation
H336:	May cause drowsiness or dizziness
H373:	May cause damage to organs through prolonged or repeated exposure
H410:	Very toxic to aquatic life with long lasting effects
H411:	Toxic to aquatic life with long lasting effects

16.2 – Further information

Other:	The information provided in this safety data sheet is correct to our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements and is not to be considered as a warranty or quality specification and does not constitute a legal relationship. The information contained in this safety data sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text
HS Tariff code:	32159070