

PIXMA HOME OFFICE TR7660

TECHNICAL SPECIFICATIONS



Canon

PIXMA HOME OFFICE TR7660

The All-In-One Home Office Printer



EQUIPPED WITH ALL THE BASIC HOME OFFICE PRINTER FUNCTIONS

The PIXMA HOME OFFICE TR7660 is a home office printer that has the features you require for personal business such as print, copy, scan, and fax.



EFFICIENT PRINTING

The PIXMA HOME OFFICE TR7660 offers high productivity printing with print speeds of approximately 15.0 ipm for black and 10.00 ipm for colour.



EASY SETUP WITH YOUR PC OR SMARTPHONE

The PIXMA HOME OFFICE TR7660 has improved Wi-Fi connectivity for simple setup, enabling quick and easy printing from your computer or smartphone. Connecting to a smartphone is even easier with the QR code direct connection function.



AUTO DUPLEX PRINT

Save time and money with the auto duplex printing function, which automatically prints on both sides of the paper.



AUTO DOCUMENT FEEDER

Scan or copy your documents efficiently with the auto document feeder function.



What inks can I use with my printer?



PIXMA HOME OFFICE TR7660 | SPECIFICATIONS

GENERAL FEATURES	
Model	PIXMA HOME OFFICE TR7660
Ink Type	5 Individual Ink Tanks (PGBK / C / M / Y / BK)
Maximum Print Resolution	4,800 dpi ² x 1,200 dpi
Size	Approx. 438 x 350 x 190 Approx. 17.3 x 13.8 x 7.5
Weight	Approx. 7.9 kg Approx. 17.3 lbs
Display	3.0" / 7.5 cm LCD (Touch Screen, Colour)
Paper capacity- Auto document feeder	Paper Handling (Plain Paper)- A4 / LTR: 20, LGL: 5
Interface	USB / Wireless / QR code
Input Power	AC 100 V - 240 V, 50 Hz / 60 Hz
PRINT SPEED	
Document: Colour ^{*3}	Approx. 10.0 ipm
Document: Black & White ^{*3}	Approx. 15.0 ipm
Photo (4" x 6") ^{*3}	Approx. 37 sec
POWER CONSUMPTION	
OFF	Approx. 0.3 W
Standby (MFP: scanning lamp is off) USB connection to PC	Approx. 1.0 W
Standby (all ports connected, MFP: scanning lamp is off)	Approx. 1.8 W
Copying ^{*28} USB connection to PC	Approx. 13 W
ENVIRONMENT	
Operating Environment ^{*24}	Temperature: 5 °C - 35 °C, Humidity: 10 %RH - 90 %RH (no dew condensation)
Recommended Environment ^{*25}	Temperature: 15 °C - 30 °C, Humidity: 10 %RH - 80 %RH (no dew condensation)
Storage Environment	Temperature: 0 °C - 40 °C, Humidity: 5 %RH - 95 %RH (no dew condensation)
ACOUSTIC NOISE (PC PRINT)	
Quiet Mode	Available
Acoustic Noise (PC Print) Plain Paper ^{*27}	Approx. 46.5 dB(A)
PRINT HEAD / INK	
Number of Nozzles	Total 4,096 nozzles (PGBK / C / M: each 1,024 nozzles, Y / BK: each 512 nozzles)
Ink Tank	5 Individual Ink Tanks (PGBK / C / M / Y / BK)
PRINTABLE WIDTH	
	Up to 203.2 mm (8") / Borderless: Up to 216 mm (8.5")
PRINTABLE AREA	
Borderless Printing ^{*4}	Top / Bottom / Right / Left margin: each 0 mm
Bordered Printing	• #10 Envelope / DL Envelope Top: 8 mm, Bottom: 12.7 mm, Right: 5.6 mm, Left: 5.6 mm
	• Square (127 mm x 127 mm) Top: 6 mm, Bottom: 6 mm, Right: 6 mm, Left: 6 mm
	• Square (89 mm x 89 mm) Top: 5 mm, Bottom: 5 mm, Right: 5 mm, Left: 5 mm
	• LTR / LGL Top: 3 mm, Bottom: 5 mm, Right: 6.3 mm, Left: 6.4 mm
Bordered Auto 2-sided printing	• Other Top: 3 mm, Bottom: 5 mm, Right: 3.4 mm, Left: 3.4 mm
	• LTR Top: 3 mm, Bottom: 5 mm, Right: 6.3 mm, Left: 6.4 mm
	• Other Top: 5 mm, Bottom: 5 mm, Right: 3.4 mm, Left: 3.4 mm

PIXMA HOME OFFICE TR7660 | SPECIFICATIONS (CONTINUED)

SUPPORT MEDIA

Rear Tray	Plain Paper (64 g/m2 - 105 g/m2), High Resolution Paper (HR-101N), Photo Paper Pro Platinum (PT-101), Photo Paper Plus Glossy II (PP-301) (for Pan-American / Oceania), Photo Paper Pro Luster (LU-101), Photo Paper Plus Semi-gloss (SG-201), Photo Paper Glossy (GP-701) (for North America / Oceania), Matte Photo Paper (MP-101), T-Shirt Transfer, Envelope, Magnetic Photo Paper (MG-101) (for except China), Restickable Photo Paper (RP-101) (for except China), Greeting Card (manufactured by Avery and RedRiverPaper), Cardstock (manufactured by Neenah Paper and INKPRESS), Dark Fabric Iron on Transfers (DF-101), Light Fabric Iron on Transfers (LF-101), Premium Fine Art Rough (FA-RG1)
Cassette	Plain Paper (64 g/m2 - 105 g/m2)

PAPER SIZE

Rear Tray	A4, A5, B5, LTR, LGL, #10 Envelope, DL Envelope, Card Size (91 mm x 55 mm), 4" x 6", 5" x 7", 7" x 10", 8" x 10", Square (89 mm x 89 mm, 127 mm x 127 mm), Custom Size (width: 55 mm - 215.9 mm, length: 89 mm - 676 mm)
Cassette	A4, A5, B5, LTR, Custom Size (width: 148 mm - 215.9 mm, length: 210 mm - 297 mm)

PAPER SIZE (BORDERLESS)

	A4, B5, LTR, 4" x 6", 5" x 7", 8" x 10", Card Size (91 mm x 55 mm), Square (89 mm x 89 mm), Square (127 mm x 127 mm)
--	---

PAPER HANDLING (MAXIMUM NUMBER)

Rear Tray	<ul style="list-style-type: none"> • Plain Paper (LTR): Plain Paper (64 g/m2): 100 • Plain Paper (A4): Plain Paper: 100 • Photo Paper (4" x 6"): Photo Paper Pro Platinum (PT-101) / Photo Paper Plus Glossy II (PP-301) (for Pan-American / Oceania) / Photo Paper Plus Semi-gloss (SG-201) / Photo Paper Glossy (GP-701) (For North America / Oceania) / Matte Photo Paper (MP-101) / Restickable Photo Paper (RP-101) (for except China): 1
Cassette	<ul style="list-style-type: none"> • Plain Paper (LTR): Plain Paper (64 g/m2): 100 • Plain Paper (A4): Plain Paper (64 g/m2)

SUPPORT MEDIA FOR AUTO 2-SIDED PRINTING

Type	Plain Paper
Size	A4, A5, B5, LTR

PAPER WEIGHT

Rear Tray	Plain Paper: 64 g/m2 - 105 g/m2 , Canon paper: Max. paper weight Approx. 300 g/m2 (Photo Paper Pro Platinum (PT-101))
Cassette	Plain Paper: 64 g/m2 - 105 g/m2

SCANNER FUNCTIONS

Scanner Type	Flatbed (ADF / Platen)
Optical Resolution ⁶	1,200 dpi x 2,400 dpi
Scanning Bit Depth (Input / Output)	Grayscale: 16 bit / 8 bit Colour: RGB each 16 bit / 8 bit
Maximum Document Size	Flatbed: A4 / LTR (216 mm x 297 mm) ADF: A4 / LTR / LGL

PIXMA HOME OFFICE TR7660 | SPECIFICATIONS (CONTINUED)

COPY FUNCTIONS	
Maximum Document Size	A4 / LTR
Compatible Media	Size: A4, A5, B5, LTR, LGL, 4" x 6", 5" x 7", Card Size (91 x 55 mm), Square (127 mm x 127 mm) Type: Plain Paper, Photo Paper Pro Platinum (PT-101), Photo Paper Plus Glossy II (PP-301) (for Pan-American / Oceania), Photo Paper Pro Luster (LU-101), Photo Paper Plus Semi-gloss (SG-201), Photo Paper Glossy (GP-701) (for North America / Oceania), Matte Photo Paper (MP-101), Dark Fabric Iron on Transfers (DF-101), Light Fabric Iron on Transfers (LF-101)
Multiple Copy	Black & White / Colour: max. 99 pages
FAX FUNCTIONS	
Type	Desktop Transceiver (Super G3, Colour Communication)
Applicable Line	PSTN
Transmission Speed ^{*30}	Black & White: Approx. 3 sec Colour: Approx. 1 min
Fax Resolution	Black & White: 8 pels/mm x 3.85 lines/mm (Standard) 8 pels/mm x 7.7 lines/mm (Fine) 300 dpi x 300 dpi (Extra Fine) Colour: 200 dpi x 200 dpi
Print Size	A4, LTR, LGL
Scanning Width	A4 / LTR
Modem Speed	Max. 33.6 kbps (Automatic fall back)
Compression	Black & White: MH, MR, MMR Colour: JPEG
Gradation	Black & White: 256 levels Colour: 24 bit (RGB each 8 bit)
Automatic Dialling	Directory: Max. 100 locations Group Dialling: Max. 99 locations
Transmission / Reception Memory ^{*31}	Approx. 250 pages
PRINTING SOLUTIONS	
Available for	AirPrint / Mopria / Canon Print Service (for Android) / PIXMA Cloud Link / Canon PRINT Inkjet/SELPHY (for iOS / Android)

^{*2:} Ink droplets can be placed with a pitch of 1/4800 inch at minimum.

^{*3:} Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

^{*4:} Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers

^{*6:} Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.

^{*24:} The performance of the printer may be reduced under certain temperature and humidity conditions.

^{*25:} For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.

^{*27:} Acoustic Noise is measured based on ISO7779 standard with default setting.

^{*28:} Print: When printing ISO/JIS-SCID N2 on A4 size plain paper using default settings.
Copy: When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.

^{*30:} Black & white document fax transmission speed is based on default setting using ITU-T No.1 chart.
Colour document fax transmission speed is based on default setting using Canon Colour Fax Test Sheet.
Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.

^{*31:} Page count is based on ITU-T No.1 chart or Canon FAX Standard Chart No.1.

Canon

www.canon.com.au