

PIXMA HOME OFFICE TR4660

TECHNICAL SPECIFICATIONS



Canon

PIXMA HOME OFFICE TR4660

Compact Home Office Inkjet Printer



STYLISHLY COMPACT

Compact and stylish, the PIXMA HOME OFFICE TR4660 can copy, scan and fax multiple page documents with the 20-Sheet ADF. With high productivity and seamless wireless connectivity, it's a perfect fit for any home office.



EASY CONNECTION

Set up is made simple with guided installation via Canon Print Inkjet Selphy App available from IOS store or Google Play. Wi-Fi connectivity and the Canon PRINT app gives you control of your printer functions from your smart devices. If you're away from a Wi-Fi connection, just switch to Wireless Direct.



HIGH SPEED, HIGH QUALITY

The PIXMA HOME OFFICE TR4665 delivers crisp and clear text from the pigment black ink and print speeds of 8.8 ipm for monochrome and 4.4 ipm for colour. Auto duplex (two sided) printing saves you time, money and paper.



DOCUMENT REMOVAL REMINDER

The PIXMA HOME OFFICE TR4660 features a handy Document Removal Reminder alarm to ensure that you won't forget to remove confidential originals from the scanning platen. From faxing to copying, printing and scanning, the on printer screen and button layout is clear and simple to control.



What inks can I use with my printer?



Ink Yield
A4 document: 400
4"x6" photos: 3520



Ink Yield
A4 document: 180
4"x6" photos: 1445



Ink Yield
A4 document: 300
4"x6" photos: 90



Ink Yield
A4 document: 180
4"x6" photos: 55

Canon

PIXMA HOME OFFICE TR4660

SPECIFICATIONS

GENERAL FEATURES	
Model	PIXMA HOME OFFICE TR4660
Ink Type	2 FINE Cartridges (Black and Colour)
Maximum Print Resolution	4,800 dpi* ¹ x 1,200 dpi
Size	Approx. 435 x 295 x 189
Weight	Approx. 5.8kg
Display	Full dot LCD(Monochrome)
Paper capacity- Auto document feeder	A4 / LTR: 20, LGL: 5
Interface	USB / Wireless
Input Power	AC 100 - 240 V, 50 Hz / 60 Hz
PRINT SPEED	
Document: Colour* ²	Approx. 4.4 ipm
Document: Black & White* ²	Approx. 8.8 ipm
Photo (4" x 6")* ²	Approx. 65 sec
POWER CONSUMPTION	
OFF	Approx. 0.3 W
Standby (MFP: scanning lamp is off) USB connection to PC	Approx. 0.8 W
Standby (all ports connected, MFP: scanning lamp is off)	Approx. 1.4 W
Time to enter Standby mode	Approx. 10 min 6 sec
ENVIRONMENT	
Operating Environment* ⁵	Temperature: 5 °C - 35 °C, Humidity: 10 % RH - 90% RH (no dew condensation)
Recommended Environment * ⁶	Temperature: 15 °C - 30 °C, Humidity: 10% RH - 80% RH (no dew condensation)
Storage Environment	Temperature: 0 °C - 40 °C, Humidity: 5% RH - 95% RH (no dew condensation)
ACOUSTIC NOISE (PC PRINT)	
Quiet Mode	Available
Acoustic Noise (PC Print) Plain Paper* ⁷	Approx. 56.5 dB(A)
PRINT HEAD / INK	
Number of Nozzles	Total 1,280 nozzles (PGBK: 320 nozzles, C / M / Y: each 320 nozzles)
PRINTABLE WIDTH	
	Up to 203.2 mm (8"), Borderless: Up to 216 mm (8.5")
PRINTABLE AREA	
Borderless Printing* ³	Top / Bottom / Right / Left margin: each 0 mm
Bordered Printing	<ul style="list-style-type: none">• #10 Envelope/DL Envelope Top: 8 mm, Bottom: 12.7 mm, Right: 5.6 mm, Left: 5.6 mm• LTR/LGL Top: 3 mm, Bottom: 5 mm, Right: 6.3 mm, Left: 6.4 mm• Other Top: 3 mm, Bottom: 5 mm, Right: 3.4 mm, Left: 3.4 mm
Bordered Auto 2-Sided Printing	<ul style="list-style-type: none">• LTR Top: 3 mm, Bottom: 5 mm, Right: 6.3 mm, Left: 6.4 mm• Other Top: 5 mm, Bottom: 5 mm, Right: 3.4 mm, Left: 3.4 mm

PIXMA

HOME OFFICE TR4660

SPECIFICATIONS

(CONTINUED)

SUPPORT MEDIA	
Front Tray	Plain Paper, Photo Paper Pro Platinum (PT-101), Photo Paper Pro Luster (LU-101), Photo Paper Plus Glossy II (PP-301), Matte Photo Paper (MP-101), Photo Paper Glossy (GP-701), High Resolution Paper (HR-101N), Envelope, Photo Paper Plus Semi-gloss (SG-201), Greeting Card (manufactured by Avery and RedRiverPaper), Restickable Photo Paper(RP-101) Magnetic Photo Paper(MG-101)
Cassette	N/A
PAPER SIZE	
Front Tray	A4, A5, B5, LTR, LGL, #10 Envelope, DL Envelope, 4"x6", 5"x7", 8"x10" [Custom size] width 101.6 mm - 215.9 mm, length 152.4 mm - 676 mm
Cassette	N/A
PAPER SIZE (BORDERLESS)	
	A4, LTR, 4"x6", 5"x7", 8"x10"
PAPER HANDLING (MAXIMUM NUMBER)	
Front Tray	Plan Paper (LTR): Plain Paper (64 g/m2): 100 Canon 4x6 Photo Papers: 20 Canon 5x7 Photo Papers: 10
Cassette	N/A
SUPPORT MEDIA FOR AUTO 2-SIDED PRINTING	
Type	Plain Paper
Size	A4, LTR
PAPER WEIGHT	
Front Tray	Plain Paper: 64 g/m2 - 105 g/m2, Canon paper: max paper weight : approx. 300 g/m2 (Photo Paper Pro Platinum PT-101)
Cassette	N/A

PIXMA

HOME OFFICE TR4660

SPECIFICATIONS

(CONTINUED)

SCANNER FUNCTIONS	
Scanner Type	Flatbed (ADF / Platen)
Optical Resolution*4	600 dpi x 1200 dpi
Scanning Bit Depth (Input / Output)	Grayscale: 16 bit / 8 bit Colour: RGB each 16 bit / 8 bit
Maximum Document Size	Flatbed: A4 / LTR (216 x 297 mm) ADF: A4 / LTR / LGL
COPY FUNCTIONS	
Maximum Document Size	A4 / LTR
Compatible Media	Plain Paper(64 g/m2 - 105 g/m2), Photo Paper Pro Platinum (PT-101), Photo Paper Pro Luster (LU-101), Photo Paper Plus Semi-gloss (SG-201), Matte Photo Paper (MP-101), Photo Paper Plus Glossy II (PP-301) Photo Paper Glossy (GP-701)
Multiple Copy	Max. 99 pages
PRINTING SOLUTIONS	
Available for	AirPrint / Mopria / Canon Print Service (for Android) / PIXMA Cloud Link / Canon PRINT Inkjet/SELPHY (for iOS / Android)

*1: Ink droplets can be placed with a pitch of 1/4800 inch at minimum.

*2: Document print speeds are the averages of ESAT (Estimated Saturated Throughput) (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

*3: Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers

*4: Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.

*5: The performance of the printer may be reduced under certain temperature and humidity conditions.

*6: For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.

*7: Acoustic Noise is measured based on ISO7779 standard with default setting.

Canon

www.canon.com.au