

Data Sheet No: DS500 Version No: 004
Issue Date: 19th April 2021 Page 1

1.0 - Identification of the substance/mixture and of the company/undertaking

1.1 - Product Identification

Trade name: Whiteboard Ink WB900P, WB1500, WB500.1, Fabric Ink L3

Substance name: n/a
Index No: n/a
CAS-No: n/a
EC-No: n/a

1.2 - Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture: Preparation for use in writing instruments

Recommended restrictions on use: No information available

1.3 - Supplier: Officeworks Ltd

236-262 East Boundary Road Bentleigh East VIC 3165

Australia

Tel: 1300 633 423 **ABN:** 36 004 763 526

1.4 - Emergency telephone number

POISONS INFORMATION CENTRE 13 11 26

2.0 - Hazards Identification

2.1 - Classification of the substance or mixture

Regulation (EC) No. 1272/2008					
Hazard class	Hazard category	Target organs	Hazard statements		
Flammable liquids	2	n/a	H225		
Serious eye damage/eye irritation	2	eyes	H319		

For the full text of the H-Statements mentioned in this Section, see Section 16.

Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation.

2.2 - Label Elements

Labelling according to Regulation (EC) No. 1272/2008

Hazard Symbols:





Signal word: DANGER

Hazard statements: H225 Highly flammable liquid and vapour

H319 Causes serious eye irritation

Precautionary statements: P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment P243 Take precautionary measures against static discharge





Data Sheet No: DS500 Version No: 004
Issue Date: 19th April 2021 Page 2

P280 Wear protective gloves/protective clothing/eye protection P305/P351/P338 IF IN EYES: rinse cautiously with water for several minutes Remove contact lenses, if present and easy to do. Continue rinsing P337/P313 If eye irritation persists: get medical advice/attention P403/P235 Store in a well-ventilated place. Keep cool.

2.3 - Other hazards

No other information available.

3.0 - Composition / information on ingredients

3.1 - Substances

Chemical nature: mixture

Chemical name	REACH Reg. No.	CAS No.	EC No.	Amount (%)
Ethanol	01-2119457610-43	64-17-5	200-578-6	<75%
Propan-2-ol	01-2119457558-25	67-63-0	200-661-7	10%
2-ethylhexylether (3) phosphate		31800-88-1	n/a	<0.5%

Chemical name	Classification according to Regulation (EC) No. 1272/2008		
Ethanol	H225 (2), H319 (2)		
Propan-2-ol	H225 (2), H319 (2), H336 (3)		
2-ethylhexylether (3) phosphate	H314 (1), H318 (1)		

For the full text of the H-Statements mentioned in this Section, see Section 16.

4.0 - Description of first aid measures

4.1 - Description of first aid measures

General advice: Take off all contaminated clothing immediately

In case of inhalation: Remove to fresh air. If symptoms persist, seek medical advice. If

unconscious place in recovery position

In case of skin contact: Wash off with plenty of water. If skin irritation persists, seek medical advice In case of eye contact: Rinse thoroughly with plenty of water, also under the eyelids. Consult an eye

specialist immediately

4.2 - Most important symptoms and effects, both acute and delayed

No information available

4.3 - Indication of immediate medical attention and special treatment needed

Treat symptomatically. No further information available

5.0 - Firefighting measures

5.1 - Extinguishing media

Suitable extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide

Unsuitable extinguishing media: High volume water jet





Data Sheet No: DS500 Version No: 004
Issue Date: 19th April 2021 Page 3

5.2 - Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Highly flammable. Vapours may form explosive mixtures with air. In

case of fire hazardous decomposition products may be produced,

such as carbon monoxide (CO) and carbon dioxide (CO₂).

5.3 - Advice for firefighter

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing

apparatus. Wear appropriate body protection (full

protective suit)

Further information: Cool closed containers exposed to fire with water spray.

Heating will cause a pressure rise – with risk of bursting. Collect contaminated fire extinguishing water separately.

This must not be discharged into drains

6.0 - Accidental release measures

6.1 – Personal precautions, protective equipment and emergency procedures

Personal precautions: Use personal protective equipment. Provide adequate ventilation. Keep

away from heat and sources of ignition. Avoid contact with skin and eyes.

Do not breathe vapours.

6.2 – Environmental precautions

Environmental precautions: Do not flush into surface water or sanitary sewer system. Avoid subsoil

penetration

6.3 - Methods and materials for containment and cleaning up

Procedure: Contain spillage, and then collect with non-combustible absorbent material

(e.g. sand, earth, diatomaceous earth, vermiculite) and place in container

for disposal according to local/national regulations (see Section 13)

Further information: Treat recovered material as described in Section 13

6.4 - Reference to other sections

For personal protection see Section 8

7.0 - Handling and storage

7.1 - Precautions for safe handling

Advice on safe handling: Keep container tightly closed. Ensure adequate ventilation. Avoid contact

with skin and eyes. Do not breathe vapours. Emergency eye wash fountains and emergency showers should be available in the immediate vicinity

Hygiene measures: Keep away from food, drink and animal feeding stuffs. Smoking, eating and

drinking should be prohibited in the application area. Wash hands before breaks and at the end of the working day. Take off all contaminated clothing immediately. Avoid contact with skin and eyes. Do not breathe vapours of

spray mist





Data Sheet No: DS500 Version No: 004
Issue Date: 19th April 2021 Page 4

7.2 - Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers: Keep in an area equipped with solvent resistant flooring.

Store in original container

Advice on protection against fire and explosion: Combustible liquid. Keep away from sources of ignition – no

smoking. Take measures to prevent the build-up of electrostatic charge. Vapours may form explosive mixtures in air. Use only in an area containing explosion proof

equipment

Further information on storage conditions: Keep tightly closed in a dry and cool place. Keep in a well-

ventilated place. Keep away from heat. Keep away from

direct sunlight

Advice on common storage: Incompatible with oxidizing agents. Keep away from food,

drink and animal feeding stuffs

7.3 - Specific end uses

Specific uses(s): No information available

8.0 - Exposure controls/personal protection

8.1 - Control parameters

Ethanol (CAS No. 64-17-5)

Regulatory basis: UK. EH40 Workplace Exposure Limits (WELs)

Regulatory list: EH40 WEL

Value type: Time Weighted Average (TWA)

Value: 1000 ppm Value: 1920 mg/m^3

Propan-2-ol (CAS No. 67-63-0)

Regulatory basis: UK. EH40 Workplace Exposure Limits (WELs)

Regulatory list: EH40 WEL

Value type: Time Weighted Average (TWA)

Value: 400 ppm Value: 999 mg/m³

Regulatory basis: UK. EH40 Workplace Exposure Limits (WELs)

Regulatory list: EH40 WEL

Value type: Short Term Exposure Limit (STEL)

Value: 500 ppm Value: 1250 mg/m^3

8.2 - Exposure controls

Engineering measures: Refer to protective measures listed in Sections 7 and 8

Respiratory protection: Required, if exposure limit is exceeded (e.g. OEL). Respirator with a gas

filter. Recommended filter type: A

Hand protection: Wear suitable gloves. Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Protective gloves should

be replaced at first signs of wear





Data Sheet No: DS500 Version No: 004
Issue Date: 19th April 2021 Page 5

Butyl rubber, 0.5 mm, Fluorocarbon rubber, 0.4 mm

Eye protection: Tight fitting safety goggles
Skin and body protection: Wear suitable protective clothing

Environmental protection: Do not let product enter drains. If the product contaminates rivers and lakes

or drains inform respective authorities

9.0 - Physical and chemical properties

9.1 – Information on basic physical and chemical properties

Appearance: Various colours, liquid

Odour: Alcohol-like
Odour threshold: No data available
pH: No data available

Melting point / freezing point: -114.5°C Initial boiling point/boiling range: 78.3°C Flash point: 12°C

Evaporation rate:

Flammability:

Upper/lower flammability or explosive limits:

Vapour pressure:

Vapour density:

Relative density:

No data available

No data available

No data available

No data available

Solubility: Miscible in water, readily miscible with solvents

Partition coefficient: n-octanol/water: No data available

Auto-ignition temperature: 425°C

Decomposition temperature:

Viscosity:

Explosive properties:

Oxidising properties:

No data available

No data available

No data available

9.2 - Other information

No further information available

10.0 - Stability and reactivity

10.1 - Reactivity

Advice: Stable under recommended storage conditions

10.2 - Chemical Stability

Advice: Stable under normal conditions

10.3 - Possibility of hazardous reactions

Hazardous reactions: No information available

10.4 - Conditions to avoid

Conditions to avoid: Heat, flames and sparks





Data Sheet No: DS500 Version No: 004

Issue Date: 19th April 2021 Page 6

10.5 - Incompatible materials

Materials to avoid: Alkali metals, alkaline earth metals, strong oxidizing agents, nitric acid,

sulphuric acid, peroxides (e.g. hydrogen peroxide)

10.6 - Hazardous decomposition products

Hazardous decomposition: Under fire conditions: carbon monoxide (CO), carbon dioxide (CO₂)

11.0 - Toxicological information

11.1 - Information on toxicological effects

Ethanol (CAS No. 64-17-5)

Oral

Value type: LD50

Value: >2000 mg/Kg

Species: rat

Inhalation

Value type: LC50
Value: >20 mg/L
Exposure time: 4 h
Species: mouse

Dermal

Value type: LD50

Value: >2000 mg/Kg

Species: rabbit

Propan-2-ol (CAS No. 67-63-0)

Oral

Value type: LD50

Value: 5840 mg/Kg

Species: rat

Inhalation

Value type: LC50
Value: >25 mg/L
Exposure time: 6 h
Species: rat

Dermal

Value type: LD50

Value: >13900 mg/Kg

Species: rabbit

12.0 - Ecological information

12.1 - Toxicity

Ethanol (CAS No 64-17-5)

Fish

Species: Pimephales Promelas (Fathead Minnow)





Data Sheet No: DS500 Version No: 004

Issue Date: 19th April 2021 Page 7

Value type: LC50
Value: 15300 mg/L
Exposure time: 96 h

Daphnia and other aquatic invertebrates

Species: daphnia magna

Value type: EC50
Value: 12340 mg/L
Exposure time: 48 h

Algae

Species: Chlorella vulgaris (Fresh water algae)

Value type: EC50
Value: 275 mg/L
Exposure time: 72 h

Bacteria

Species: Paramaecium caudatum

Value type: EC50
Value: 5800 mg/L

Exposure time: 4 h

Propan-2-ol (CAS No 67-63-0)

Fish

Species: Pimephales promelas (fathead minnow)

Value type: LC50
Value: 9640 mg/L
Exposure time: 96 h
Daphnia and other aquatic invertebrates

Species: daphnia magna

Value type: EC50
Value: 9714 mg/L
Exposure time: 24 h

Algae

Species: Scenedesmus subspicatus

Value type: EC50
Value: >100 mg/L
Exposure time: 72 h

Bacteria

Value type: EC50

Value: >100 mg/L, no harming action

12.2 - Persistence and biodegradability

No data available

12.3 - Bioaccumulative potential

No data available

12.4 - Mobility in soil

Mobile in water environment



Data Sheet No: DS500 Version No: 004
Issue Date: 19th April 2021 Page 8

12.5 - Results of PBT and vPvB assessment

No data available

12.6 - Other adverse effects

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

13.0 – Disposal considerations

13.1 - Waste treatment methods

Product: Disposal together with normal waste is not allowed. Special disposal

required according to local regulations. Do not empty into drains. Contact

waste disposal services

Contaminated packaging: Empty contaminated packaging thoroughly. They can be recycled after

thorough and proper cleaning. Packaging that cannot be cleaned is to be disposed of in the same manner as the product. Do not burn, or use a

cutting torch on the empty drum. Risk of explosion

14.0 - Transport Information

14.1 - UN Number

1993

14.2 - UN proper shipping name

ADR: Flammable Liquid n.o.s (contains ethanol)
RID: Flammable Liquid n.o.s (contains ethanol)
IMDG: Flammable Liquid n.o.s (contains ethanol)
IATA-DGR: Flammable Liquid n.o.s (contains ethanol)

14.3 - Transport hazardous class(es)

Labels/classification code/ hazard identification number /tunnel restriction code

ADR: 3; F1; 33: (D/E)
RID: 3; F1; 33
IMDG: 3; (F-E, S-E)

IATA-DGR: 3

14.4 - Packing group

ADR: II
RID: II
IMDG: II
IATA-DGR: II

14.5 - Environmental hazards

Labelling according to 5.2.1.8 ADR:

Labelling according to 5.2.1.8 RID:

No
Labelling according to 5.2.1.6.3 IMDG:

No
Classification as environmentally hazardous according to 2.9.3 IMDG:

No
Classified as 'P' according to 2.10 IMDG:

No





Data Sheet No: DS500 Version No: 004
Issue Date: 19th April 2021 Page 9

14.6 - Special precautions for user

Not applicable

14.7 - Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IMDG: Not applicable

15.0 - Regulatory Information

15.1 – Safety, health and environmental regulations/legislation specific for the substance or mixture

All components are REACh registered or are exempt from REACh registration
Our inks do not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57)
All components are listed on TSCA list of active substances

15.2 - Chemical safety assessment

No information available

16.0 - Other Information

16.1 - Full text of H-Statements referred to under Sections 2 and 3

H225: Highly flammable liquid and vapour

H314: Causes severe skin burns and eye damage

H318: Causes serious eye damage H319: Causes serious eye irritation

H336: May cause drowsiness or dizziness

16.2 - Further information

Other: The information provided in this safety data sheet is correct to our

knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements and is not to be considered

as a warranty or quality specification and does not constitute a legal

relationship. The information contained in this safety data sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless

specified in the text

HS Tariff code: 32159070