

72 -VOLT AC ELECTRIC

13.3-HP GAS ENGINE WITH CLOSED LOOP EFI

CONVERTIBLE REAR SEAT

EXPRESS™ S4





SAY GOODBYE TO ORDINARY.

Every hour is an opportunity to live your life to the fullest, and the E-Z-GO® Express S4 ensures you're doing just that. The Express S4 has a rear seat that converts to a cargo deck, allowing you to host or haul more. Choose from E–Z–GO's exclusive 72–volt AC powertrain that offers you unrivaled enjoyment and power, or an energy efficient 13.5 hp closed-loop EFI gas powertrain. No matter what you choose, you'll always stand out of the crowd with the Express S4.

KEY FEATURES

- · 23-in Desert Eagle Tires
- · Front Brush Guard
- · Fold-Down Cargo Deck
- Headlights, Taillights and Brake Lights
- · Dual USB Ports
- Horn
- Cupholders
- · Dashboard Storage Pockets
- · Premium Steering Wheel
- State of Charge Meter (Electric Only)
- DC/DC Converter (Electric Only)
- 72-Volt Battery Charger (Electric Only)
- Fuel Gauge (Gas Only)
- · Low Oil Indicator (Gas Only)

ELECTRIC

GAS

DIMENSIONS		
OVERALL LENGTH	118 in. (300 cm)	
OVERALL WIDTH	48.5 in (123 cm)	
OVERALL HEIGHT (W/O ROOF)	52.5 in (133 cm)	
OVERALL HEIGHT (W/ ROOF)	82 in (208 cm)	
WHEEL BASE	65.5 in (166 cm)	
FRONT WHEEL TRACK	38.0 in (97 cm)	
REAR WHEEL TRACK	38.5 in (98 cm)	
GROUND CLEARANCE @ DIFFERENTIAL	7 in (18 cm)	

POWER		
POWER SOURCE	72 Volts AC	4 Cycle 24.5 cu in (401 cc)
VALVE TRAIN	N/A	Single Cylinder OHV
MOTOR TYPE	AC Induction	N/A
FUEL SYSTEM	N/A	Closed-Loop Electronic Fuel Injection
HORSEPOWER (KW)	22.4 hp (16.7 kW) Peak	13.5 hp (10.1 kW) Exceeds SAE J1940 Std
ELECTRICAL SYSTEM	72 Volt	Starter/Generator - Solid State Regulator
BATTERIES (QTY/TYPE)	Six, 12 Volt Deep Cycle	One, 12 Volt Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) Tank
BATTERY CHARGER	72 VDC Delta Q, 120/230 VAC, UL & CSA	N/A
SPEED CONTROLLER	350 Amp AC	N/A
DRIVETRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse	
REAR AXLE RATIO	17:1	11.47:1 (Forward); 14.35:1 (Reverse)

PERFORMANCE

SEATING CAPACITY	4-Pas	senger
DRY WEIGHT	968 lb (439kg)	870 lb (395 kg)
CURB WEIGHT	1460 lb (662kg) Trojan T-1275	910 lb (413 kg)
VEHICLE LOAD CAPACITY	800 lb ((360 kg)
OUTSIDE CLEARANCE CIRCLE	19 ft. (!	5.8 m)
SPEED (LEVEL GROUND)	19.5 mph ± 0.5 mph (31.4 kph ± 0.8 kph)	17.0 mph ± 0.5 mph (27.4 kph ± 0.8 kph)

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single Point Engagement
TIRES	Desert Eagle 23 x 10 - 14 on Alloy Wheel

BODY & CHASSIS

FRAME	Welded Steel with Powder-Coat Protection
BODY & FINISH	Injection Molded TPO
AVAILABLE BODY COLORS	Almond, Black, Electric Blue, Flame Red, Inferno Red, Metallic Charcoal, Ocean Grey, Platinum, White
AVAILABLE SEAT COLORS	Gray, Oyster, Tan, Black

















Platinum







www.ezgo.com

