

GUARDIT DENSE ALL STONE SEALER

GuardIt® Dense All Stone Sealer is the most effective water-based product available because of the unique benefits offered with regard to penetration and durability and does not change the substrates appearance. It's invisible upon application and maintains the natural look, feel and texture of the stone. It provides years of supreme protection!

Application

There are two applications applicable for the Dense Substrates, one is polished surfaces and the other is for honed or unpolished surfaces.

Polished Surfaces

1. Ensure surface is clean, remove all cement residue, dirt, oil, mould and grime.
2. Apply an even wet first coat using a Lamb's wool applicator or pump spray unit over the surface, coverage rate 10-12 M2 per litre.
3. When first coat is almost dry apply the second coat, apply second coat using a Lamb's wool applicator or pump spray unit, coverage rate 15-18 M2
4. On polished surfaces buff off excess material when almost dry using a polishing machine with a white pad.
5. Do not walk on surface for 3-4 hours; full cure is 14 days, but product functioning after 24 hours.

Honed Or Unpolished Surfaces

1. Ensure surface is clean, remove all cement residue, dirt, oil, mould and grime, using GuardIt Green Acid.
2. Apply an even wet first coat using a low pressure pump spray or Lamb's wool applicator unit over the surface, coverage rate 10-12 M2 per litre.
3. When first coat is almost dry apply the second coat, apply second coat using a low pressure pump spray or Lamb's wool applicator coverage rate 15-18 M2
4. On polished surfaces buff off excess material when almost dry using a polishing machine with a white pad.
5. Do not walk on surface for 3-4 hours; full cure is 14 days, but product functioning after 24 hours.