



2LRF704

APPLICATIONS

- Meat industry
- Bakeries
- Biscuit Industry
- Potato/Chips Production
- Dairy Industry
- Canning Industry

CONSTRUCTION

2 ply polyester fabric. With great width stability

Top Surface: 0.4mm white PVC, shore hardness 65. Oil and grease resistant.

Bottom Surface: Very low friction fabric.

CHARACTERISTICS

- Odourless and taste free
- Good resistance to oils and fats
- Good resistance to acids and salts except when highly concentrated
- Resistant to many solvents
- FDA, 2002/72/EC

TECHNICAL DATA

| | | | | |
|----------------------|------------------------------------|------|----------------------|------|
| Thickness: | 2.0mm | | | |
| Weight: | 2.4kg/m ² | | | |
| Max width: | 2000mm | | | |
| Min Pulley: | Flexing: | 25mm | Back Flexing: | 50mm |
| Joining: | Finger joint, overlap or fasteners | | | |
| Belt Support: | Sliding bed and Rollers: flat | | | |
| Work Load: | 8N/mm will result in 1% elongation | | | |
| Temp: | -10°C to +100°C | | | |

The above information is applicable at 15°C. To allow for ongoing product developments this data is subject to alterations without prior notice. This information replaces that included in previous publications.