

Phone: 03 9794 8870 Fax: 03 9794 7708

Email: belts@ammeraal.com.au

AMMERAAL AMRA 30 55 Shore D Polyester

APPLICATIONS

- Use in high contamination environments
- Cheese, milk, meat and poultry industries
- Wet applications where cleaning is required: fruit, vegetables, flower growers and handlers

CONSTRUCTION

Homogeneous 55 Shore D, synthetic material. Meets FDA Requirements. USDA Approved

Top surface: gloss **Bottom surface:** satin

CHARACTERISTICS

- Ammeraal Amra 30 is available in either Blue or Ivory
- Highly sanitary, non-porous
- 100% non-fraying
- Low stretch, low noise and easy to clean with water up to 100°C
- Meets F.D.A requirements for contact with dry & bulk foods (Regulation No.21CFR 177-1590) and fatty & wet foods (Regulation No.CFR 177-2600)
- No foreign matter is included in formulation

TECHNICAL DATA

Thickness: 3.0mm

Weight: 3.5kg/m2

Max width: 1300mm

Min Pulley: 105mm (180° wrap) 80mm (120° wrap)

Joining: Mirror welded, welding rod, fasteners

Belt Support: UHMWPE deck or rollers

Work Load: 3.6N/mm will result in 1% elongation

Temp: Operating: -20°C to +70°C Cleaning: +100°C

The above information is applicable at 15° C. To allow for ongoing product developments this data is subject to alterations without prior notice. This information replaces that included in previous publications.