

AMMERAAL AMRA 30DE 55 Shore D Polyester

APPLICATIONS

- Use in high contamination environments.
- Cheese, milk, meat and poultry industries
- Wet applications where cleaning is required: fruit, vegetables, flower growers and handlers

CONSTRUCTION

Homogeneous 55 Shore D, synthetic material. Meets FDA requirements. USDA approved

Top surface: gloss

Bottom surface: low friction, diamond profile

CHARACTERISTICS

- Ammeraal Amra 30 DE available in either Blue or Ivory
- Highly sanitary, non-porous.
- 100% non-fraying
- Easy to join using low cost equipment.
- Meets F.D.A requirements for contact with dry & bulk foods (regulation No.21CFR 177-1590) and fatty & wet foods (Regulation No.CFR 177-2600)
- No foreign matter is included in formulation.
- Odour and taste free, has excellent resistance to oil, fats and is UV stable

TECHNICAL DATA

| | |
|----------------------|--|
| Thickness: | 3.0mm |
| Weight: | 3.5kg/m ² |
| Max width: | 1300mm |
| Min Pulley: | 105mm (180° wrap) 80mm (120° wrap) |
| Joining: | Mirror Welded, welding rod, fasteners |
| Belt Support: | UHMWPE deck or Rollers |
| Work Load: | 3.4N/mm will result in 1% elongation |
| Temp: | Operating: -20°C to +70°C Cleaning: +100°C |

The above information is applicable at 15°C. To allow for ongoing product developments this data is subject to alterations without prior notice. This information replaces that included in previous publications.