


# Container Dimensions

	20' Dry Cargo Container		40 ' Dry Cargo Container	
	8'6" STANDARD		8 '6" STANDARD	
SPECIFICATIONS:				
Inside Cubic Capacity	32.8 cu.m (1,158 cu.ft )		67.2 cu.m (2,372 cu.ft )	
Cargo Capacity	21,640 kg (47,716 Ibs.)		26 ,500 kg (58,433 Ibs. )	
Tare weight	2,360 kg (5,204 Ibs.)		3 ,980 kg (8,776 Ibs. )	
	OUTSIDE:	INSIDE:	OUTSIDE:	INSIDE:
Length	6.05 m (19.84 ft)	5.90 m (19.35 ft)	12.19 m (40.00 ft)	12.01 m (39.39 ft)
Width	2.44m (8.00 ft)	2.35m (7.71 ft)	2.44m (8.00 ft)	2.35 m (7.71 ft )
Height	2.59m (8.50 ft)	2.38m (7.80 ft)	2.59m (8.50 ft)	2.38 m ( 7.80 ft )
DOOR SIZE:				
Height	2.28m (7.48 ft)		2.28m(7.48 ft)	
Width	2.33m (7.64 ft)		2.33m(7.64 ft)	
				

**40 ' Dry Cargo Super / Hi-Cube Container**



<b>9 '6" SUPER HI-CUBE</b>		
SPECIFICATIONS:		
Inside Cubic Capacity	75.9 cu.m (2,679 cu.ft )	
Cargo Capacity	26 ,330 kg (58,058 Ibs. )	
Tare weight	4 ,150 kg (9,150 Ibs. )	
	<b>OUTSIDE:</b>	<b>INSIDE:</b>
Length	21.19m (19.84 ft)	12.01m (39.39 ft)
Width	2.44m (8.00 ft)	2.35 m (7.71 ft )
Height	2.90m (9.50 ft)	2.69 m (8.82 ft )
<b>DOOR SIZE:</b>		
Height	2.58m (8.46 ft)	
Width	2.35m (7.71 ft)	

<b>20 ' Reefer Containers ( FINSAM )</b>		
	<b>MODEL 2107</b>	<b>MODEL 2061/2084</b>
SPECIFICATIONS:		
WEIGHTS:		
Max. Gross Weight	24,000 kg	22 ,860 kg


Net Tare Weight	3,230 kg	3 ,800 kg
Payload	20,770 kg	19 ,060 kg
<b>DIMENSIONS:</b>	<b>INSIDE:</b>	<b>INSIDE:</b>
Length	5,485 mm	5 ,170 mm
Width	2,250 mm	2 ,235 mm
Height	2,260 mm	2 ,250 mm
<b>DOOR OPENING:</b>		
Width	2,230 mm	2 ,235 mm
Height	2,220 mm	2 ,215 mm
<b>VOLUMES:</b>		
Capacity	<sup>3</sup> 27.9m (985 cu.ft)	<sup>3</sup> 26.0m (918 cu.ft)



<b>20 ' BIN</b>	
<b>SPECIFICATIONS:</b>	
Cargo Capacity	21 ,960 kg (48,421lbs. )
Max. Gross Weight	2 ,040 kg (4,498 lbs. )
	<b>OUTSIDE:</b>



Length	6.06 m (19.88 ft )
Width	2.44 m (8.00 ft )
Height	1.30 m (4.25 ft )

	<b>20' Bolster (PLATFORM)</b>	<b>40 ' Bolster (PLATFORM )</b>
SPECIFICATIONS:		
Cargo Capacity	23,460 kg (51,729 Ibs.)	26 ,260 kg (57,903 Ibs. )
Tare Weight	1,940 kg (4,2777 Ibs.)	4 ,220 kg (9,305 Ibs. )
Length (overall)	6.06 m (19.88 ft)	12.19 m (40.00 ft )
Width	2.44 m (8.00 ft)	2.44 m (8.00 ft )
Height	0.23 m (0.66 ft)	0.65 m (2.13 ft )
		

	<b>20' FLATRACK</b>	<b>40 ' FLATRACK</b>
SPECIFICATIONS:		

Cargo Capacity	approx 20,015 kg (44,133 lbs.)		approx 30,476 kg (67,200 lbs.)	
Tare weight	up to 3,100 kg (6,835 lbs.)		approx 5,646 kg (12,450 lbs.)	
	OUTSIDE:	INSIDE:	OUTSIDE:	INSIDE:
Length	6.06m (19.88 ft)	5.85 m (19.19 ft)	12.19m (40.00 ft)	12.05 m (39.52 ft)
Width	2.44m (8.00 ft)	2.23m (7.31 ft)	2.44m (8.00 ft)	2.12 m (6.95 ft )
Height	2.44m (8.00 ft)	2.15m (7.04 ft)	2.44m (8.00 ft)	1.96 m (6.43 ft )
	or 2.59 m (8.50 ft )		or 2.59 m (8.50 ft )	



	<b>20 ' OPEN TOP CONTAINER</b>		<b>40 ' OPEN TOP CONTAINER</b>	
	8'6" STANDARD		8 '6" STANDARD	
SPECIFICATIONS:	8'6" STANDARD		8 '6" STANDARD	
Inside Cubic Capacity	32.6 cu.m (1,151 cu.ft )		66.7 cu.m (2,355 cu.ft )	
Cargo Capacity	21,700 kg (47,839 lbs.)		26 ,530 kg (58,490 lbs. )	
Tare weight	2,300 kg (5,071 lbs.)		3 ,950 kg (8,710 lbs. )	
	OUTSIDE:	INSIDE:	OUTSIDE:	INSIDE:
Length	6.06m (19.88 ft)	5.88m (19.29 ft)	12.19 m (40.00 ft)	12.01 m (39.39 ft)
Width	2.44m (8.00 ft)	2.33m (7.64 ft)	2.44m (8.00 ft)	2.33 m (7.64 ft )
Height	2.59m (8.50 ft)	2.31m (7.58 ft)	2.59m (8.50 ft)	2.31 m (7.58 ft )
DOOR SIZE:				
Height	2.28m (7.48 ft)		2.28m (7.48 ft)	

Width	2.33m (7.64 ft)		2.33m (7.64 ft)	
-------	-----------------	--	-----------------	--

