



Russell Heale Engineering Pty Ltd  
 26 Hutchinson Street Burleigh  
 Heads QLD 4220 Phone:  
 (07) 5593 7755 Fax: (07) 5593 7744  
 A.B.N. 16 163 606 370  
 A.C.N. 010 209 677

**ATM, TARE AND MAX LOAD INFORMATION FOR TRAILERS**

		127mm Bartlett Ball/ 8 Ball	Flying Saucer	Pintle Hook
Single Axle 8.5 tonne axle group	ATM	13.3	18.5	17.5
	Approx TARE	4.5	4.5	4.5
	Theoretical Max Load- up to	8.8	14	11
	SVL	4.807	12	8.5
Tandem Axle 16.5 tonne axle group	ATM	19.8	28.5	25.5
	Approx TARE	6.020	6.020	6.020
	Theoretical Max Load- up to	12	18.5	16.5
Tri Axle 20 tonne axle group *	ATM	22.1	32	29
	Approx TARE	7.475	7.475	7.475
	Theoretical Max Load- up to	14	23	20
	SVL	2.615	12	9

Notes: The maximum load is also dependant on the rating and capability of the truck and the tare weight of the truck. The deciding factor is usually the axle loadings. We usually suggest that 2 tonne is taken off the maximum load of tandem and tri axle trailers to allow for practical loading situations.

\*Please note:

- Tri-axle trailers with pull out outriggers are slightly heavier by about 600kg.
- Bi-fold ramps add 715kg.

**ATM- Aggregate Trailer Mass**  
**Tare- Unladen mass of trailer**  
**SVL- Static Vertical Load**

Call us today on 1300 55 93 75 for friendly, expert advice on your trailer requirements