

Statement of Approval



Approval No. **WP 1340011 HH**

The material described below complies with the applicable requirements as given in the Rules and Regulations of Germanischer Lloyd. On this basis the material is

approved as **Elastomeric Adhesive**

for the construction of components provided that the recommendations for use as specified by the producer are observed.


Type	Fix15
Description	One Component MS-Polymer
Producer	FIXTECH PO Box 568 Southport, Queensland, 4215 Australia
Normative Reference	Rules for Classification and Construction, II - Material and Welding Technology Part 2 Non-Metallic Materials

This document consists of this page and a one-page annex which is integral part of the approval.

This Statement of Approval is valid until 2017-06-20.

Hamburg, 2013-06-21

Germanischer Lloyd


Stefan Röhr


Guido Michalek

Statement of Approval



ANNEX

Approval No. WP 1340011 HH

Date: 2013-06-21

Page 1 of 1

Reference Documents Technical specifications deposited at Germanischer Lloyd Head Office.

Assessed Documents - Technical Data Sheet
- Test Report No. 12/7292/01 issued by Kiwa MPA Bautest GmbH, NL Berlin

Fields of Application Joining of components on condition that the adhesive material is compatible to the base materials and the applicable requirements of the Germanischer Lloyd are met.

Approved as class B adhesive for bonding of e.g. single-pane polymer glass and windbreakers.

Confirmed Values	Standard	Value
Shore A	DIN 53505	50
Fracture Strain at -20°C	DIN 53504	275 %
Tensile Strength at 60°C	DIN 53504	2,4 Mpa
Resistance to Tear Propagation	DIN 53515	5,4 N/mm
Tensile Lap Shear Strength 23°C / 50% humidity	in acc. to DIN EN 1465	1,4 Mpa
Tensile Lap Shear Strength 60°C	in acc. to DIN EN 1465	0,15 Mpa
Creep Test after 90 days Conditioning	in acc. to DIN EN 1465 and DIN 50017	30 %

Limitations Any significant changes in design and/or quality of the material will render the approval invalid.

End of Annex

Germanischer Lloyd 