

# SAFETY DATA SHEET

## Fixseal 1060 - Part A

### 1. Identification

#### 1.1 Identification of the substance or preparation:

Product Name: Fixseal 1060 - Part A  
Description: Epoxy resin in flammable solvent

#### 1.2 Use of substance or preparation:

Sealing and Priming

#### 1.3 Company undertaking identification:

Fixtech Pty Ltd – Fixtech Marine Solutions  
1/20 Export Drive  
Molendinar, Queensland 4214  
Tel. : +61 7 5530 1099  
Fax : +61 7 5530 1322  
Email: [info@fixtech.com.au](mailto:info@fixtech.com.au)

#### 1.4 Emergency telephone:

+61 7 5530 1099

### 2. Composition/information on ingredients

Hazardous Ingredients	CAS No.	R-phrases	Conc. In %
Xylene	1330-20-7	R20-R21-R38	40- 60%
Epoxy resin	25068-38-6	R36/38-R43-R51/533	30- 50%
PGMME	107-98-2	R10	<10%
Non-hazardous ingredients or those not affecting classification			to 100%

### 3. Hazardous identification

#### Classification:

Flam.Liq 3                      H226: Flammable liquid and vapour.  
ASP.1                            H304: May be fatal if swallowed and enters airways.  
Skin Corr. 2                    H315: Causes skin irritation.

# SAFETY DATA SHEET

## Fixseal 1060 - Part A

Eye Dam.2A	H319: Causes serious eye irritation
STOT.3	H335: May cause respiratory irritation.
STOT.2	H373: May cause damage to organs through prolonged or repeated exposure.

### Label elements

#### GHS label elements

The substance is classified and labelled according to the Globally Harmonised System (GHS)



Signal Word **DANGER**

GHS07

GHS02

GHS08

#### Hazard Statements:

Flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure

#### Prevention and response statements:

**P210:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
**P243:** Take actions to prevent static discharges.  
**P260:** Do not breathe dust/fume/gas/mist/vapours/spray.  
**P280:** Wear protective gloves/protective clothing/eye protection/face protection.  
**P303+P361+P353:** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
**P301+P310:** IF SWALLOWED: Immediately call a POISON CENTER/doctor/ P331: Do NOT induce vomiting.

#### 4. First aid measures

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

# SAFETY DATA SHEET

## Fixseal 1060 - Part A

### After inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

### Skin contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

### Eye contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

### After ingestion:

#### Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

#### Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

## 5. Fire fighting measures

### Suitable Extinguishing Media:

Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used.

### Hazchem or Emergency Action Code: · 3[Y]

### Specific hazards arising from the substance or mixture:

Flammable liquid. On burning will emit toxic fumes, including those of oxides of carbon.

**Special protective equipment and precautions for fire-fighters:** Keep containers cool with water spray. If safe to do so, remove containers from path of fire. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

# SAFETY DATA SHEET

## Fixseal 1060 - Part A

### 6. Accidental release measures

#### Emergency procedures/Environmental precautions:

If contamination of sewers or waterways has occurred advise local emergency services.

#### Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

### 7. Handling and storage

#### Precautions for safe handling:

Keep out of reach of children. Avoid skin and eye contact and breathing in vapour, mists and aerosols. May form flammable vapour mixtures with air. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc.) must be eliminated both in and near the work area. Do NOT smoke. Vapour may travel a considerable distance to source of ignition and flash back.

#### Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Store away from foodstuffs. Keep containers closed when not in use - check regularly for leaks.

### 8. Exposure controls/personal protection

**Control Parameters:** No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Xylene (o-, m-, p- isomers): 8hr TWA = 350 mg/m<sup>3</sup> (80 ppm), 15 min STEL = 655 mg/m<sup>3</sup> (150 ppm)

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

# SAFETY DATA SHEET

## Fixseal 1060 - Part A

**TWA** - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

**STEL (Short Term Exposure Limit)** - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

### Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

### Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: H - OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.



Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator or air supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

## 9. Physical and Chemical Properties

**Appearance:** Clear Liquid

**Odour:** Xylene solvent

**Percent Volatile:** 75% - 80%

**Specific Gravity:** 0.9 -1.0

# SAFETY DATA SHEET

## Fixseal 1060 - Part A

**pH:** Not Determined

**Vapour Pressure:** Not Determined

**Vapour Density:** Not Determined

**Auto Ignition:** Not Determined

**Flammability Limits:** N/A

**Boiling Point:** Not Determined

**Flash Point:** > 23 Deg C PMCC

**Solubility /miscibility with water** None

Note: the above information is not intended for use in preparing product specifications

### 10. Stability and reactivity

**Reactivity:**

**Chemical stability:**

**Possibility of hazardous reactions:**

**Conditions to avoid:**

**Incompatible materials:**

**Hazardous decomposition products:**

No information available

Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Hazardous polymerisation will not occur.

Avoid exposure to heat, sources of ignition, and open flame.

Incompatible with oxidising agents and epoxy resins

Oxides of carbon.

### 11. Toxicological information

### 12. Effects on the environment

**Eco toxicity:** Avoid contaminating waterways

**Aquatic toxicity:** Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment

### 13. Disposal considerations

**Disposal methods:**

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Advise flammable nature. Normally suitable for incineration by an approved agent.

Fixtech Pty Ltd – PO Box 568, Southport, QLD  
PH: +61 (0) 7 5530 1099, Fax: +61 (0) 7 5530 1322  
Email: [info@fixtech.com.au](mailto:info@fixtech.com.au)

# SAFETY DATA SHEET

## Fixseal 1060 - Part A

### 14. Transport information

Labels required:



**Proper Shipping Name:** Paint  
**Hazard Class:** 3  
**ID Number:** UN 1263

**Hazchem Code:** 3[Y]  
**Packing Group:** III

### 15. Regulatory information

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations

### 16. Other information

#### Acronyms

**AICS:** Australian Inventory of Chemical Substances  
**CAS Number:** Chemical Abstracts Service Number  
**Hazchem Code:** Emergency action code that provides information to emergency services.  
**UN Number:** United Nations Number  
**R36/38** Irritating to eyes and skin  
**R43** May cause sensitisation by skin contact  
**R51** Toxic to aquatic organisms  
**R53** May cause long-term adverse effects in the aquatic environment

#### **Important Note:**

**This data completes the technical datasheet for use, but does not replace it. The data given here is based on current knowledge and experience. The purpose of this safety data sheet is to describe the products in terms of their safety requirements. Data quoted is typical for the product, but does not constitute a specification, and is based on the most accurate information available to Fixtech P/L at the time of writing. All information contained herein is given in good faith, but is subject to change without notice. The data does not signify any warranty with regards to the products properties**