



# ZODIAC

## Nature<sup>2</sup> The Natural Spa Purifier



Natural Mineral Purifiers  
for Pools and Spas

### Owner's Manual

**IMPORTANT:** Spa Owner, save this manual.  
Installer, leave this manual with the spa owner.

#### Safety Instructions Important Information

Please read prior to installation.

Nature<sup>2</sup> The Natural Spa Purifier (hereafter referred to as Nature<sup>2</sup> Spa) has been designed to sanitize spas up to 2000 litres.



#### ATTENTION

Failure to heed the following can result in permanent injury or drowning.

#### EQUIPMENT UNDER PRESSURE

- Always turn spa off prior to installing or changing Nature<sup>2</sup> Spa. Your spa system is operated under pressure and the pressure must be released before you begin work. Please see your spa owner's manual for further instructions.

#### PREVENT CHILD DROWNING

- Do not let anyone, especially small children, sit, step, lean or climb on any equipment installed as part of your spa's operational system.

#### LOW CHLORINE RECIPE

- You must strictly follow the Nature<sup>2</sup> Spa recipe included in this manual to maintain proper water chemistry and avoid health hazards. Failure to follow these instructions can lead to sickness from bacteria and other noxious organisms.



#### CAUTION

#### PRECAUTIONARY STATEMENT HAZARDS TO HUMANS AND ANIMALS

#### CAUTION:

In the unlikely event that a cartridge breaks, mineral media should not be ingested by humans or animals as it may cause gastric distress.

**FIRST AID IF INGESTED:** Call poison control center or doctor immediately for treatment advice.

The Nature<sup>2</sup> Spa is designed only for residential spas.

Thank you for purchasing Nature<sup>2</sup> Spa. Please take a few moments to review the material in this manual. We believe the more you know, the more enjoyable your bathing experience will be and the more you will reduce the time, effort and cost of maintaining your spa. While every spa has its own characteristics of water type, amount of sunlight, etc. the recipe included in this manual will help ensure good water quality in any spa. If you have questions, your Nature<sup>2</sup> Spa dealer can provide professional advice and service.

<b>Contents</b>	<b>Page</b>
Safety Instructions .....	1
Start-Up .....	3
Balance the Water .....	3
Install the Nature <sup>2</sup> Spa .....	4
Recipe .....	6
Provide Filtration/Circulation .....	8
Nature <sup>2</sup> Spa Replacement Intervals .....	8
Disposal .....	8
Limited Warranty .....	9
Troubleshooting .....	10
Nature <sup>2</sup> Spa Test Strips .....	12

## **Directions for Use**

NOT TO BE USED FOR ANY PURPOSE, OR IN ANY MANNER, CONTRARY TO THIS LABEL UNLESS AUTHORISED UNDER APPROPRIATE LEGISLATION.

## **Nature<sup>2</sup> Spa Compatibility**

**Attention:** Not to be used with product containing biguanides. If these products are being used, be sure to drain and refill the spa with fresh water.

## Start-Up

Before using a new Nature<sup>2</sup> Spa, clean debris and algae out of the spa and spa equipment.

**Important: Do not install the new Nature<sup>2</sup> Spa until the spa water is clean and chemically balanced.**

Balance spa water before installing Nature<sup>2</sup> Spa.

- pH 7.2-7.6
- Calcium Hardness 200-400 ppm
- Total Alkalinity 80-120 ppm
- Total Dissolved Solids (TDS) 300-2000 ppm

Consult your Nature<sup>2</sup> dealer for water balance instructions.

## Balance the Water

To find out if your spa water is balanced:

- take a water sample to your dealer to be tested, or
- ask your dealer to recommend a spa test kit for water balance.

### Element: pH

Range: 7.2-7.6

If too low: The surface of your spa can become etched. Metal parts in the pump and plumbing will corrode.

How to fix: Add pH increaser.

If too high: "Scale" forms on the surface of your spa. The water can become cloudy. Equipment can be damaged.

How to fix: Add pH decreaser.

### Element: Calcium Hardness

Range: 200-400 ppm

If too low: Metal parts in the pump and plumbing will corrode.

How to fix: Add calcium chloride and hardness increaser.

If too high: Rough, discolored deposits ("scale") will form on the spa surface and inside spa equipment.

How to fix: Drain or dilute the spa water. Consult your dealer.

### Element: Total Alkalinity

Range: 80-120 ppm

If too low: It provides no buffer so that you constantly get fluctuating pH readings, which can damage equipment and spa surfaces.

How to fix: Use an alkalinity increaser.

If too high: The water becomes cloudy or milky white.

How to fix: Add acid to bring alkalinity down.

# Install the Nature<sup>2</sup> Spa

The Nature<sup>2</sup> Spa is designed to fit most spas.


**Zodiac assumes no liabilities for the product if installed in any way other than the methods described in this manual.**

- 1 Drain and refill your spa. Balance the water per spa manufacturer guidelines.
- 2 Install the Nature<sup>2</sup> Spa after water is balanced. Refer to Assembly and Installation Diagrams below for instructions regarding your particular model's installation.
- 3 Superoxidize the spa water with an approved source of chlorine according to manufacturer's instructions to burn off contaminants and activate cartridge. **Important: Initial superoxidation with dichlor\* is required to burn off contaminants and activate cartridge.**
  - Add 1.5 tablespoons of dichlor\* to spa per 1000 litres. Note: 1.5 tablespoons is approximately 24 grams.
  - Do not enter the spa if the free available chlorine residual is over 5 ppm.
- 4 Run spa according to recommendations supplied to you by the manufacturer of your spa.

## Assembly and Installation Diagrams

The Nature<sup>2</sup> Spa comes in three parts; the main body (A) and two support stems (B, and C).

- 1 Connect the support stems together and press onto main body to create a single device as shown.



2. Slide the entire device into the core of your existing spa filter cartridge. See examples below.

**Open Top:** Slide unit in from the top. Position near the top half of the cartridge. (Support stems may be cut to position the cartridge correctly.)

**Open Top with Stand Pipe:** Some spa filter systems are configured with a standpipe running the length of the filter core. Simply slide unit in from the top. Position near the top half of the cartridge for easy retrieval.


**Closed Top:** Slide unit in from the bottom. Position unit to rest on shelf inside filter core.

---


**When installed, the Nature<sup>2</sup> Spa must be at least 2.5 cm above the bottom of the filter to prevent blocking water flow.**

---


**Open Top  
correct**




**Open Top  
wrong**



**Closed  
Top**



**Open Top  
with Stand Pipe**



# Operation and Maintenance

There is one recipe for maintaining clean, clear, sanitized water with minimum time and effort. This recipe provides the easiest and most economical way to care for your Nature<sup>2</sup> Spa.

## Low-Chlorine Recipe

Ingredients:

- Nature<sup>2</sup> Spa
- Non-chlorine oxidizer (MPS<sup>^</sup>)
- Nature<sup>2</sup> Spa Test Strips<sup>~</sup>, or equivalent (MPS<sup>^</sup>, pH, and total alkalinity)
- pH, hardness and total alkalinity adjusting chemicals
- Dichlor<sup>\*</sup>

**When:    What to do:**

---

<b>Every day</b>	Run spa according to recommendations supplied to you by the manufacturer of your spa.
------------------	---

---

<b>Before each use</b>	Test the water with Nature <sup>2</sup> Spa Test Strip (or equivalent). If the MPS <sup>^</sup> level is low, add 1 tablespoon of MPS <sup>^</sup> to spa per 1000 litres. <b>Note:</b> 1 tablespoon is approximately 16 grams. Use the Nature <sup>2</sup> Spa Test Strip (or equivalent) to test the spa water after each addition of MPS <sup>^</sup> . If the test strip indicates levels below the OK range, add 1 tablespoon MPS <sup>^</sup> to spa per 1000 litres and re-test. Enter spa only after test strip indicates a sufficient level of MPS <sup>^</sup> .
------------------------	---

---

<b>After each use</b>	Add 1 tablespoon of MPS <sup>^</sup> to spa per 1000 litres.
-----------------------	--

---

<b>Once per week</b>	Adjust the pH, total alkalinity, and hardness as needed. A convenient way to test pH and total alkalinity is the Nature <sup>2</sup> Spa Test Strip.
----------------------	--

---

<b>Every 4 months</b>	Drain and refill your spa. Replace Nature <sup>2</sup> Spa and repeat sanitizer start-up.
-----------------------	---

---

**When:      What to do:**

---

**As needed** Shock treat with 1.5 tablespoons of an approved source of dichlor\* per 1000 litres to remedy problems which may occur when bathing loads are high, when successive MPS^ test strip reading indicate high demand, when water appears hazy or dull, when unpleasant odors or eye irritation occur, after heavy wind and rainstorms or if foam develops.

---

**Note:** As an alternative to MPS^, an approved source of dichlor\* may be substituted: 1 tablespoon dichlor\* = approximately 3 tablespoons MPS^.

**Important: Perform start-up procedures for spas which have been unused or unattended. The Nature<sup>2</sup> Spa is not to be used with copper based algaecides or biguanides. If these products are being used, DRAIN AND REFILL SPA WITH FRESH WATER.**

## Provide Filtration / Circulation

**To manage:      You need to:**

**Circulation**      Follow the manufacturer's directions for keeping the circulating pump in good working order and operate it at least four hours a day. Consult your Nature<sup>2</sup> Spa dealer for optimum run times.

**Filtration**      Check the spa filter periodically and clean it as recommended by the manufacturer.

\* Sodium dichloroisocyanurate dihydrate

^ Potassium monopersulphate

\*\* MPS may cause a lowering of the pH and total alkalinity of your spa water. Please monitor pH and total alkalinity at least once per week and adjust accordingly.

~ Nature<sup>2</sup> Spa Test Strips are available at your local Zodiac Nature<sup>2</sup> Dealer. The use of silver test strips is also recommended please consult your local pool professional.

## Spa Replacement Intervals

Use the month indicator decal to identify the date on which the cartridge should be replaced.

Always turn spa off prior to installing or changing Nature<sup>2</sup> Spa. Your spa is operated under pressure and the pressure must be released before you begin work. Please see your spa owner's manual for further instructions.

A cartridge lasts four (4) months. The cartridge should not be used longer than four (4) months.

## Disposal

After four months of use, discard Nature<sup>2</sup> Spa in household trash. Do not save the cartridge for re-use. The cartridge is manufactured with the mineral media sealed inside. In the unlikely event a cartridge breaks, remove it and vacuum out any media introduced into the spa.

# Nature<sup>2</sup> Spa Warranty

We do not exclude or limit the application of any provision of any statute (including the Trade Practices Act 1974) where to do so would contravene that statute or cause any part of this clause to be void.

We exclude:

- all conditions, warranties and terms implied by statute, general law or custom, except any implied condition or warranty the exclusion of which would contravene any statute or cause this clause to be void;
- all liability for consequential or indirect damages arising out of or in connection with Nature<sup>2</sup> Spa even if we knew they were possible or they were otherwise foreseeable, including without limitation lost profits and damage suffered as a result of claims by any third party; and
- all liability in negligence for our acts or omissions, or the acts or omissions of our employees, agents and contractors arising out of or in connection with Nature<sup>2</sup> Spa.

Our liability for breach of any warranty (except where the limitation of a warranty is prohibited by law) is limited at our option to the replacement of the goods or the supply of equivalent goods, the repair of the goods, the payment of the cost of replacing the goods or of acquiring equivalent goods or the payment of the cost of having the goods repaired.

## **ADDITIONAL WARRANTY**

Nature<sup>2</sup> Spa is warranted to be free of defects in materials at the time of purchase. Subject to the exclusions set out below. Nature<sup>2</sup> Spa is also warranted to perform satisfactorily for a period of four months from the date of purchase and not to cause staining in your spa. This additional warranty does not cover discoloration to chromium fittings and does not cover cartridges used with any biguanide products such as BaquaSpa<sup>^^</sup>, Baquacil<sup>^^</sup>. If the cartridge is defective and does not perform satisfactorily for the entire four months, we will replace the cartridge.

## **EXCLUSIONS FROM THE ADDITIONAL WARRANTY**

Nature<sup>2</sup> Spa is designed for use in residential portable spas up to 2000 litres. If it is used in any other application, the additional warranty is void, and the purchaser and/or spa owner releases the manufacturer from any and all claims related to the use of the Nature<sup>2</sup> Spa. The warranty is also void if you fail to exercise reasonable care in maintaining your spa or fail to keep water in balance at all times.

## **TO SUBMIT A CLAIM**

Report claims to Zodiac Group Australia, by calling 1800 688 552. Only the original purchaser may submit a claim under this warranty. Claims must be accompanied by an original purchase receipt.

<sup>^^</sup> Trademark of Arch Chemicals, Inc.

# Troubleshooting

	Problem	What to look for
<b>Cloudy water</b> Frequently caused by improper start up. See section on Start Up and Install the Cartridge.	Spa filtration	Slow filter turnover rates
	Algae growth	Hazy spa water; may have slightly green appearance.
	Unbalanced water	1. High hardness 2. High TDS (total dissolved solids) 3. High pH 4. High total alkalinity
<b>Algae</b> Algae may be caused by insufficient levels of oxidizer and/or inadequate water circulation.	Green or white algae	Pea green to white colour; attaches to spa walls, sometimes colours the entire body of water.  Note: Do not use algae treatments containing copper.
<b>Stains</b>	Blue/green	Copper or iron from spa equipment corrosion or water supply
	Red/brown	Iron or manganese from equipment corrosion or water supply.
	Black	Manganese in water supply.
	Metal tarnishing	High native mineral content in water; unbalanced water
<b>Scale</b>	Crusty deposits on spa surfaces	High pH and high total alkalinity  High TDS (total dissolved solids) or high hardness

## Treatment

---

- 1 Backwash and clean filter.
  - 2 Run filter for 24 hours.
  - 3 Increase run time per day.
- 

Superchlorinate water with an approved source of dichlor\* according to manufacturer's instructions.

---

Balance the spa water.

---

- 1 Check pH and adjust if necessary
  - 2 Superchlorinate water with an approved source of dichlor\* according to manufacturer's instructions.
  - 3 Repeat steps 1 and 2 until algae is gone.
- 

- 1 Adjust pH and total alkalinity to ideal ranges.
  - 2 Vigorously brush stained areas.
  - 3 Add sequestrant.
  - 4 Run filter.
  - 5 Twelve hours later, superchlorinate the spa.
  - 6 Test and balance water.
  - 7 Test spa water for dissolved metals.
- 

Clean with soft cloth and mild detergent.  
Test water for minerals; use a sequestrant;  
maintain water balance.

---

Adjust pH and total alkalinity to ideal ranges.

---

- 1 Replace a volume of spa water with water low in hardness and dissolved solids.
- 2 Use sequestrant to prevent scale buildup if high hardness is a continuing problem.
- 3 If remedial action has been taken, and problem still persists, drain and refill spa.

# Nature<sup>2</sup> Spa Test Strips



**Just dip and swirl the Test Strip.**

**See accurate and reliable results on the levels of MPS<sup>^</sup>, Alkalinity and pH in your spa's water.**

**Now available at your local Zodiac Nature<sup>2</sup> Dealer**



**Fluidra Group Australia PTY LTD**  
219 Woodpark Road, Smithfield,  
NSW 2164  
Tel: 1300 763 021  
Fax: 1300 781 688  
[www.zodiac.com.au](http://www.zodiac.com.au)

Nature<sup>2</sup> is a registered trademark  
of Zodiac Pool & Marine  
© 2007 Zodiac Pool Care, Inc.  
All rights reserved.  
TL-2700 6/07